










LOC	DIST	REVISIONS					
AD	00	P	LTR	DESCRIPTION	DATE	DWN	APVD
			—	SEE SHEET 1	—	—	—

	101.19 [3.984]	99.06 [3.900]	39	80	9-146509-0
	98.65 [3.884]	96.52 [3.800]	38	78	8-146509-9
	96.11 [3.784]	93.98 [3.700]	37	76	8-146509-8
	93.57 [3.684]	91.44 [3.600]	36	74	8-146509-7
	91.03 [3.584]	88.90 [3.500]	35	72	8-146509-6
	88.49 [3.484]	86.36 [3.400]	34	70	8-146509-5
	85.95 [3.384]	83.82 [3.300]	33	68	8-146509-4
	83.41 [3.284]	81.28 [3.200]	32	66	8-146509-3
	80.87 [3.184]	78.74 [3.100]	31	64	8-146509-2
	78.33 [3.084]	76.20 [3.000]	30	62	8-146509-1
	75.79 [2.984]	73.66 [2.900]	29	60	8-146509-0
	73.25 [2.884]	71.12 [2.800]	28	58	7-146509-9
	70.71 [2.784]	68.58 [2.700]	27	56	7-146509-8
	68.17 [2.684]	66.04 [2.600]	26	54	7-146509-7
	65.63 [2.584]	63.50 [2.500]	25	52	7-146509-6
	63.09 [2.484]	60.96 [2.400]	24	50	7-146509-5
	60.55 [2.384]	58.42 [2.300]	23	48	7-146509-4
	58.01 [2.284]	55.88 [2.200]	22	46	7-146509-3
	55.47 [2.184]	53.34 [2.100]	21	44	7-146509-2
	52.93 [2.084]	50.80 [2.000]	20	42	7-146509-1
	50.39 [1.984]	48.26 [1.900]	19	40	7-146509-0
	47.85 [1.884]	45.72 [1.800]	18	38	6-146509-9
	45.31 [1.784]	43.18 [1.700]	17	36	6-146509-8
	42.77 [1.684]	40.64 [1.600]	16	34	6-146509-7
	40.23 [1.584]	38.10 [1.500]	15	32	6-146509-6
	37.69 [1.484]	35.56 [1.400]	14	30	6-146509-5
	35.15 [1.384]	33.02 [1.300]	13	28	6-146509-4
	32.61 [1.284]	30.48 [1.200]	12	26	6-146509-3
	30.07 [1.184]	27.94 [1.100]	11	24	6-146509-2
	27.53 [1.084]	25.40 [1.000]	10	22	6-146509-1
	24.99 [.984]	22.86 [.900]	9	20	6-146509-0
	22.45 [.884]	20.32 [.800]	8	18	5-146509-9
	19.91 [.784]	17.78 [.700]	7	16	5-146509-8
	17.37 [.684]	15.24 [.600]	6	14	5-146509-7
	14.83 [.584]	12.70 [.500]	5	12	5-146509-6
	12.29 [.484]	10.16 [.400]	4	10	5-146509-5
	9.75 [.384]	7.62 [.300]	3	8	5-146509-4
	7.21 [.284]	5.08 [.200]	2	6	5-146509-3
	4.67 [.184]	2.54 [.100]	1	4	5-146509-2
	2.13 [.084]	- -	-	2	5-146509-1
PLATING	G	F	E	NO. OF POSITIONS	P

5	101.19 [3.984]	99.06 [3.900]	39	80	4-146509-0
5	98.65 [3.884]	96.52 [3.800]	38	78	3-146509-9
5	96.11 [3.784]	93.98 [3.700]	37	76	3-146509-8
5	93.57 [3.684]	91.44 [3.600]	36	74	3-146509-7
5	91.03 [3.584]	88.90 [3.500]	35	72	3-146509-6
5	88.49 [3.484]	86.36 [3.400]	34	70	3-146509-5
5	85.95 [3.384]	83.82 [3.300]	33	68	3-146509-4
5	83.41 [3.284]	81.28 [3.200]	32	66	3-146509-3
5	80.87 [3.184]	78.74 [3.100]	31	64	3-146509-2
5	78.33 [3.084]	76.20 [3.000]	30	62	3-146509-1
5	75.79 [2.984]	73.66 [2.900]	29	60	3-146509-0
5	73.25 [2.884]	71.12 [2.800]	28	58	2-146509-9
5	70.71 [2.784]	68.58 [2.700]	27	56	2-146509-8
5	68.17 [2.684]	66.04 [2.600]	26	54	2-146509-7
5	65.63 [2.584]	63.50 [2.500]	25	52	2-146509-6
5	63.09 [2.484]	60.96 [2.400]	24	50	2-146509-5
5	60.55 [2.384]	58.42 [2.300]	23	48	2-146509-4
5	58.01 [2.284]	55.88 [2.200]	22	46	2-146509-3
5	55.47 [2.184]	53.34 [2.100]	21	44	2-146509-2
5	52.93 [2.084]	50.80 [2.000]	20	42	2-146509-1
5	50.39 [1.984]	48.26 [1.900]	19	40	2-146509-0
5	47.85 [1.884]	45.72 [1.800]	18	38	1-146509-9
5	45.31 [1.784]	43.18 [1.700]	17	36	1-146509-8
5	42.77 [1.684]	40.64 [1.600]	16	34	1-146509-7
5	40.23 [1.584]	38.10 [1.500]	15	32	1-146509-6
5	37.69 [1.484]	35.56 [1.400]	14	30	1-146509-5
5	35.15 [1.384]	33.02 [1.300]	13	28	1-146509-4
5	32.61 [1.284]	30.48 [1.200]	12	26	1-146509-3
5	30.07 [1.184]	27.94 [1.100]	11	24	1-146509-2
5	27.53 [1.084]	25.40 [1.000]	10	22	1-146509-1
5	24.99 [.984]	22.86 [.900]	9	20	1-146509-0
5	22.45 [.884]	20.32 [.800]	8	18	146509-9
5	19.91 [.784]	17.78 [.700]	7	16	146509-8
5	17.37 [.684]	15.24 [.600]	6	14	146509-7
5	14.83 [.584]	12.70 [.500]	5	12	146509-6
5	12.29 [.484]	10.16 [.400]	4	10	146509-5
5	9.75 [.384]	7.62 [.300]	3	8	146509-4
5	7.21 [.284]	5.08 [.200]	2	6	146509-3
5	4.67 [.184]	2.54 [.100]	1	4	146509-2
5	2.13 [.084]	—	—	2	146509-1
PLATING	G	F	E	NO. OF POSITIONS	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWG. P. BROWN	190CT2006	 TE Connectivity	
		CHK. J. GEFORD	190CT2006		
DIMENSIONS: mm [INCHES]		TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ± 0.5[.005] 2 PLC ± 0.13[.005] 4 PLC ± — ANGLES ± — FINISH SEE TABLE		NAME HEADER ASSEMBLY, MOD II, STACKING, DOUBLE ROW, .025 SUB.POST, UNSHROUDED	
		APD. J. GEFORD PRODUCT SPEC APPLICATION SPEC	SIZE A1	CASE CODE 00779	DRAWING NO. 146509
MATERIAL 		WEIGHT —	RESTRICTED TO —		
CUSTOMER DRAWING		SCALE 4:1		SHEET 2 OF 2	REV A1

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[6-146509-7](#)