



TSM SERIES

IDSS, IDSD

RoHS Compliant: Yes

Note:
Some lengths, styles and options are non-standard, non-returnable.

OTHER OPTIONS

= Matte Tin

-SH & -DH

–SV: 02-22 positions, –DV:02-28 positions,
–SH: 02-30 positions, –DH: 02-29 positions
(Not available with –MT or –TM)

Figure 1: Dimensions for the design of a 10-pin connector. The figure shows three views: a top view, a side view, and a detail view of the pin assembly. The top view shows a rectangular connector with 10 pins, labeled 01 to 02 and 71 to 72. Dimensions include a total width of (2.54) .100 x No. of positions, a pin pitch of (0.64) .025, and a total length of (7.87) .310. The side view shows the pin height of (2.54) .100 and the total height of (6.10) .240. The detail view shows the pin diameter of (0.16) .046 and the post height of (1.52) .060.

*All parts within this catalog are built to Samtec's specifications.
Customer specific requirements must be approved by Samtec and identified in a Samtec customer-specific drawing to apply.*

*All parts within this catalog are built to Samtec's specifications.
Customer specific requirements must be approved by Samtec and identified in a Samtec customer-specific drawing to apply.*

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Samtec:](#)

[TSM-103-02-S-SH-A-TR](#)