

4		3		2		1			
THIS DRAWING IS UNPUBLISHED.				RELEASED FOR PUBLICATION ,19 .					
© COPYRIGHT 19				BY AMP INCORPORATED. ALL RIGHTS RESERVED.					
LOC		DIST		REVISIONS					
G		86		P	LTR	DESCRIPTION	DATE	DWN	APVD
					C	REVISED PER 0L20-0260-97	22DEC97	DKS	MJS

BODY

INSERT


BRAZED SEAM

6.55
[.258]
MAX DIA


3.15
[.124]
MIN DIA

9.53
[.375]
MAX

AMP
12-10
AL-CU



BODY: COPPER PER ASTM B-152 TIN PL 0.00254[.000100] MIN THK PER ASTM B-545 INSERT: BRASS PER MIL-C-50 TIN PL 0.00254[.000100] MIN THK PER ASTM B-545	52792
MATERIAL & FINISH	AMP PART NUMBER

AMP INCORPORATED CUSTOMER SERVICE SYSTEMS			THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN DK SCHRUM 22DEC97		AMP Incorporated Harrisburg, PA 17105-3608		
FOR ADDITIONAL PRODUCT INFORMATION OR COPIES OF DRAWINGS AND TECHNICAL DOCUMENTS	PRODUCT INFORMATION CENTER 1-800-522-6752	RECOMMENDED OPERATING TEMPERATURE: 170°C MAX	DIMENSIONS: mm [INCHES]		TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ±- 1 PLC ±- 2 PLC ±0.20[.008] 3 PLC ±- 4 PLC ±- ANGLES ±5°	CHK MJ SPICER 23DEC97		NAME SPLICE, PARALLEL, STRANDED/SOLID, COPALUM™, WIRE SIZE: 12-10 AWG	
		VOLTAGE RATING: NOT APPLICABLE				APVD JL MECKLEY 23DEC97			
FOR APPLICATION TOOLING INFORMATION	TOOLING ASSISTANCE CENTER 1-800-722-1111	WIRE CROSS SECTIONAL AREA RANGE: 2.62-6.64mm² [5,180-13,100] CIR MILS SOLID/STRANDED	MATERIAL SEE TABLE	FINISH SEE TABLE	PRODUCT SPEC -		SIZE A300779		RESTRICTED TO -
FOR ORDER ENTRY	1-800-526-5142				APPLICATION SPEC -		DRAWING NO C- 52792		
CUSTOMER DRAWING					SCALE 4:1		SHEET 1 OF 1		REV C

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[52792](#)