



NOTE:

- MATERIAL: MEDIUM DENSITY, CLOSED CELLULAR NEOPRENE SPONGE, APPROX. 50-70 DUROMETER. BLACK COLOR
- SURFACES INDICATED BY THIS DIMENSION TO HAVE NO SKIN (BOTH SIDES) AND MAY HAVE A WAFFLED FINISH OF MIN DEPTH.

SOURCE: SEAL RING'S  
OR ENG'R APPROVED EQUAL

NO	COMPONENT NO	DESCRIPTION	QTY/M	U/M
----	--------------	-------------	-------	-----

**BILL OF MATERIAL**

UNLESS OTHERWISE SPECIFIED, DIMENSIONS DO NOT INCLUDE PLATING.

O	DENOTES CRITICAL CHARACTERISTICS.
CPK	DENOTES CPK DIMENSIONS, -MINIMUM CPK VALUE 1.33
ST	DENOTES A CHARACTERISTIC THAT PROVIDES AN INDICATION OF PROCESS PERFORMANCE. PROCEDURE FOR MEASUREMENT AND TRACKING TO BE DEFINED IN LITTELFUSE INSPECTION INSTRUCTIONS.
CP	DENOTES CP DIMENSIONS, -MINIMUM CP VALUE MUST BE WITHIN THE DIMENSIONAL LIMITATIONS SHOWN ON DRAWING AND INITIALLY LOCATED TO ALLOW FOR MAXIMUM TOOL LIFE.

LTR		REVISION	CHK	APD
F	G			
39212C - REVISED & REORAIN ON NEW FORMAT 6/12/98 JMB	39313D - CHG. TITLE 7/27/98 BJJ			

COPIES TO		MATL SPEC	FINISH	
1	9 18	DRW KAM	DATE 4/8/98	SCALE 4:1
2	10 19	CHK	DATE	SUPER DRW
3	12 20	APPD	DATE	RAW STK WT
4	13 21	TOLERANCE UNLESS OTHERWISE SPECIFIED		
5	14 23	TWO PLACE DEC ±.01	FRACTIONAL	
6	15 33	THREE PLACE DEC ±.005	ANGULAR	
7	16 43	TITLE WASHER RUBBER		
8	17 53	REVISION DRWG. NO.		

CAD GENERATED DRAWING - NO PENCIL CHANGES ALLOWED

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Littelfuse:](#)

[901-124](#)