

HEAT SINK: ALUMINUM BLACK PEI (UL94-VO)

2. BEFORE THE HEATSINK APPLICATION, THE USER SHOULD IDENTIFY THE SPECIFICATION OF MAXIMUM LOAD ON

SCREW DRIVER SLOT (.070 WIDE X .100 DEEP)PROVIDED IN THE CENTER PORTION OF THE HEAT SINK. FOR ACCURATE TORQUE SETTING, SCREW DRIVER BIT MUST BE ALIGNED TO THE CENTER LINE OF THE HEAT SINK.

HEATSINK TORQUE SPECIFICATIONS CONVERTED TO FORCE.

2.0 POUND-FORCE INCH TORQUE = 8.1 POUND-FORCE (0.23 NEWTON METER TORQUE = 36.03 NEWTON)2.5 POUND-FORCE INCH TORQUE = 10.1 POUND-FORCE (0.28 NEWTON METER TORQUE = 44.93 NEWTON)

FULL SIZE LID PACKAGE:

2.0 POUND-FORCE INCH TORQUE = 6.9 POUND-FORCE (0.23 NEWTON METER TORQUE = 30.69 NEWTON)2.5 POUND-FORCE INCH TORQUE = 8.7 POUND-FORCE (0.28 NEWTON METER TORQUE = 38,70 NEWTON) 3. REMOVE CLIP WITH REMOVAL TOOL P/N: 1542616-1 4. RoHS COMPLIANT AND CERTIFIED.

TABLE 2						
DESCRIPTION Ø "B" DIM "A"						
HS, I"	THRD.	2	FINS	1.375	. 440	
HS, I"	THRD,	3	FINS	1.375	. 540	
HS, I"	THRD,	4	FINS	I.375	. 640	
HS, I"	THRD,	5	FINS	1.375	.740	
HS, I"	THRD,	7	FINS	1.375	. 940	
HS, I"	THRD.	2	FINS	2.000	. 440	
HS, I"	THRD.	3	FINS	2.000	. 540	
HS, I"	THRD.	4	FINS	2.000	.640	
HS, I"	THRD.	5	FINS	2.000	.740	
HS, I"	THRD.	7	FINS	2.000	. 940	

)	Confidential property of Electronics. Not to be disc to others, reproduced or u any purposes except as aut	CLOSED SED FOR	ASSEMBLY					
	IN WRITING BY AN AUTHORIZED OFFICIAL OF TYCO ELECTRONICS. MUST BE RETURNED TO TYCO ELECTRONICS ON DEMAND, ON COMPLETION OF ORDER OR OTHER PURPOSES FOR WHICH LENT.		HEATSINK WITH					
			4 LEGS, 32.5mm CLIP					
	DIMENSIONS ARE IN: INCHES	SCALE:	TE PART NO.: SHEET SEF TABLE 2 1011					
	INCHES	6,1						
	THIRD ANGLE	SIZE	DWG. NO.: REV.					
	PROJECTION O +-+	В	C-1963557 BI					

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TE Connectivity: <u>1-1963557-5</u>