

1 2 3 4 5 6 7

A

B

C

D

E

F

G

H

Recommended P.C.B Layout(Top Side)
(PCB BOARD TOLERANCE±0.05)

Dimensions:
 2,54±0,10
 2,54xNo.of Positions-2,54±0,20
 2,54xNo.of Positions+5,32±0,25
 2,54xNo.of Positions+7,62±0,30
 2,54±0,15
 6,50±0,15
 8,80±0,15

Dimensions:
 2,54
 1,02
 4,50
 10,50

NOTES:

MATERIAL

⑨ 1.Insulator Material:PA9T+30%GF(UL94V-0),Black
 2.Contact Material : Brass
 3.Contact Plating : Gold flash

ELECTRICAL

1.Current Rating : 3.0AMP
 2.Withstand Voltage : 1000V AC/minute
 3.Contact Resistance : 20mΩ max
 4.Insulation Resistance: 1000MΩ min

ENVIRONMENTAL

1.Operation Temperature: -40°C to +105°C
 2.Packing: Tube+Cap

⑤ 3. Soldering temperature: +260°C(10s)

Order Information

⑩ Contacts xx: 06,08,10,12,14,16,18,20,24
 26,30,34,40,50,60,64

Dimensions:
 10,00
 5,90
 2,54±0,10
 9,00±0,15
 SQ 0,64
 CAP ⑥

Dimensions:
 9,00
 10,50
 1,00±0,25
 9,50±0,25
 0,15

RoHS compliant

⑦
 File No.: E198287

Scale	Free	⑩	Add 40pin	30.11.2018	Xavier		Date	Name	Customer-No.
TOLERANCE		⑨	Correct the material to PA9T	22.03.2016	Winnie	Drawn	25.01.2006	Alex	ASSMANN WSW-No. ⑧ AWHW xxG-SMD
X.X	±0.40	⑧	Update the correct part number	11.02.2014	Winnie	Approved	22.03.2016	Winnie	
X.XX	±0.25	⑦	Add UL-File No	12.12.2013	Amy				Drawing-No. ASS 2316 CO rev10
X.XXX	±0.15	⑥	Modification the cap	07.11.2012	Amy				
Angle	±3°	⑤	add soldering temperature	09.12.2011	Lucas				Replace Sheet
		Id.	Modification	Date	Name				

1 2 3 4 5 6 7

SV1129