



注記

1. 嵌合相手 : 51006  
MATE WITH : 51006
2. 適合ターミナル : 50013  
APPLICABLE TERMINAL : 50013
3. 製品番号表記例  
MATERIAL NO.  
51005 - \*\*0\*  

極数	色	自然色 (白)	0
CIRCUIT	COLOR	NATURAL	
		黒	1
		BLACK	
		赤	2
		RED	
4. ELV 及び RoHS適合品  
ELV AND RoHS COMPLIANT.

10.6	8.6	6	51005-0402	4
6.6	4.6	2	51005-0202	2
C	B	A	MATERIAL NO.	極数
色 : 赤 / COLOR : RED				
6.6	4.6	2	51005-0201	2
C	B	A	MATERIAL NO.	極数
色 : 黒 / COLOR : BLACK				
12.6	10.6	8	51005-0500	5
10.6	8.6	6	↑ -0400	4
8.6	6.6	4	↓ -0300	3
6.6	4.6	2	51005-0200	2
C	B	A	MATERIAL NO.	極数
色 : 自然色 (白) / COLOR : NATURAL (WHITE)				

MATERIAL  
PBTP (UL94V-0)

REVISED EC NO: J2008-2082 DRWN: MNABEI 2007/11/22 CHKD: KTOYODA 2007/11/26 APPR: NUKITA 2007/11/27	DESCRIPTION	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY		SCALE 5:1	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION	
		10 UNDER	±0.3	DRAWN BY K. SETO	DATE '04/04/27	TITLE 2.0 WIRE TO WIRE CONN. RECEPTACLE HOUSING			
		10 OVER 30 UNDER	±0.4	CHECKED BY H. TAKASE	DATE '04/04/27				
		30 OVER	±0.5	APPROVED BY J. MIYAZAWA	DATE '04/04/27				
		ANGULAR ±--- °		MATERIAL NO. SEE TABLE		DOCUMENT NO. SD-51005-001		SHEET NO. 1 OF 1	
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		SIZE A3	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION						

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Molex:](#)

[51005-0201](#)