



Part Number: 8500

Lead Wire, #16 Str TC, PVC Ins, TYPE B MIL-W-16878/1 600V 105C

Request Sample

Product Description

Low Temp Plastic Lead Wire, 16AWG (19x29) Tinned Copper, PVC Insulation, TYPE B MIL-W-16878/1 600V 105C

Technical Specifications

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	N	lo. of Conductors
16	19x29	TC - Tinned Co	pper 1	
Condu	uctor Count:	1		
Condu	uctor Size:	16	AWG	

Insulation

Material	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.079 in	0.01 in

Outer Jacket Material



Electrical Characteristics

Voltage

Voltage Rating [V] 600 V

Temperature Range

Non-UL Temp Rating: 105°C

Mechanical Characteristics

Bulk Cable Weight: 10 lbs/1000ft

Standards

UL AWM Style:	N/A
Military Specification:	MIL-W-16878/1

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes

EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2006-04-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Flammability, LS0H, Toxicity Testing

UL voltage rating:	N/A				
--------------------	-----	--	--	--	--

Plenum/Non-Plenum

Plenum (Y/N):	No			

Part Number

Variants

Item #	Color	Footnote			
8500 010100	Black				
8500 0101000	Black	Р			
8500 006100	Blue, Light				
8500 0061000	Blue, Light	Р			
8500 0011000	Brown	Р			
8500 0081000	Gray	Р			
8500 005100	Green, Dark				
8500 0051000	Green, Dark	Р			
8500 0031000	Orange	Р			
8500 002100	Red				
8500 0021000	Red	Р			
8500 0071000	Violet	Р			
8500 009100	White				
8500 0091000	White	Р			
8500 0141000	White, Black Stripe				
8500 0181000	White, Blue Stripe	А			
8500 0191000	White, Brown Stripe	А			
8500 0161000	White, Green Stripe	А			
8500 0201000	White, Orange Stripe	А			
8500 0151000	White, Red Stripe	Α			
8500 0171000	White, Yellow Stripe	А			
8500 004100	Yellow				
8500 0041000	Yellow	Р			

Footnote:	P - STRIPE COLORS ON STOCK SOLID COLORS. STRIPING ADDER OF \$8.00/M= FOR 1 OR 2 STRIPES. 10,000' MINIMUM ORDER FOR COLOR COMBINATION. PUT-UP WILL BE SUBJECT TO TWO PIECES (+ OR -) 10% PER SPOOL, WITH A MINIMUM LENGTH OF 100'.
Footnote:	A - STOCKED STRIPE COLORS.

© 2019 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.