

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

0782342033

Status:

Active

Overview:

GbX I-Trac Backplane Connector System

Description:

GbX I-Trac Right-Angle Header with Right Hold Down, Power Module, 4 Blades, 80 Amps, 2 Ganged Modules, Lead-Free

Documents:

3D Model

Application Specification AS-78231-007-001 (PDF)

Drawing (PDF)

Packaging Specification PK-78234-001 (PDF)

Product Specification PS-78231-006-001 (PDF)

RoHS Certificate of Compliance (PDF)

Agency Certification

CSA	LR19980
UL	E29179


General

Product Family	Backplane Connectors
Series	78234
Application	Daughtercard
Component Type	Power Header
Overview	GbX I-Trac Backplane Connector System
Product Name	GbX I-Trac
UPC	883906913212

Physical

Circuits (Loaded)	4
Circuits (maximum)	4
Circuits Detail	80 Amps (40/Split Blade). Power Module 1: Blade Length P1, 6.77mm; P2, 9.77mm. Power Module 2: Blade Length P1, 6.77mm; P2, 9.77mm

Color - Resin	Black
Durability (mating cycles max)	100
First Mate / Last Break	Yes
Flammability	94V-0
Guide to Mating Part	No
Keying to Mating Part	None
Material - Metal	High Performance Alloy (HPA)
Material - Plating Mating	Gold
Material - Plating Termination	Tin
Material - Resin	High Temperature Thermoplastic
Number of Columns	1
Number of Pairs	6
Number of Rows	2
Orientation	Right Angle
PC Tail Length	2.41mm
PCB Locator	Yes
PCB Retention	Yes
PCB Thickness - Recommended	1.60mm
Packaging Type	Tray
Pitch - Mating Interface	2.00mm, 7.40mm
Pitch - Termination Interface	2.00mm, 7.40mm
Plating min - Mating	0.762µm
Plating min - Termination	2.540µm
Polarized to PCB	Yes
Stackable	No
Surface Mount Compatible (SMC)	Yes
Temperature Range - Operating	-20° to +85°C



Series image - Reference only

EU ELV

Not Relevant

EU RoHS

Not Relevant

China RoHS

REACH SVHC

Not Relevant

Halogen-Free

Status

Not Relevant

For more information, please visit [Contact US](#)

China ROHS	Not Relevant
ELV	Not Relevant
RoHS Phthalates	Not Relevant

Search Parts in this Series

78234 Series

Mates With

78232 GbX I-Trac Vertical Receptacle, Power Module, 78235 GbX I-Trac Power Right Angle Receptacle

Use With

75710 GbX I-Trac Right Angle, 11 Row Receptacle Module

Application Tooling | FAQ

Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.

Global

Description	Product #
Press-in Tool for Right-Angle Power Receptacle and Header for 11-Row	622018628

Termination Interface: Style	Through Hole - Compliant Pin
Electrical	
Current - Maximum per Contact	80.0A
Data Rate	12.0 Gbps
Shield Type	N/A
Shielded	No
Voltage - Maximum	250V DC
Material Info	
Reference - Drawing Numbers	
Application Specification	AS-78231-007-001
Packaging Specification	PK-78234-001
Product Specification	PS-78231-006-001
Sales Drawing	SD-78234-003

This document was generated on 02/01/2019

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Molex:](#)

[78234-2033](#)