






| NO. | MASSE / DIMENSION |
|-----|-------------------|
| A   | 1 1/4-18NEF-2A    |
| B1  | 15.9              |
| B2  | -                 |
| C   | 19                |
| D   | 4                 |
| E   | 68                |
| F   | 37.7              |
| G   | 32.1              |

| NO. | BESCHREIBUNG / DESCRIPTION          |
|-----|-------------------------------------|
| 1   | ISOLIERKÖRPER STIFT / INSULATOR PIN |
| 3   | DICHTKÖRPER / GROMMET               |
| 4   | ENDRING / ENDRING                   |
| 5   | KONTAKTSTIFT/ CONTACT PIN           |
| 8   | DOSENGEHÄUSE / SHELL                |
| 12  | ENDGEHÄUSE / ENDBELL                |



Note: Due to an automatic nomenclature system, numbers generated may not be sequential.

Specification and Dimensions subject to change  
Drawings illustrate normal insulator positioning

|                                |                                                  |
|--------------------------------|--------------------------------------------------|
| <b>Material Specification:</b> |                                                  |
| Shell Material:                | Aluminium alloy                                  |
| Shell Plating:                 | Olive drab chromate coating over cadmium plating |
| Insulator Material:            | Neoprene                                         |
| Contact Material:              | Copper alloy                                     |
| Contact Plating:               | Hard silver                                      |

all dimensions are in mm  
Dimensions without tolerance indications are general tolerances in acc. with DIN7168m

drawing for  
CUSTOMER



description **CA3101E20-27P-F80**  
Cable connecting plug  
Endbell with clamp and bushing  
AWG Crimp / Pin / Layout: 20-27

© All rights reserved. Reproduction or issue to third in any form  
whenever is only permitted with written authorization of ITT Cannon



page 1/1  
revision 1041 28. Oct 20