Level V IDC Connectors, .125 x .125 [3.18 x 3.18] Centerline

Product Facts

- **Termination of discrete wire sizes 26-22 AWG [0.12-0.3 mm²] as well as jacketed cable and bonded ribbon cable (conductors separated)**
- **Connectors stackable end-to-end and side-to-side on .125 [3.18] centers**
- **Connectors preloaded with insulation displacement receptacle contacts**
- **Contact design employs dual cantilever beams, redundant insulation displacement slots, built-in post stop and wire support crimp**
- **Copper alloy contacts are duplex plated**
- **Snap-on covers with or without cable tie paddles**
- **Full line of mass termination tooling offers lowest installed costs for most production needs**
- **Recognized under the Component Program of Underwriters Laboratories Inc., File No. E28476**
- **Certified by Canadian Standards Association, File No. LR 7189**



AMPMODU Level V IDC connectors provide cost effective discrete wire connections that are compatible with today's telecommunications packaging techniques. These connectors are designed to mate with .025 [0.64] sq. posts on .125 x .125 [3.18 x 3.18] centers and are comprised of double-row housings preloaded with insulation displacement receptacle contacts, snap-on hermaphroditic covers, and a full line of mass termination tooling to meet virtually every production need. For modular flexibility, connectors can be stacked end-to-end or side-to-side, maintaining a .125 x .125 [3.18 x 3.18] centerline spacing.

Covers can be furnished with and without a cable tie paddle. The covers are simply snapped onto a housing after the connector has been terminated.

The receptacle contacts feature the Tyco Electronics insulation displacement crimp technique for achieving top quality, low cost terminations. These contacts employ dual cantilever beams for redundant interface with a mating post, an integral post stop to limit post mating depth and protect the crimp termination, and a wire support (strain relief) crimp to prevent accidental wire pull-out. The contacts are made of high conductivity copper alloy and are duplex plated.

Performance Characteristics

Contact Current Rating — 3 amperes

Termination Resistance — 12 milliohms (max.)

Durability — Ref. Product Specification 108-25028 (Interconnection System, Insulation Displacement Connector, IDC Level)

Application Specification
114-25020 (Interconnection System, IDC Level V, Application of)

Catalog 1307819
Revised 8-08

www.tycoelectronics.com

Dimensions are in inches and millimeters unless otherwise specified. Values in brackets are metric equivalents.

Dimensions are shown for reference purposes only. Specifications subject to change.

USA: 1-800-522-6752
Canada: 1-905-470-4425
Mexico: 01-800-733-8926
C. America: 52-55-1106-0803

South America: 55-11-2103-6000
Hong Kong: 852-2735-1628
Japan: 81-44-844-8013
UK: 44-8706-080-208a

Receptacle Assemblies, Double-Row, .125 x .125 [3.18 x 3.18] Centerline

Housings Preloaded with Insulation Displacement Crimp Receptacle Contacts

Material and Finish

Housing — Black thermoplastic, flame retardant

Contacts — Copper alloy, duplex plated .000050 [0.00127] gold on contact area, .000100 [0.00254] min. tin in crimp area, with entire contact underplated .000050 [0.00127] nickel

Note: Preloaded contacts accept max. insulation dia. of .050 [1.27]. The minimum point of contact, as measured from front edge of housing, is .095 [2.41].

Technical Documents — pages 277, 278

Product Specification
108-25028

Application Specification
114-25020

Receptacle assemblies can be stacked end-to-end and side-to-side on .125 x .125 [3.18 x 3.18] centers.



No. of Pos.	Dimensions		Receptacle Assembly (Stamped[1]) for 26-22 AWG [0.12-0.3 mm²] Wire
	A	B	
8	**.493** [12.52]	**.375** [9.52]	102935-4
10	**.618** [15.70]	**.500** [12.70]	102935-6
12	**.743** [18.87]	**.625** [15.88]	102935-8
16	**.993** [25.22]	**.875** [22.23]	1-102935-2
20	**1.243** [31.57]	**1.125** [28.58]	1-102935-6
24	**1.493** [37.92]	**1.375** [34.93]	1-102935-9
30	**1.868** [47.45]	**1.750** [44.45]	1-102935-3
32	**1.993** [50.62]	**1.875** [47.63]	2-102935-8
40	**2.493** [63.32]	**2.375** [60.33]	3-102935-6

[1]White ink stamped, one side—8- thru 12-position with AMP and arrow; 14- and 16-position with AMP, part no., and arrow; 18- thru 40-position with AMP, part no., date code and arrow.

Notes: 1. Covers for these housings are shown on pages 281 & 282.
2. Termination tooling for these connectors are shown on page 273-275.
3. 14- and 18-position receptacle assemblies, as well as other sizes, can be made available upon request. Consult Tyco Electronics.

Note: All part numbers are RoHS compliant.

Catalog 1307819
Revised 8-08

www.tycoelectronics.com

Dimensions are in inches and millimeters unless otherwise specified. Values in brackets are metric equivalents.

Dimensions are shown for reference purposes only. Specifications subject to change.

USA: 1-800-522-6752
Canada: 1-905-470-4425
Mexico: 01-800-733-8926
C. America: 52-55-1106-0803

South America: 55-11-2103-6000
Hong Kong: 852-2735-1628
Japan: 81-44-844-8013
UK: 44-8706-080-208a

Hermaphroditic Covers for Level V IDC Receptacle Assemblies, Double-Row, .125 x .125 [3.18 x 3.18] Centerline

All covers illustrated here and on the following page can be used on the double-row Level V IDC connectors shown on page 280.

Material

Black thermoplastic, flame retardant, 94V-0 rated



Cover 103056 Series without Cable Tie Paddle



Cover 103058 Series with Cable Tie Paddle



Cover 103349 Series with Wide Cable Tie Paddle



Cover 103350 Series with Wide Cable Tie Paddle and Polarization

No. of Pos. (Housing Size)	Dimensions					Cover Part Nos.			
	A	B	C	D	E	Without Cable Tie Paddle	With Cable Tie Paddle	With Wide Cable Tie Paddle	With Wide Cable Tie Paddle and Polarization
8	**.491** [12.47]	**.150** [3.81]	**.285** [7.24]	**.166** [4.22]	**.125** [3.18]	—	—	103349-4	103350-4
10	**.616** [15.65]	—	—	—	**.125** [3.18]	—	103058-3	—	—
12	**.741** [18.82]	—	—	—	**.200** [5.08]	—	103058-4	—	—
16	**.991** [25.17]	**.300** [7.62]	**.592** [15.04]	**.416** [10.57]	—	—	—	103349-1	103350-1
20	**1.241** [31.52]	**.300** [7.62]	**.592** [15.04]	**.541** [13.74]	—	—	—	103349-5	103350-5
24	**1.491** [37.87]	—	—	—	**.400** [10.16]	1-103056-0	1-103058-0	—	—
32	**1.991** [50.57]	**.600** [15.24]	**1.312** [33.32]	**.916** [23.27]	—	—	—	103349-2	103350-2
40	**2.491** [63.27]	**.750** [19.05]	**1.820** [46.23]	**1.166** [29.61]	—	—	—	103349-3	103350-3
64	See page 282 for Double Cable Tie Paddle versions.								

Notes: 1. Two hermaphroditic covers of any style can be installed on a double-row connector housing.
2. Other sizes can be made available upon request.

Note: All part numbers are RoHS compliant.

Catalog 1307819
Revised 8-08

www.tycoelectronics.com

Dimensions are in inches and millimeters unless otherwise specified. Values in brackets are metric equivalents.

Dimensions are shown for reference purposes only. Specifications subject to change.

USA: 1-800-522-6752
Canada: 1-905-470-4425
Mexico: 01-800-733-8926
C. America: 52-55-1106-0803

South America: 55-11-2103-6000
Hong Kong: 852-2735-1628
Japan: 81-44-844-8013
UK: 44-8706-080-208a

Hermaphroditic Covers for Level V IDC Receptacle Assemblies, Double-Row, .125 x .125 [3.18 x 3.18] Centerline (Continued)



Cover Part No. 104583-1, 64-Position with Double Cable Tie Paddle



Cover Part No. 104584-1, 64-Position with Double Cable Tie Paddle and Polarization

Note: All part numbers are RoHS compliant.

Catalog 1307819
Revised 8-08

www.tycoelectronics.com

Dimensions are in inches and millimeters unless otherwise specified. Values in brackets are metric equivalents.

Dimensions are shown for reference purposes only. Specifications subject to change.

USA: 1-800-522-6752
Canada: 1-905-470-4425
Mexico: 01-800-733-8926
C. America: 52-55-1106-0803

South America: 55-11-2103-6000
Hong Kong: 852-2735-1628
Japan: 81-44-844-8013
UK: 44-8706-080-208a

AMPMODU .031 x .062 [0.79 x 1.57] Interconnection System

Product Facts

- **Rugged connector system featuring .031 x .062 [0.79 x 1.57] posts with mating receptacles**
- **Current rating 5 amps max per contact. Varies due to ambient temperature, wire size and duty cycles.**
- **Available for board-to-board and wire-to-board applications**
- **Posts available on strip for machine application directly to pc board or in housings for board mounting**
- **Receptacles available for board mounting or wire crimping**
- **Contacts available in both tin and gold plating**
- **Flame retardant thermoplastic housings 94V-0 rated**
- **Locking Clip contacts available to mate with .031 x .062 [0.79 x 1.57] posts**
- **Recognized under the Component Program of Underwriters Laboratories Inc., File No. E28476**
- **Certified by Canadian Standards Association, File No. LR 16455**

The .031 x .062 [0.79 x 1.57] interconnection system has served as an industry standard for modular packaging for over three decades. It is a rugged, large scale system designed for board-to-board and board-to-wire or cable applications that has offered millions of reliable interconnections and countless mating cycles. This versatile interconnection system successfully meets the requirements for most modular power supply packaging.

Board mounted receptacles and receptacle assemblies are available in various geometries, offering packaging interconnections that include perpendicular, parallel and stacking capabilities. Machine applied terminations, through matched application equipment, are geared to virtually any production requirement, assuring the lowest possible applied cost.

Crimp snap-in receptacles for 26-18 AWG [0.12 – 0.9mm^2] wire provide excellent discrete wire terminations. Housings for these contacts provide for ease of handling terminations in high density applications.

AMPMODU mating posts are supplied typically as header assemblies. They are available in various sizes to meet the interconnection and packaging requirements of your system. However, in instances where packaging configurations do not lend themselves to the economies of assemblies, Tyco Electronics can provide for the discrete location of individual posts and receptacles.

If your interconnections require Top Entry, Bottom Entry and/or Side Entry for perpendicular, parallel and stacked configurations, the .031 x .062 [0.79 x 1.57] interconnection system can fulfill your needs with the lowest applied cost through efficient interconnections and supporting application equipment.

Catalog 1307819
Revised 8-08

www.tycoelectronics.com

Dimensions are in inches and millimeters unless otherwise specified. Values in brackets are metric equivalents.

Dimensions are shown for reference purposes only. Specifications subject to change.

USA: 1-800-522-6752
Canada: 1-905-470-4425
Mexico: 01-800-733-8926
C. America: 52-55-1106-0803

South America: 55-11-2103-6000
Hong Kong: 852-2735-1628
Japan: 81-44-844-8013
UK: 44-8706-080-208a

AMPMODU .031 x .062 [0.79 x 1.57] Interconnection System (Continued)





The AMPMODU receptacle cross-section is primarily rectangular, with rounded corners. Two integral cantilever beams contact the mating square or rectangular posts. Deflection of these spring members is limited by anti-overstress and excessive permanent deformation is prevented. This feature allows a wide range of tolerances for misalignment of mating contacts. The configuration of the receptacle completely encloses the spring members preventing damage during handling and assembly and makes the system compatible with automatic application techniques.

This design also permits the use of the receptacles without housings or encapsulation.

Note: Application of a contact lubricant is part of the manufacturing process of all AMPMODU tin-plated crimp products. However, it is not part of the manufacturing process of products that customers will solder, then clean. For these products, Tyco Electronics recommends that customers purchase a contact lubricant. (See application specification 114-25004 for further information.)



Wire Crimp Receptacle

Catalog 1307819
Revised 8-08

www.tycoelectronics.com

Dimensions are in inches and millimeters unless otherwise specified. Values in brackets are metric equivalents.

Dimensions are shown for reference purposes only. Specifications subject to change.

USA: 1-800-522-6752
Canada: 1-905-470-4425
Mexico: 01-800-733-8926
C. America: 52-55-1106-0803

South America: 55-11-2103-6000
Hong Kong: 852-2735-1628
Japan: 81-44-844-8013
UK: 44-8706-080-208a

Mod I Receptacles, Board Mount, .031 x .062 [0.79 x 1.57] Centerline

Vertical and Horizontal Board Mount



Bottom Post Entry Type A

Top Post Entry Type B





Horizontal Post Entry Type C

Receptacle Styles



Type A



Type B



Typical Solder Resist Tab (Type A or B)



Type C

Related Product Data

Recommended Board Layout for Type C — page 288

Mates with —

Machine Applied Posts — page 294

Headers — pages 295-297

Application Tooling — pages 300-304

Performance Specifications — page 305

Technical Documents — page 305

Keying Plug

Part No. 86181-2
Use in Board Mount Receptacles

Recommended Board Layout for Receptacle Assemblies and Individual Receptacles (Type A and B)



Round Hole (Post Entry Type A or B)

J-Receptacle centers may vary depending on requirements. For individual receptacles, minimum nominal centerline spacing between adjacent receptacles is .150 [3.81]; for receptacle assemblies, centerline spacing between adjacent receptacles is .156 [3.96]. The .003 [0.08] tolerances are not to accumulate over length of board. For solder mask, see Tyco Electronics Instruction Sheet 408-7411.

Note: Drawings depict normal use of the contact in a one or two-sided circuit board. When using plated thru-holes, refer to Tyco Electronics Engineering Report ER-001 and Tyco Electronics Instruction Sheet 408-7411. For solder mask, see Tyco Electronics Instruction Sheet 408-7411.

Note: All part numbers are RoHS compliant.

Catalog 1307819
Revised 8-08

www.tycoelectronics.com

Dimensions are in inches and millimeters unless otherwise specified. Values in brackets are metric equivalents.

Dimensions are shown for reference purposes only. Specifications subject to change.

USA: 1-800-522-6752
Canada: 1-905-470-4425
Mexico: 01-800-733-8926
C. America: 52-55-1106-0803

South America: 55-11-2103-6000
Hong Kong: 852-2735-1628
Japan: 81-44-844-8013
UK: 44-8706-080-208a

Mod I Receptacles, Board Mount, .031 x .062 [0.79 x 1.57] Centerline (Continued)

Material and Finish

Copper alloy, plated as follows:

Plating A — Selectively plated .000030 [0.00076] gold on contact area, with gold flash over .000050 [0.00127] nickel on entire contact

Plating B — .000079 [0.00201] min. tin on entire contact

Plating C — (Solder Resist) — .000030 [0.00076] gold over .000050 [0.00127] nickel on contact area, .000500 [0.01270] aluminum on inside area of solder tines; remainder of contact unfinished



Standard Pressure Receptacle



High Pressure Receptacle

Type	Board Thickness Range	Dimension T (*Ref. Pg. 285*)	Finish	Standard Pressure Part Nos.		High Pressure Part Nos.		Insertion Applicator No. for "U" Frame Machine
				Strip Form	Loose Piece	Strip Form	Loose Piece	
A	**.070-.055** [1.78-1.40]	**.112** [2.84]	Plating A	86477-2	86480-2	—	—	466376-1
			Plating B	86477-3	—	87316-3	—	466376-1
			Plating C (Solder Resist)	87772-2	—	—	—	466376-1
B	**.070-.055** [1.78-1.40]	**.112** [2.84]	Plating A	87003-1	87105-1	—	—	466376-1
			Plating B	87003-2	—	—	—	466376-1
			Plating C (Solder Resist)	87774-2	—	—	—	466376-1
C	**.103-.055** [2.62-1.40]	**.145** [3.68]	Plating A	85487-4	85493-4	86432-8	86434-6	565967-3
			Plating B	85487-3	—	86432-1	86434-1	

Notes: 1. All strip form parts in packaged quantities of 5,000 each.
2. All loose piece parts in packaged quantities of 500 each.

Note: All part numbers are RoHS compliant.

Catalog 1307819
Revised 8-08

www.tycoelectronics.com

Dimensions are in inches and millimeters unless otherwise specified. Values in brackets are metric equivalents.

Dimensions are shown for reference purposes only. Specifications subject to change.

USA: 1-800-522-6752
Canada: 1-905-470-4425
Mexico: 01-800-733-8926
C. America: 52-55-1106-0803

South America: 55-11-2103-6000
Hong Kong: 852-2735-1628
Japan: 81-44-844-8013
UK: 44-8706-080-208a

Mod I Receptacle Assemblies, Vertical Board Mount, .031 x .062 [0.79 x 1.57] Centerline

Single Row .156 [3.96] Centerline





Material and Finish

Housing — Black thermoplastic, 94V-0 rated

Contacts — Copper alloy, plated as follows:

Plating A — Selectively plated .000030 [0.00076] gold on contact area, with gold flash over .000050 [0.00127] nickel on entire contact

Plating B — .000079 [0.00201] min. tin on entire contact

Plating C — (Solder Resist) — .000030 [0.00076] gold over .000050 [0.00127] nickel on contact area, .000500 [0.01270] aluminum on inside area of solder tines; remainder of contact unfinished

Related Product Data

Recommended Board Layout — page 288

Mates with —

Machine Applied Posts — page 294

Headers — pages 295-297

Performance Specifications — page 305

Technical Documents — page 305

No. of Pos.	Dimensions		Type A				Type B		
			Standard Pressure			High Pressure	Standard Pressure		
	A	B	Plating A	Plating B	Plating C	Plating B	Plating A	Plating B	Plating C
2	**.156** [3.96]	**.312** [7.92]	87984-2	87983-2	87989-2	87993-2	87986-2	87985-2	87990-2
3	**.312** [7.92]	**.468** [11.89]	87984-3	87983-3	87989-3	87993-3	87986-3	87985-3	87990-3
4	**.468** [11.89]	**.624** [15.85]	87984-4	87983-4	87989-4	87993-4	87986-4	87985-4	87990-4
5	**.624** [15.85]	**.780** [19.81]	87984-5	87983-5	87989-5	87993-5	87986-5	87985-5	87990-5
6	**.780** [19.81]	**.936** [23.77]	87984-6	87983-6	87989-6	87993-6	87986-6	87985-6	87990-6
7	**.936** [23.77]	**1.092** [27.74]	87984-7	87983-7	87989-7	87993-7	87986-7	87985-7	87990-7
8	**1.092** [27.74]	**1.248** [31.70]	87984-8	87983-8	87989-8	87993-8	87986-8	87985-8	87990-8
9	**1.248** [31.70]	**1.404** [35.66]	87984-9	87983-9	87989-9	87993-9	87986-9	87985-9	87990-9
10	**1.404** [35.66]	**1.560** [39.62]	1-87984-0	1-87983-0	1-87989-0	1-87993-0	1-87986-0	1-87985-0	1-87990-0
11	**1.560** [39.62	**1.716** [43.59]	1-87984-1	1-87983-1	1-87989-1	1-87993-1	1-87986-1	1-87985-1	1-87990-1
12	**1.716** [43.59]	**1.872** [47.55]	1-87984-2	1-87983-2	1-87989-2	1-87993-2	1-87986-2	1-87985-2	1-87990-2
13	**1.872** [47.55]	**2.028** [51.51]	1-87984-3	1-87983-3	1-87989-3	1-87993-3	1-87986-3	1-87985-3	1-87990-3
14	**2.028** [51.51]	**2.184** [55.47]	1-87984-4	1-87983-4	1-87989-4	1-87993-4	1-87986-4	1-87985-4	1-87990-4
15	**2.184** [55.47]	**2.340** [59.44]	1-87984-5	1-87983-5	1-87989-5	1-87993-5	1-87986-5	1-87985-5	1-87990-5
16	**2.340** [59.44]	**2.496** [63.40]	1-87984-6	1-87983-6	1-87989-6	1-87993-6	1-87986-6	1-87985-6	1-87990-6
17	**2.496** [63.40]	**2.652** [67.36]	1-87984-7	1-87983-7	1-87989-7	1-87993-7	1-87986-7	1-87985-7	1-87990-7
18	**2.652** [67.36]	**2.808** [71.32]	1-87984-8	1-87983-8	1-87989-8	1-87993-8	1-87986-8	1-87985-8	1-87990-8
19	**2.808** [71.32]	**2.964** [75.29]	1-87984-9	1-87983-9	1-87989-9	1-87993-9	1-87986-9	1-87985-9	1-87990-9
20	**2.964** [75.29]	**3.120** [79.25]	2-87984-0	2-87983-0	2-87989-0	2-87993-0	2-87986-0	2-87985-0	2-87990-0

Keying Plug



Part No. 86181-2
(Use in Board Mount Receptacles)



Post Entry Type A



Post Entry Type B

Note: All part numbers are RoHS compliant.

Catalog 1307819
Revised 8-08

www.tycoelectronics.com

Dimensions are in inches and millimeters unless otherwise specified. Values in brackets are metric equivalents.

Dimensions are shown for reference purposes only. Specifications subject to change.

USA: 1-800-522-6752
Canada: 1-905-470-4425
Mexico: 01-800-733-8926
C. America: 52-55-1106-0803

South America: 55-11-2103-6000
Hong Kong: 852-2735-1628
Japan: 81-44-844-8013
UK: 44-8706-080-208a

Mod I Receptacle Assemblies, Horizontal Board Mount, .031 x .062 [0.79 x 1.57] Centerline

Single Row .156 [3.96] Centers

Material and Finish

Housing — Black thermoplastic, 94V-0 rated

Contacts — Copper alloy, plated as follows:

Plating A — Selectively plated .000030 [0.00076] gold contact area, with gold flash over .000050 [0.00127] nickel on entire contact

Plating B — .000079 [0.00201] min. tin on entire contact



Post Entry Type C

Related Product Data

Mates with —

Machine Applied Posts — page 294

Headers — pages 295-297

Performance Specifications — page 305

Technical Documents — page 305



The letter A stamped on contact indicates mating end of receptacle.







Recommended Board Layouts for Receptacle Assemblies and Individual Receptacles (Type C)



This configuration recommended for use with machine applied posts or headers with a .405 [10.29] minimum mating end post length.*



This configuration recommended for use with machine applied posts or headers with a .345 [18.76] minimum mating end post length.*



This configuration recommended for use with machine applied posts or headers with a .500 [12.70] minimum mating end post length.*

Keying Plug



Part No. 86181-2
(Use in Board Mount Receptacles)

The mating post length is depicted by the A dimension on page 294 (machine applied posts) and the C dimension on pages 295-297 (headers).

H-Receptacle centers may vary depending on requirements. For individual receptacles, minimum nominal centerline spacing between adjacent receptacles is .125 [3.18] for receptacle assemblies, centerline spacing between adjacent receptacles is .156 [3.96]. The .003 [0.08] tolerances are not to accumulate over length of board.

Note: All part numbers are RoHS compliant.

Catalog 1307819
Revised 8-08

www.tycoelectronics.com

Dimensions are in inches and millimeters unless otherwise specified. Values in brackets are metric equivalents.

Dimensions are shown for reference purposes only. Specifications subject to change.

USA: 1-800-522-6752
Canada: 1-905-470-4425
Mexico: 01-800-733-8926
C. America: 52-55-1106-0803

South America: 55-11-2103-6000
Hong Kong: 852-2735-1628
Japan: 81-44-844-8013
UK: 44-8706-080-208a

Mod I Receptacle Assemblies, Horizontal Board Mount, .031 x .062 [0.79 x 1.57] Centerline (Continued)

No. of Pos.	Dimensions		Standard Pressure		High Pressure
	A	B	Plating A	Plating B	Plating B
2	**.156** [3.96]	**.312** [7.92]	87988-2	87987-2	87995-2
3	**.312** [7.92]	**.468** [11.89]	87988-3	87987-3	87995-3
4	**.468** [11.89]	**.624** [15.85]	87988-4	87987-4	87995-4
5	**.624** [15.85]	**.780** [19.81]	87988-5	87987-5	87995-5
6	**.780** [19.81]	**.936** [23.77]	87988-6	87987-6	87995-6
7	**.936** [23.77]	**1.092** [27.74]	87988-7	87987-7	87995-7
8	**1.092** [27.74]	**1.248** [31.70]	87988-8	87987-8	87995-8
9	**1.248** [31.70]	**1.404** [35.66]	87988-9	87987-9	87995-9
10	**1.404** [35.66]	**1.560** [39.62]	1-87988-0	1-87987-0	1-87995-0
11	**1.560** [39.62]	**1.716** [43.59]	1-87988-1	1-87987-1	1-87995-1
12	**1.716** [43.59]	**1.872** [47.55]	1-87988-2	1-87987-2	1-87995-2
13	**1.872** [47.54]	**2.028** [51.51]	1-87988-3	1-87987-3	1-87995-3
14	**2.028** [51.51]	**2.184** [55.47]	1-87988-4	1-87987-4	1-87995-4
15	**2.184** [55.47]	**2.340** [59.44]	1-87988-5	1-87987-5	1-87995-5
16	**2.340** [59.44]	**2.496** [63.40]	1-87988-6	1-87987-6	1-87995-6
17	**2.496** [63.40]	**2.652** [67.36]	1-87988-7	1-87987-7	1-87995-7
18	**2.652** [67.36]	**2.808** [71.32]	1-87988-8	1-87987-8	1-87995-8
19	**2.808** [71.32]	**2.964** [75.29]	1-87988-9	1-87987-9	1-87995-9
20	**2.964** [75.29]	**3.120** [79.25]	2-87988-0	2-87987-0	2-87995-0

Note: All part numbers are RoHS compliant.

Catalog 1307819
Revised 8-08

www.tycoelectronics.com

Dimensions are in inches and millimeters unless otherwise specified. Values in brackets are metric equivalents.

Dimensions are shown for reference purposes only. Specifications subject to change.

USA: 1-800-522-6752
Canada: 1-905-470-4425
Mexico: 01-800-733-8926
C. America: 52-55-1106-0803

South America: 55-11-2103-6000
Hong Kong: 852-2735-1628
Japan: 81-44-844-8013
UK: 44-8706-080-208a

Mod I Receptacles, Crimp Snap-In (Wire Applied), .031 x .062 [0.79 x 1.57] Centerline

Material and Finish

Copper alloy, plated as follows:

Plating A — Selectively plated .000030 [0.00076] gold on contact area, with gold flash over .000050 [0.00127] nickel on entire contact

Plating B — .000016 [0.00041] min. tin on entire contact

Related Product Data

Housings used in — pages 291-293

Mate with Machine Applied Posts — page 294

Headers — pages 295-297

Application Tooling — page 300-304

Performance Specification — page 305

Technical Documents — page 305





Standard Pressure Receptacle

Wire Size Range AWG [mm²]	Ins. Dia. Range	Finish	Standard Pressure			
			Strip Form		Loose Piece	
			Packaged Quantities	Part Nos.	Packaged Quantities	Part Nos.
22-18 [0.3-0.9]	**.051-.090** [1.30–2.29]	Plating A	5,000	102099-2	500	102103-2
		Plating B	5,000	102099-5	500	102103-3

Wire Size Range AWG [mm²]	Applicator (Standard Pressure)			Premium CERTI-CRIMP Hand Tool Part Number
	Part Number	Type	Used With Machine	
22-18 [0.3-0.9]	466764-3	HDM	Model "G" (AMP-O-LECTRIC)	90274-2
	466764-2	HDM	Model "K" (AMP-O-LECTRIC)	
	466764-1	HDM	CLS IV+ (AMPOMATOR)	
	466937-1	SCA	Stripper-Crimper (AMP-O-MATIC)	

AMP-O-LECTRIC KII Machine. Applicators also available for AMPOMATOR Lead Making Machines and Stripper/Crimper Machines. Consult Tyco Electronics.



High Pressure Receptacle

Wire Size Range AWG [mm²]	Ins. Dia. Range	Finish	High Pressure			
			Strip Form		Loose Piece	
			Packaged Quantities	Part Nos.	Packaged Quantities	Part Nos.
22-18 [0.3-0.9]	**.051-.090** [1.30–2.29]	Plating A	5,000	102100-2	500	102104-2
		Plating B	5,000	102100-5	500	102104-3
26-22 [0.12-0.4]	**0.42-.073** [1.07-1.85]	Plating A	5,000	102102-2	500	102106-2
		Plating B	5,000	102102-5	500	102106-3

Wire Size Range AWG [mm²]	Applicator (High Pressure)			Premium CERTI-CRIMP Hand Tool Part Number
	Part Number	Type	Used With Machine	
22-18 [0.3-0.9]	466764-3	HDM	Model "G" (AMP-O-LECTRIC)	90274-2
	466764-2	HDM	Model "K" (AMP-O-LECTRIC)	
	466764-1	HDM	CLS IV+ (AMPOMATOR)	
26-22 [0.12-0.4]	466937-1	SCA	Stripper-Crimper (AMP-O-MATIC)	90328-1
	466763-2	HDM	Model "K" (AMP-O-LECTRIC)	
	466763-1	HDM	CLS IV+ (AMPOMATOR)	

AMP-O-LECTRIC KII Machine. Applicators also available for AMPOMATOR Lead Making Machines and Stripper/Crimper Machines. Consult Tyco Electronics.

Extraction Tool Part No. 843473-1
Part Instruction Sheet 408-9451

Note: All part numbers are RoHS compliant.

Catalog 1307819
Revised 8-08

www.tycoelectronics.com

Dimensions are in inches and millimeters unless otherwise specified. Values in brackets are metric equivalents.

Dimensions are shown for reference purposes only. Specifications subject to change.

USA: 1-800-522-6752
Canada: 1-905-470-4425
Mexico: 01-800-733-8926
C. America: 52-55-1106-0803

South America: 55-11-2103-6000
Hong Kong: 852-2735-1628
Japan: 81-44-844-8013
UK: 44-8706-080-208a

Mod I Receptacle Housings, Standard Profile, Unkeyed, .031 x .062 [0.79 x 1.57] Centerline

Single Row, .156 [3.96] Centers, Without Strain Relief





Material

Black thermoplastic, flame retardant, 94V-0 rated

Related Product Data

Contacts used with — page 290
Mate with —
Machine Applied Posts — page 294
Headers — pages 295-297
Performance Specifications — page 305

Technical Documents — page 305

No. of Pos.	Dimensions			Housing Part Nos.	
	A	B	L	Stamped[1]	Unstamped[2]
2	1	**.156** [3.96]	**.312** [7.92]	—	2-87025-5
3	2	**.312** [7.92]	**.468** [11.89]	—	2-87025-1
4	3	**.468** [11.89]	**.624** [15.85]	—	1-87025-3
5	4	**.624** [15.85]	**.780** [19.81]	—	2-87025-3
6	5	**.780** [19.81]	**.936** [23.77]	87025-1	87025-2
7	6	**.936** [23.77]	**1.092** [27.74]	—	3-87025-4
8	7	**1.092** [27.74]	**1.248** [31.70]	—	1-87025-6
9	8	**1.248** [31.70]	**1.404** [35.66]	87025-9	1-87025-0
10	9	**1.404** [35.66]	**1.560** [39.62]	1-87025-7	1-87025-8
11	10	**1.560** [39.62]	**1.716** [43.59]	—	3-87025-6
12	11	**1.716** [43.59]	**1.872** [47.55]	1-87025-1	1-87025-2
13	12	**1.872** [47.55]	**2.028** [51.51]	—	3-87025-0
14	13	**2.028** [51.51]	**2.184** [55.47]	—	3-87025-8
15	14	**2.184** [55.47]	**2.340** [59.44]	—	3-87025-2
16	15	**2.340** [59.44]	**2.496** [63.40]	—	2-87025-0
17	16	**2.496** [63.40]	**2.652** [67.36]	—	4-87025-0
18	17	**2.652** [67.36]	**2.808** [71.32]	—	87025-4
19	18	**2.808** [71.32]	**2.964** [75.29]	—	87025-6
20	19	**2.964** [75.29]	**3.120** [79.25]	—	87025-8
25	24	**3.744** [95.10]	**3.900** [99.06]	—	5-87025-0

Notes: [1]Markings on housing.
[2]No markings on housing.

Note: All part numbers are RoHS compliant.

Catalog 1307819
Revised 8-08

www.tycoelectronics.com

Dimensions are in inches and millimeters unless otherwise specified. Values in brackets are metric equivalents.

Dimensions are shown for reference purposes only. Specifications subject to change.

USA: 1-800-522-6752
Canada: 1-905-470-4425
Mexico: 01-800-733-8926
C. America: 52-55-1106-0803
South America: 55-11-2103-6000
Hong Kong: 852-2735-1628
Japan: 81-44-844-8013
UK: 44-8706-080-208a

Mod I Receptacle Housings, Standard Profile, Unkeyed, .031 x .062 [0.79 x 1.57] Centerline (Continued)

Single Row, .156 [3.96] Centers, With Strain Relief





10 Position Receptacle Housing, Part No. 1-102090-0

Material

Black thermoplastic, flame retardant, 94V-0 rated

Related Product Data

Contacts used with — page 290
Mate with —
Machine Applied Posts — page 294
Headers — pages 295-297
Performance Specifications — page 305

Technical Documents

— page 305

Note: All part numbers are RoHS compliant.

Catalog 1307819
Revised 8-08

www.tycoelectronics.com

Dimensions are in inches and millimeters unless otherwise specified. Values in brackets are metric equivalents.

Dimensions are shown for reference purposes only. Specifications subject to change.

USA: 1-800-522-6752
Canada: 1-905-470-4425
Mexico: 01-800-733-8926
C. America: 52-55-1106-0803

South America: 55-11-2103-6000
Hong Kong: 852-2735-1628
Japan: 81-44-844-8013
UK: 44-8706-080-208a

Mod I Receptacle Housings, Low Profile, Keyed, .031 x .062 [0.79 x 1.57] Centerline

Single Row, .156 [3.96] Centers



Material
Black thermoplastic, flame retardant, 94V-0 rated

Related Product Data
Contacts used with — page 290
Mate with —
Headers — pages 295-297
Performance Specifications — page 305

Technical Documents — page 305



No. of Pos.	Dimensions			No. of Keys	Housing Part Nos. (Unstamped)[1]	Key Locations
	A	B	L			
2	1	**.156** [3.96]	**.312** [7.92]	1	87159-3	A
3	2	**.312** [7.92]	**.468** [11.89]	1	87159-4	A
4	3	**.468** [11.89]	**.624** [15.85]	2	87159-5	A,C
5	4	**.624** [15.85]	**.780** [19.81]	2	87159-1	A,D
6	5	**.780** [19.81]	**.936** [23.77]	3	87159-6	A,C,E
7	6	**.936** [23.77]	**1.092** [27.74]	3	87159-7	A,C,E
8	7	**1.092** [27.74]	**1.248** [31.70]	4	87159-8	A,C,E,G
9	8	**1.248** [31.70]	**1.404** [35.66]	3	87159-9	A,D,G
10	9	**1.404** [35.66]	**1.560** [39.62]	5	1-87159-0	A,C,E,G,J
11	10	**1.560** [39.62]	**1.716** [43.59]	4	1-87159-1	A,D,G,K
12	11	**1.716** [43.59]	**1.872** [47.55]	6	1-87159-2	A,C,E,G,J,L
13	12	**1.872** [47.55]	**2.028** [51.51]	4	87159-2	A,D,J,M
14	13	**2.028** [51.51]	**2.184** [55.47]	7	1-87159-3	A,C,E,G,J,L,N
15	14	**2.184** [55.47]	**2.340** [59.44]	5	1-87159-4	A,D,G,K,N
16	15	**2.340** [59.44]	**2.496** [63.40]	8	1-87159-5	A,C,E,G,J,L,N,Q
17	16	**2.496** [63.40]	**2.652** [67.36]	6	1-87159-6	A,D,G,K,N,R
18	17	**2.652** [67.36]	**2.808** [71.32]	6	1-87159-7	A,D,F,J,P,S
19	18	**2.808** [71.32]	**2.964** [75.29]	8	1-87159-8	B,D,F,J,L,N,Q,S
20	19	**2.964** [75.29]	**3.120** [79.25]	10	1-87159-9	A,C,E,G,J,L,N,Q,S,U
25	24	**3.744** [95.10]	**3.900** [99.06]	11	2-87159-4	A,C,E,H,K,M,Q,S,U,W,Y

[1]No marking on housing.

Keying Plug

Material — Natural Color Nylon



Part No. 87116-2

Keying Plug References



For Standard Housings



For Low Profile Housings

Note: All part numbers are RoHS compliant.

Catalog 1307819
Revised 8-08

www.tycoelectronics.com

Dimensions are in inches and millimeters unless otherwise specified. Values in brackets are metric equivalents.

Dimensions are shown for reference purposes only. Specifications subject to change.

USA: 1-800-522-6752
Canada: 1-905-470-4425
Mexico: 01-800-733-8926
C. America: 52-55-1106-0803

South America: 55-11-2103-6000
Hong Kong: 852-2735-1628
Japan: 81-44-844-8013
UK: 44-8706-080-208a

Mod I Posts, Machine Applied, .031 x .062 [0.79 x 1.57] Centerline

Straight Posts



Typical Assembly





Recommended Mounting Holes

Material and Finish

Brass, plated .000030 [0.00076] gold over .000050 [0.00127] nickel on entire post

Related Product Data

Mate with —

Board Mount Receptacles — pages 285, 286

Board Mount Receptacle Assemblies — pages 287-289

Crimp Snap-In Receptacles and Housings — pages 290-292

Locking Clip Contacts & Housings — pages 298, 299 (see page 298 for recommended post length).

Application Tooling — pages 300-304

Performance Specifications — page 305

Technical Documents — page 305

D—Post centers may vary depending on requirements. Minimum nominal centerline spacing between adjacent contacts is .125 [3.18]; .003 [0.08] tolerances not to accumulate over length of board.

E—Post center location from edge of board may vary to satisfy application.

Dimensions			Finish	Part Nos.	
A	B	C		Strip Form[1]	Loose Piece[2]
.360 [9.14]	**.187** [4.75]	**.595** [15.11]	Plating A	86147-7	86182-7
			Plating B	5086147-2	5086182-2
.380 [9.65]	**.320** [8.13]	**.748** [19.00]	Plating A	1-86147-5	1-86182-5
			Plating B	5086147-9	5086182-9
.400 [10.16]	**.125** [3.18]	**.573** [14.55]	Plating A	4-86147-2	2-86182-9
			Plating B	3-5086147-7	2-5086182-5
.480 [12.19]	**.187** [4.75]	**.715** [18.16]	Plating A	1-86147-8	1-86182-8
			Plating B	2-5086147-2	2-5086182-2
.565 [14.35]	**.187** [4.75]	**.800** [20.32]	Plating A	86147-8	86182-8
			Plating B	5086147-1	5086182-1
.800 [20.32]	**.150** [3.81]	**.998** [25.35]	Plating A	1-86147-2	1-86182-2
			Plating B	1-5086147-0	1-5086182-0

[1] Packaging quantity of 20,000 per reel.
[2] Packaging quantity of 1,000 per bag.
Note: Strip form posts applied with Insertion Machine No. **3-457382-1**, includes power unit and applicator.

Note: All part numbers are RoHS compliant.

Catalog 1307819
Revised 8-08

www.tycoelectronics.com

Dimensions are in inches and millimeters unless otherwise specified. Values in brackets are metric equivalents.

Dimensions are shown for reference purposes only. Specifications subject to change.

USA: 1-800-522-6752
Canada: 1-905-470-4425
Mexico: 01-800-733-8926
C. America: 52-55-1106-0803

South America: 55-11-2103-6000
Hong Kong: 852-2735-1628
Japan: 81-44-844-8013
UK: 44-8706-080-208a

Mod I Headers, Straight Post, Keyed, .031 x .062 [0.79 x 1.57] Centerline

Single Row, .156 [3.96] Centers





Material and Finish

Housing — Black thermoplastic, 94V-0 rated

Posts — Brass, plated as follows:

Plating A — Selectively plated .000030 [0.00076] gold on contact area, with gold flash over .000050 [0.00127] min. nickel on entire post

Plating B — .000100-.000200 [0.00254-0.00508] tin over .000030 [0.00762] nickel on entire post

Related Product Data

Mate with —

Board Mount Receptacles — pages 285, 286

Board Mount Receptacle Assemblies — pages 287-289

Crimp Snap-In Receptacles and Housings — pages 290-292

Locking Clip Contacts & Housings — pages 298 & 299 (see page 298 for recommended post length).

Performance Specifications — page 305

Technical Documents — page 305



Recommended Board Layout

Keyway Locations (Ref only)

No. of Pos.	Dimensions A	B	C	No. of Keying Slots	Post Height D=.405 [10.29] Plating A	Plating B	Post Height D=.587 [14.91] Plating A	Plating B	Keyway Locations
2	1	**.156** [3.96]	**.267** [6.78]	1	85829-2	5-87160-4	87247-2	5-87262-2	A
3	2	**.312** [7.92]	**.423** [10.74]	1	85829-3	5-87160-5	87247-3	5-87262-3	A
4	3	**.468** [11.89]	**.579** [14.71]	2	85829-4	5-87160-6	87247-4	5-87262-4	A,C
5	4	**.624** [15.85]	**.735** [18.67]	2	85829-5	5-87160-1	87247-5	5-87262-5	A,D
6	5	**.780** [19.81]	**.891** [22.63]	3	85829-6	5-87160-7	87247-6	5-87262-6	A,C,E
7	6	**.936** [23.77]	**1.047** [26.59]	3	85829-7	5-87160-8	87247-7	5-87262-7	A,C,E,
8	7	**1.092** [27.74]	**1.203** [30.56]	4	85829-8	5-87160-9	87247-8	5-87262-8	A,C,E,G
9	8	**1.248** [31.70]	**1.359** [34.52]	3	85829-9	6-87160-0	87247-9	5-87262-9	A,D,G
10	9	**1.404** [35.66]	**1.515** [38.48]	5	1-85829-0	6-87160-1	1-87247-0	6-87262-0	A,C,E,G,J
11	10	**1.560** [39.62]	**1.671** [42.44]	4	1-85829-1	6-87160-2	1-87247-1	6-87262-1	A,D,G,K
12	11	**1.716** [43.59]	**1.827** [46.41]	6	1-85829-2	6-87160-3	1-87247-2	6-87262-2	A,C,E,G,J,L
13	12	**1.872** [47.55]	**1.983** [50.37]	4	1-85829-3	5-87160-2	1-87247-3	6-87262-3	A,D,J,M
14	13	**2.028** [51.51]	**2.139** [54.33]	7	1-85829-4	6-87160-4	1-87247-4	6-87262-4	A,C,E,G,J,L,N
15	14	**2.184** [55.47]	**2.295** [58.29]	5	1-85829-5	6-87160-5	1-87247-5	6-87262-5	A,D,G,K,N
16	15	**2.340** [59.44]	**2.451** [62.26]	8	1-85829-6	6-87160-6	1-87247-6	6-87262-6	A,C,E,G,J,L,N,Q
17	16	**2.496** [63.40]	**2.607** [66.22]	6	1-85829-7	6-87160-7	1-87247-7	6-87262-7	A,D,G,K,N,R
18	17	**2.652** [67.36]	**2.763** [70.18]	7	1-85829-8	6-87160-8	1-87247-8	6-87262-8	A,D,F,J,M,P,S
19	18	**2.808** [71.32]	**2.919** [74.14]	8	1-85829-9	6-87160-9	1-87247-9	6-87262-9	B,D,F,J,L,N,Q,S
20	19	**2.964** [75.29]	**3.075** [78.11]	10	2-85829-0	7-87160-0	2-87247-0	7-87262-0	A,C,E,G,J,L,N,Q,S,U
21	20	**3.120** [79.25]	**3.231** [82.07]	7	2-85829-1	7-87160-1	2-87247-1	7-87262-1	A,D,G,K,N,R,U
22	21	**3.276** [83.21]	**3.387** [86.03]	11	2-85829-2	7-87160-2	2-87247-2	7-87262-2	A,C,E,G,J,L,N,Q,S,U,W
23	22	**3.432** [87.17]	**3.543** [89.99]	8	2-85829-3	7-87160-3	2-87247-3	7-87262-3	A,D,G,K,N,R,U,X
24	23	**3.588** [91.14]	**3.699** [93.95]	12	2-85829-4	7-87160-4	2-87247-4	7-87262-4	A,C,E,G,J,L,N,Q,S,U,W,Y
25	24	**3.744** [95.10]	**3.855** [97.92]	11	2-85829-5	7-87160-5	2-87247-5	7-87262-5	A,C,E,H,K,M,Q,S,U,W,Y

Note: All part numbers are RoHS compliant.

Catalog 1307819
Revised 8-08

www.tycoelectronics.com

Dimensions are in inches and millimeters unless otherwise specified. Values in brackets are metric equivalents.

Dimensions are shown for reference purposes only. Specifications subject to change.

USA: 1-800-522-6752
Canada: 1-905-470-4425
Mexico: 01-800-733-8926
C. America: 52-55-1106-0803

South America: 55-11-2103-6000
Hong Kong: 852-2735-1628
Japan: 81-44-844-8013
UK: 44-8706-080-208a

Mod I Headers, Straight Post, Keyed, .031 x .062 [0.79 x 1.57] Centerline (Continued)

No. of Pos.	Dimensions			No. of Keying Slots	Post Height D=.750 [19.05]		Post Height D=1.187 [30.15]		Post Height D=1.310 [33.27]		Keyway Locations
	A	B	C		Plating A	Plating B	Plating A	Plating B	Plating A	Plating B	
2	1	**.156** [3.96]	**.267** [6.78]	1	85923-2	5-85875-7	87283-2	—	85839-2	5-85840-2	A
3	2	**.312** [7.92]	**.423** [10.74]	1	85923-3	5-85875-8	87283-3	5-86207-2	85839-3	5-85840-3	A
4	3	**.468** [11.89]	**.579** [14.71]	2	85923-4	5-85875-1	87283-4	5-86207-9	85839-4	5-85840-4	A,C
5	4	**.624** [15.85]	**.735** [18.67]	2	85923-5	5-85875-2	87283-5	5-86207-3	85839-5	5-85840-5	A,D
6	5	**.780** [19.81]	**.891** [22.63]	3	85923-6	5-85875-9	87283-6	—	85839-6	5-85840-6	A,C,E
7	6	**.936** [23.77]	**1.047** [26.59]	3	85923-7	6-85875-0	87283-7	—	85839-7	5-85840-7	A,C,E,
8	7	**1.092** [27.74]	**1.203** [30.56]	4	85923-8	6-85875-1	87283-8	—	85839-8	5-85840-8	A,C,E,G
9	8	**1.248** [31.70]	**1.359** [34.52]	3	85923-9	5-85875-3	87283-9	—	85839-9	5-85840-9	A,D,G
10	9	**1.404** [35.66]	**1.515** [38.48]	5	1-85923-0	6-85875-2	1-87283-0	—	1-85839-0	6-85840-0	A,C,E,G,J
11	10	**1.560** [39.62]	**1.671** [42.44]	4	1-85923-1	6-85875-3	1-87283-1	—	1-85839-1	6-85840-1	A,D,G,K
12	11	**1.716** [43.59]	**1.827** [46.41]	6	1-85923-2	5-85875-4	1-87283-2	—	1-85839-2	6-85840-2	A,C,E,G,J,L
13	12	**1.872** [47.55]	**1.983** [50.37]	4	1-85923-3	6-85875-4	1-87283-3	—	1-85839-3	6-85840-3	A,D,J,M
14	13	**2.028** [51.51]	**2.139** [54.33]	7	1-85923-4	6-85875-5	1-87283-4	—	1-85839-4	6-85840-4	A,C,E,G,J,L,N
15	14	**2.184** [55.47]	**2.295** [58.29]	5	1-85923-5	6-85875-6	1-87283-5	—	1-85839-5	6-85840-5	A,D,G,K,N
16	15	**2.340** [59.44]	**2.451** [62.26]	8	1-85923-6	6-85875-7	1-87283-6	—	1-85839-6	6-85840-6	A,C,E,G,J,L,N,Q
17	16	**2.496** [63.40]	**2.607** [66.22]	6	1-85923-7	6-85875-8	1-87283-7	—	1-85839-7	6-85840-7	A,D,G,K,N,R
18	17	**2.652** [67.36]	**2.763** [70.18]	7	1-85923-8	6-85875-9	1-87283-8	—	1-85839-8	6-85840-8	A,D,F,J,M,P,S
19	18	**2.808** [71.32]	**2.919** [74.14]	8	1-85923-9	7-85875-0	1-87283-9	—	1-85839-9	6-85840-9	B,D,F,J,L,N,Q,S
20	19	**2.964** [75.29]	**3.075** [78.11]	10	2-85923-0	7-85875-1	2-87283-0	—	2-85839-0	7-85840-0	A,C,E,G,J,L,N,Q,S,U
21	20	**3.120** [79.25]	**3.231** [82.07]	7	2-85923-1	7-85875-2	2-87283-1	—	2-85839-1	7-85840-1	A,D,G,K,N,R,U
22	21	**3.276** [83.21]	**3.387** [86.03]	11	2-85923-2	7-85875-3	2-87283-2	—	2-85839-2	7-85840-2	A,C,E,G,J,L,N,Q,S,U,W
23	22	**3.432** [87.17]	**3.543** [89.99]	8	2-85923-3	5-85875-5	2-87283-3	—	2-85839-3	7-85840-3	A,D,G,K,N,R,U,X
24	23	**3.588** [91.14]	**3.699** [93.95]	12	2-85923-4	7-85875-4	2-87283-4	—	2-85839-4	7-85840-4	A,C,E,G,J,L,N,Q,S,U,W,Y
25	24	**3.744** [95.10]	**3.855** [97.92]	11	2-85923-5	7-85875-5	2-87283-5	—	2-85839-5	7-85840-5	A,C,E,H,K,M,Q,S,U,W,Y

Note: All part numbers are RoHS compliant.

Catalog 1307819
Revised 8-08

www.tycoelectronics.com

Dimensions are in inches and millimeters unless otherwise specified. Values in brackets are metric equivalents.

Dimensions are shown for reference purposes only. Specifications subject to change.

USA: 1-800-522-6752
Canada: 1-905-470-4425
Mexico: 01-800-733-8926
C. America: 52-55-1106-0803

South America: 55-11-2103-6000
Hong Kong: 852-2735-1628
Japan: 81-44-844-8013
UK: 44-8706-080-208a

Mod I Headers, Right-Angle Post, Keyed, .031 x .062 [0.79 x 1.57] Centerline

Single Row, .156 [3.96] Centers





Keyway Locations (Ref Only)

Material and Finish

Housing — Black thermoplastic, 94V-0 rated

Posts — Brass, plated as follows:

Plating A — Selectively plated .000030 [0.00076] gold on contact area, with gold flash over .000050 [0.00127] nickel on entire post

Plating B — .000015 [0.00038] gold over .000050 [0.00127] nickel on entire post

Plating C — .000100-.000200 [0.00254-0.00508] tin over .000050 [0.00127] nickel on entire post

Related Product Data

Mate with —
Board Mount Receptacles — pages 285, 286

Board Mount Receptacle Assemblies — pages 287-289

Crimp Snap-In Receptacles and Housings — pages 290-292

Locking Clip Contacts and Housings — pages 298 & 299 (see page 298 for recommended post length).

Performance Specifications — page 305

Technical Documents — page 305



Recommended Board Layout

E Dimension

.345 [8.76] Post Height — .250 [6.35] for mounting header flush with board edge; .595 [15.11] for supporting mating connector on board.

.500 [12.70] Post Height — .250 [6.35] for mounting header flush with board edge; .750 [19.05] for supporting mating connector on board.

No. of Pos.	Dimensions			No. of Keying Slots	Post Height D=.345 [8.76]		Post Height D=.500 [12.70]		Keyway Locations
	A	B	C		Plating A	Plating C	Plating B	Plating C	
2	1	**.156** [3.96]	**.267** [6.78]	1	87654-2	5-87655-2	87258-2	5-87194-1	A
3	2	**.312** [7.92]	**.423** [10.74]	1	87654-3	5-87655-3	87258-3	5-87194-2	A
4	3	**.468** [11.89]	**.579** [14.71]	2	87654-4	5-87655-4	87258-4	5-87194-3	A,C
5	4	**.624** [15.85]	**.735** [18.67]	2	87654-5	5-87655-5	87258-5	5-87194-4	A,D
6	5	**.780** [19.81]	**.891** [22.63]	3	87654-6	5-87655-6	87258-6	5-87194-5	A,C,E
7	6	**.936** [23.77]	**1.047** [26.59]	3	87654-7	5-87655-7	87258-7	5-87194-6	A,C,E
8	7	**1.092** [27.74]	**1.203** [30.56]	4	87654-8	5-87655-8	87258-8	5-87194-7	A,C,E,G
9	8	**1.248** [31.70]	**1.359** [34.52]	3	87654-9	5-87655-9	87258-9	5-87194-8	A,D,G
10	9	**1.404** [35.66]	**1.515** [38.48]	5	1-87654-0	6-87655-0	1-87258-0	5-87194-9	A,C,E,G,J
11	10	**1.560** [39.62]	**1.671** [42.44]	4	1-87654-1	6-87655-1	1-87258-1	6-87194-0	A,D,G,K
12	11	**1.716** [43.59]	**1.827** [46.41]	6	1-87654-2	6-87655-2	1-87258-2	6-87194-1	A,C,E,G,J,L
13	12	**1.872** [47.55]	**1.983** [50.37]	4	1-87654-3	6-87655-3	1-87258-3	6-87194-2	A,D,J,M
14	13	**2.028** [51.51]	**2.139** [54.33]	7	1-87654-4	6-87655-4	1-87258-4	6-87194-3	A,C,E,G,J,L,N,
15	14	**2.184** [55.47]	**2.295** [58.29]	5	1-87654-5	6-87655-5	1-87258-5	6-87194-4	A,D,G,K,N
16	15	**2.340** [59.44]	**2.451** [62.26]	8	1-87654-6	6-87655-6	1-87258-6	6-87194-5	A,C,E,G,J,L,N,Q
17	16	**2.496** [63.40]	**2.607** [66.22]	6	1-87654-7	6-87655-7	1-87258-7	6-87194-6	A,D,G,K,N,R
18	17	**2.652** [67.36]	**2.763** [70.18]	7	1-87654-8	6-87655-8	1-87258-8	6-87194-7	A,D,F,J,M,P,S
19	18	**2.808** [71.32]	**2.919** [74.14]	8	1-87654-9	6-87655-9	1-87258-9	6-87194-8	B,D,F,J,L,N,Q,S
20	19	**2.964** [75.29]	**3.075** [78.11]	10	2-87654-0	7-87655-0	2-87258-0	6-87194-9	A,C,E,G,J,L,N,Q,S,U
21	20	**3.120** [79.25]	**3.231** [82.07]	7	2-87654-1	7-87655-1	2-87258-1	7-87194-0	A,D,G,K,N,R,U
22	21	**3.276** [83.21]	**3.387** [86.03]	11	2-87654-2	7-87655-2	2-87258-2	7-87194-1	A,C,E,G,J,L,N,Q,S,U,W
23	22	**3.432** [87.17]	**3.543** [89.99]	8	2-87654-3	7-87655-3	2-87258-3	7-87194-2	A,D,G,K,N,R,U,X
24	23	**3.588** [91.14]	**3.699** [93.95]	12	2-87654-4	7-87655-4	2-87258-4	7-87194-3	A,C,E,G,J,L,N,Q,S,U,W,Y
25	24	**3.744** [95.10]	**3.855** [97.92]	11	2-87654-5	7-87655-5	2-87258-5	7-87194-4	A,C,E,H,K,M,Q,S,U,W,Y

Note: All part numbers are RoHS compliant.

Catalog 1307819
Revised 8-08

www.tycoelectronics.com

Dimensions are in inches and millimeters unless otherwise specified. Values in brackets are metric equivalents.

Dimensions are shown for reference purposes only. Specifications subject to change.

USA: 1-800-522-6752
Canada: 1-905-470-4425
Mexico: 01-800-733-8926
C. America: 52-55-1106-0803

South America: 55-11-2103-6000
Hong Kong: 852-2735-1628
Japan: 81-44-844-8013
UK: 44-8706-080-208a

Locking Clip Contacts for .031 x .062 [0.79 x 1.57] Posts, .031 x .062 [0.79 x 1.57] Centerline

Wire Crimp Contacts with Insulation Support

Material and Finish

Contact Body — Phosphor bronze, plated as follows:

Plating A — Selectively plated .000015 [0.00038] gold on contact area, with gold flash over .000050 [0.00127] nickel on entire post

Plating B — .000100 [0.00254] min. tin over .000050 [0.00127] nickel on entire contact

Contact Spring — Stainless steel

Related Product Data

Mate with —
Machine Applied Posts — page 294
Headers (.500 Post Height Only) — pages 295-297 (see recommended post length below)*
Housings used in — page 299
Application Tooling — pages 300-304
Performance Specification — page 305

Technical Documents — page 305

Extraction Tool Part No. 91104-1

Instruction Sheet
408-7678



Wire Size Range AWG [mm²]	Ins. Dia. Range	Finish	Contact Part Nos. Strip Form	Contact Part Nos. Loose Piece
22-18 [0.3-0.9]	**.050-.0100** [1.27–2.54]	Plating A	87269-2	87278-2
		Plating B	5-87269-1	5-87278-1

Wire Size Range AWG [mm²]	Applicator Part Number	Applicator Type	Applicator Used With Machine	Premium CERTI-CRIMP Hand Tool Part Number
22-18 [0.3-0.9]	466007-2	HDM	Model "K" (AMP-O-LECTRIC)[1]	90308-1
	466950-2	SCA	Stripper/Crimper (AMP-O-MATIC)	

[1]AMP-O-LECTRIC KII Machine. Applicators also available for AMPOMATOR Lead Making Machines. Consult Tyco Electronics.

Note: These contacts must be crimped in accordance with Tyco Electronics Specification No. 114-25008 in order to function properly in a connector housing.

Extraction Tool **Part No. 91104-1** is used for removing individual contacts from connector housings and for detaching contacts from mating posts.

Wire Harnessing

If necessary, wires can be grouped with cable ties and secured to a panel with fixed clamps. However, locking clip contacts must be free to float within the connector housings to allow proper extraction. Therefore, harnessing hardware or the use of multiple terminations per contact must not restrict the free-floating action of contacts in the housing. For more information, request Insulating and Bundling Products Catalog 124132.



*Dimension defines .031 x .062 [0.79 x 1.57] portion of post.
If post is longer than maximum specified, post tip may butt against wire ends.

Note: All part numbers are RoHS compliant.

Catalog 1307819
Revised 8-08

www.tycoelectronics.com

Dimensions are in inches and millimeters unless otherwise specified. Values in brackets are metric equivalents.

Dimensions are shown for reference purposes only. Specifications subject to change.

USA: 1-800-522-6752
Canada: 1-905-470-4425
Mexico: 01-800-733-8926
C. America: 52-55-1106-0803

South America: 55-11-2103-6000
Hong Kong: 852-2735-1628
Japan: 81-44-844-8013
UK: 44-8706-080-208a

Locking Clip Connector Housings, .031 x .062 [0.79 x 1.57] Centerline

Single Row, .156 [3.96] Centers



Material and Finish
Black thermoplastic, 94V-0 rated

Related Product Data
Contacts used with — page 298
Mate with —
Machine Applied Posts — page 294
Headers — pages 295-297 (see page 298 for recommended post length)
Performance Specifications — page 305

Technical Documents —
page 305



No. of Pos.	Dimensions A	B	C	Housing Part Nos. UnKeyed	Keyed	Keyed Positions on Mating Face
1	—	—	**.200** [5.08]	87270-1	—	—
2	—	—	**.376** [9.55]	87270-2	—	—
3	**.156** [3.96]	**.156** [3.96]	**.532** [13.51]	1-87270-3	—	—
3 of 4	**.156** [3.96]	**.312** [7.92]	**.688** [17.48]	—	87270-3	□□■□
4				87270-4	—	—
4 of 5	**.312** [7.92]	**.312** [7.92]	**.844** [21.44]	—	1-87270-0	□□□■□
5				1-87270-4	—	—
5 of 6	**.312** [7.92]	**.468** [11.89]	**1.000** [25.40]	—	1-87270-2	□□□□■□
6				87270-5	—	—
6 of 7	**.468** [11.89]	**.468** [11.89]	**1.156** [29.36]	—	1-87270-1	□□□□■□□
7				1-87270-5	—	—
8	**.468** [11.89]	**.624** [15.85]	**1.312** [33.32]	87270-6	—	—
9	**.624** [15.85]	**.624** [15.85]	**1.468** [37.29]	1-87270-6	—	—
10	**.624** [15.85]	**.780** [19.81]	**1.624** [41.25]	87270-7	—	—
11	**.780** [19.81]	**.780** [19.81]	**1.780** [45.21]	1-87270-7	—	—
12	**.780** [19.81]	**.936** [23.77]	**1.936** [49.17]	87270-8	—	—

■Indicates "closed cavity". No post entry hole in this position.
Notes: 1. All housings listed above will accept Locking Clip Contacts No. 87269 and 87278, refer to page 298
2. Refer to Tyco Electronics Instruction Sheet 408-7676 for proper contact orientation within the housings.

Note: All part numbers are RoHS compliant.

Catalog 1307819
Revised 8-08

www.tycoelectronics.com

Dimensions are in inches and millimeters unless otherwise specified. Values in brackets are metric equivalents.

Dimensions are shown for reference purposes only. Specifications subject to change.

USA: 1-800-522-6752
Canada: 1-905-470-4425
Mexico: 01-800-733-8926
C. America: 52-55-1106-0803

South America: 55-11-2103-6000
Hong Kong: 852-2735-1628
Japan: 81-44-844-8013
UK: 44-8706-080-208a

Application Tooling

For Crimp Snap-In Receptacles and Locking Clip Contacts

Side-Feed Heavy-Duty Miniature Applicators (Coded HDM)

Interchangeable applicators for crimping products reeled side-by-side on single or dual carrier strips (primarily closed-barrel terminals and open-barrel contacts). Similar design as the end-feed version. All side-feed applicators include a wire stop to help correctly position the wire end in the crimping target area.

For more information, request Instruction Sheet **408-8040**.

AMP-O-LECTRIC Model "G" Terminating Machines, 354500-1, -9, -11

Semiautomatic bench machines for crimping reeled terminals and contacts, featuring a quiet and reliable direct motor drive, microprocessor controls for ease of setup and operation, and guarding and lighting designed for operator convenience and safety. All models are equipped with either manual or automatic precision adjustment of crimp height. Machine-mounted sensors are available for crimp quality monitoring using conventional miniature-style applicators.

Specifications

Width — 18.7-25.3 [475-643] depending on applicator type

Depth — 21.5-28.1 [546-713] depending on applicator type

Height — 20 [508]

Weight — 240 lb [110 kg]

Electrical — 120 or 220 VAC, 50 or 60 Hz; 310 VA

Air — 90-110 psi [6.21-7.59 bar], 6 scfm [0.00282 m^3/s] when required with air-feed applicators

Wire Range — 26-10 AWG [0.12-6 mm^2] solid or stranded, depending on product applied

For more information, request Catalog **65828**, Video **198116**, Catalog **82275 [Crimp Quality Monitor (CQM)],** Video **198094.**

AMPOMATOR CLS IV+ Lead-Making Machines, 356500-1, -2, 1213400-1, -2

Fully-automatic machines that measure, cut, strip and terminate single leads. Microprocessor-controlled, and programmed and operated using an easy-to-follow, menu-driven touchscreen. Features include direct-drive terminating units with precision crimp height adjustment, fully programmable setups, wire runout and splice detection, and motorized pre-feed with wire straightener. Crimp quality monitoring is also available.

Specifications

Width — 159 [4 040]

Depth — 68 [1 730]

Height — 86 [2 185] with 24 [610] dia. reel

Weight — 2 000 lb [907 kg]

Electrical — 220 VAC, 50 or 60 Hz, single phase, 25 A, with neutral and ground

Air — 90 psi [6.21 bar], 15 scfm [0.0071 m^3/s] sustained

Wire Range — 26-10 AWG [0.12-6 mm^2] stranded, 26-16 AWG [0.12-1.4 mm^2] solid

Lead Lengths — 3-90 [76.2-2 285], 90-1 000 [2 285-25 400] with long lead conveyors

For more information, request Catalog **124324**, Video **198142** (NTSC)**, 199609** (PAL).

Note: All part numbers are RoHS compliant.

Note: For additional tooling options, contact Tyco Electronics or reference the Tyco Electronics web site.

Catalog 1307819
Revised 8-08

www.tycoelectronics.com

Dimensions are in inches and millimeters unless otherwise specified. Values in brackets are metric equivalents.

Dimensions are shown for reference purposes only. Specifications subject to change.

USA: 1-800-522-6752
Canada: 1-905-470-4425
Mexico: 01-800-733-8926
C. America: 52-55-1106-0803

South America: 55-11-2103-6000
Hong Kong: 852-2735-1628
Japan: 81-44-844-8013
UK: 44-8706-080-208a

Application Tooling (Continued)

For Crimp Snap-In Receptacles and Locking Clip Contacts (Continued)

AMP-O-MATIC Stripper-Crimper Machines, 854040-3, -4

Semiautomatic bench crimping machines that also strip the wire, and are therefore used for terminating jacketed cable. Feature manual precision adjustment of crimp height, keyed strip blades for faster, more accurate setups, and an efficient scrap removal system. All adjustments can be made from the front of the machines without special tools. Available with crimp quality monitoring.

Specifications

Width—14 [355]

Depth—18 [457]

Height—33 [838] without reel

Weight—150 lb [68 kg]

Electrical—120 VAC, 50 or 60 Hz, .5 A

Air—80-100 psi [5.52-6.90 bar], 3.5 scfm [0.00165 m^3/s]

Wire Range—32-14 AWG [0.03-2 mm^2]

For more information, request Catalog **65004**, Video **198075,** Catalog **82275 [Crimp Quality Monitor (CQM)],** Video **198094.**

Stripper-Crimper Applicators (coded SCA)

Interchangeable applicators for crimping products in AMP-O-MATIC Stripper-Crimper Machines. Consist of separate ram and lower tooling assemblies. Similar dial-in settings for different wire sizes and insulation diameters as HDM applicators. Available with sensors for use with the Crimp Quality Monitor.

For more information, request Catalog **65004 (AMP-O-MATIC Stripper-Crimper Machines)**, Catalog **82275 [Crimp Quality Monitor (CQM)]**.

Kappa 235, Automatic Cut and Strip, 3-547178-1

The Kappa 235 has the capability of processing wires with a cross section of up to 4 AWG and an outside diameter of 0.59 inch. Options include an inner conductor processing kit for multiconductor cables and a flat ribbon cable kit.

Specifications

Width—25 [630]

Depth—16 [490]

Height—13.4 [370]

Weight—95 lb [44 kg]

Wire Cross-Sections—24-4 AWG [0.22-25 mm^2]

Flat Ribbon Cables—width up to 40mm

Length Range—0.04"-328ft [1mm - 99.99m] (+/- 0.2%)

Electrical—110/230 V - 50/60Hz, switches automatically

Cosmic 927R Micro-Cable Stripper

The Cosmic 927R Micro-Cable Stripper was developed to reliably strip various insulation materials and micro-cable. From conductor diameter 36 AWG to 10 AWG, the stripping diameter display can be set to within 0.1mm increments.

Thus optimal stripping quality is guaranteed and damage to the conductor is eliminated.

Note: All part numbers are RoHS compliant.

Note: For additional tooling options, contact Tyco Electronics or reference the Tyco Electronics web site.

Catalog 1307819
Revised 8-08

www.tycoelectronics.com

Dimensions are in inches and millimeters unless otherwise specified. Values in brackets are metric equivalents.

Dimensions are shown for reference purposes only. Specifications subject to change.

USA: 1-800-522-6752
Canada: 1-905-470-4425
Mexico: 01-800-733-8926
C. America: 52-55-1106-0803

South America: 55-11-2103-6000
Hong Kong: 852-2735-1628
Japan: 81-44-844-8013
UK: 44-8706-080-208a

Application Tooling (Continued)

For Crimp Snap-In Receptacles and Locking Clip Contacts (Continued)

CERTI-CRIMP Straight Action Hand Tools (SAHT)

Premium grade hand tools. Feature ratchet control to provide complete crimp cycle. Die sets close in a straight line. Include a contact locator and wire stop, plus an insulation crimp adjustment lever, when applicable. Approximate weight 1.3 lb [0.59 kg]

All CERTI-CRIMP head assemblies / dies, have multiple power options available. The accompanying diagram outlines those power options. See catalogs 1654714 (SDE Electric Terminator), 124208 (626 Pneumatic Tool System) and 1773381(Battery-Powered Crimp Tool Kits) for more information.

For more information, request Catalog **65780**.

PRO-CRIMPER III Hand Tool

Commercial grade hand tool for crimping various products. Features ratchet control to provide complete crimp cycle. Accepts both pinned- and shouldered-style die sets. Locators are provided with pinned-style die sets for proper contact and wire positioning, and to help minimize contact rotation and bending during crimping. Approximate weight 1.3 lb [0.60 kg].

All PRO-CRIMPER head assemblies / dies, have multiple power options available. The accompanying diagram outlines those power options. See catalogs 1654714 (SDE Electric Terminator), 124208 (626 Pneumatic Tool System) and 1773381(Battery-Powered Crimp Tool Kits) for more information.

Instruction Sheet
408-9930

Note: For additional tooling options, contact Tyco Electronics or reference the Tyco Electronics web site.

Catalog 1307819
Revised 8-08

www.tycoelectronics.com

Dimensions are in inches and millimeters unless otherwise specified. Values in brackets are metric equivalents.

Dimensions are shown for reference purposes only. Specifications subject to change.

USA: 1-800-522-6752
Canada: 1-905-470-4425
Mexico: 01-800-733-8926
C. America: 52-55-1106-0803

South America: 55-11-2103-6000
Hong Kong: 852-2735-1628
Japan: 81-44-844-8013
UK: 44-8706-080-208a

Application Tooling (Continued)

For Board Mount Receptacles and Machine Applied Posts

Modular Insertion System (MIS) Bench Machines, 217600 Series, 662820 Series (shown)

For Board Mount Receptacles

Bench machines for inserting a variety of products into pc boards. Uses the same interchangeable insertion heads as the Comp-U-Sertor II Machines. Series 217600 machines feature a manually-operated X-Y positioning fixture, plus a locator spotlight. The machine cycles when the board hole is placed on the anvil and both triggers on the dual handles attached to the X-Y fixture are depressed. Series 662820 machines, without board fixturing, cycle automatically when the hole is properly located. A stabilizing disk over the anvil helps keep the board level.

This benchtop insertion machine installs contacts into PC boards at rates to 2000 per hour. A spotlight highlights the insertion area, and lower tooling assures precise board location. The machine is activated by a foot pedal.

Specifications

Width — 18 [457]
Depth — 24 [610]
Height — 18 [457]
Weight — 250 lb [113 kg]
Electrical — 120 to 220 VAC, 50 or 60 Hz (217600); 120 or 240 VAC, 60 Hz, single phase, 120 VA (662820)
Air — 80 psi [5.52 bar] min., 15 scfm [0.00708 m^3/s] min.
Insertable Area — 18 x 22 [457 x 559] max.
For more information, request Catalog **296059**.

P300 Automatic Insertion Machine

Automatic machine for inserting a variety of contacts into pc boards (PCBs). Equipped with an insertion tool (comprised of a product-specific insertion head, an anvil, and a product feed mechanism). Stepper-motor driven X-Y table positions PCBs under insertion head. Surface Mount Equipment Manufacturers Association (SMEMA) compatible inline PCB Insertion Station for posts, tabs, receptacles or sockets. Stand-alone unit is field upgradeable to Pass Through. Mounts up to four Tyco Electronics pneumatic insertion heads. Modem diagnostics standard, vision system optional. Control panel used to program and monitor entire insertion process.

Specifications

Width — 57.5 [1 460]
Depth — 64.5 [1 640]
Height — 60 [1 520]
Weight — Depending on configuration
Electrical — 110 V, 60 Hz
Air — 87 psi [6 bar]
Insertable Area — 24 x 16 [600 x 400]
For more information, contact Tyco Electronics.

Note: All part numbers are RoHS compliant.

Note: For additional tooling options, contact Tyco Electronics or reference the Tyco Electronics web site.

Catalog 1307819
Revised 8-08

www.tycoelectronics.com

Dimensions are in inches and millimeters unless otherwise specified. Values in brackets are metric equivalents.

Dimensions are shown for reference purposes only. Specifications subject to change.

USA: 1-800-522-6752
Canada: 1-905-470-4425
Mexico: 01-800-733-8926
C. America: 52-55-1106-0803

South America: 55-11-2103-6000
Hong Kong: 852-2735-1628
Japan: 81-44-844-8013
UK: 44-8706-080-208a

Application Tooling (Continued)

For Board Mount Receptacles and Machine Applied Posts (Continued)

P350 Pin Insertion Machine

The P350 is a fully automatic inline pin insertion machine capable of applying reeled pins, tabs, receptacles and similar products into PCBs. With inline operation, an automatic tool changer and insertion rates up to 5 per second, it is focused at fully automatic high speed operation to maximize throughput while minimizing costly scrap.

A servo powered XY table positions the PCB under a central drive station at high speed. The tool changer can hold up to 3 insertion heads each capable of applying a different product. A unique rotary insertion finger allows the application of products at up to 7 different angles without rotating the PCB. This allows the P350 to apply product at different angles without a reduction in insertion rate or the potential positioning error associated with PCB rotation. Icon driven software with touch screen provides a simple to use, intuitive operator interface.

The P350 provides a wide range of solutions for pin insertion applications. Quick change tooling packs, and a wide range of options make it a flexible high speed platform.

Specifications

Width — 102 [2600]
Depth — 118 [3000]
Height — 87 [2200]
Weight — approx 3500 lb [1600 kg]
Electrical — 230 V, 50-60 Hz, 10 A
Air — 600 kPa dried air
Max. Board Size — 17.5 x 17.5 [450 x 450]

Catalog 1307819
Revised 8-08

www.tycoelectronics.com

Dimensions are in inches and millimeters unless otherwise specified. Values in brackets are metric equivalents.

Dimensions are shown for reference purposes only. Specifications subject to change.

USA: 1-800-522-6752
Canada: 1-905-470-4425
Mexico: 01-800-733-8926
C. America: 52-55-1106-0803

South America: 55-11-2103-6000
Hong Kong: 852-2735-1628
Japan: 81-44-844-8013
UK: 44-8706-080-208a

Performance Specifications

The electrical, mechanical and environmental characteristics of the AMPMODU .031 x .062 [0.79 x 1.57] Interconnection System are listed below:

Mechanical Characteristics

Contact Durability

Plating	Receptacles		Locking Clip Contacts
	Standard Pressure	High Pressure	
.000016 [0.00041] Min. Tin	75 Cycles	25 Cycles	N/A
.000079 [0.00201] Min. Tin	75 Cycles	25 Cycles	N/A
.000100 [0.00254] Min. Tin	N/A	N/A	25 Cycles
.000015 [0.00038] Gold	75 Cycles	50 Cycles	25 Cycles
.000030 [0.00076] Gold	200 Cycles	100 Cycles	N/A

Electrical Characteristics

Contact Current Rating —
5 amperes max. for single contact in free air, could vary due to ambient temperature, wire size and duty cycles.

Contact Resistance —
12 milliohms at 100 ma and 50 mv open circuit.

Dielectric Rating —
At Sea Level – 1200 VAC between contacts on .156 [3.96] centers for 1 minute.

Insulation Resistance — 5 x 10^3 megohms (initial)

Connector Durability

Receptacles	
Mating	– 16 oz. [4.45N] max. per contact after 3 mating cycles (standard pressure)
	–30 oz. [8.34N] max. per contact after 3 mating cycles (high pressure, gold)
	–60 oz. [16.68N] max. per contact after 3 mating cycles (high pressure, tin)
Unmating	– 1 oz. [0.28N] min. per contact after 3 mating cycles (standard pressure)
	3 oz. [0.83N] min. per contact after 3 mating cycles (high pressure)
Locking Clip Contacts	
Mating	– 4 lb. [17.79N] max. per contact after 3 mating cycles
Unmating	– 2 lb. [8.90N] min. per contact after 3 mating cycles

Environmental Characteristics

Operating Temperature — -65°C to 105°C [-85°F to 221°F] (Gold Plated)
-65°C to 60°C [-85°F to 140°F] (Tin Plated)

Technical Documents

Various technical documents are available for your use:

Product Specifications describe technical performance characteristics and verification tests. They are intended for the Design, Component and Quality Engineer.

108-25016 Interconnection System, Standard Pressure
108-25025 Interconnection System, High Pressure, Gold
108-25025-1 Interconnection System, High Pressure, Tin
108-36029 Locking Clip Connectors

Application Specifications describe requirements for using the product in its intended application and/or crimping information. They are intended for the Packaging and Design Engineer and the Machine Setup Person.

114-25000 Crimp Snap-In Receptacle Contacts
114-25004 Board Mount Receptacle Contacts
114-25008 Locking Clip Contacts
114-25011 Machine Applied Straight Posts

Instruction Sheets provide instructions for assembling or applying the product. They are intended for the Manufacturing Assembler or Operator.

408-7308 Clinching Procedures for Header Assemblies
408-7411 Suggestions for Wave Soldering AMPMODU Receptacles
408-7594 Tyco Electronics Hand Tool 90274-2 for Crimping Crimp Snap-In 18-22 AWG Contacts
408-7750 Tyco Electronics Hand Tool 90328-1 for Crimping Crimp Snap-In Contacts (22-26 AWG)
408-7676 AMPMODU Locking Clip Connectors and Contacts
408-7671 Tyco Electronics Hand Tool 90308-1 for Crimping Locking Clip Contacts
408-7678 Tyco Electronics Extraction Tool 91104-1 for Locking Clip Contacts
408-7981 Clinching Procedures for Receptacle Assemblies
408-9451 Tyco Electronics Extraction Tool 843473-1 for Crimp Snap-In Receptacles

Note: All part numbers are RoHS compliant.

Catalog 1307819
Revised 8-08

www.tycoelectronics.com

Dimensions are in inches and millimeters unless otherwise specified. Values in brackets are metric equivalents.

Dimensions are shown for reference purposes only. Specifications subject to change.

USA: 1-800-522-6752
Canada: 1-905-470-4425
Mexico: 01-800-733-8926
C. America: 52-55-1106-0803

South America: 55-11-2103-6000
Hong Kong: 852-2735-1628
Japan: 81-44-844-8013
UK: 44-8706-080-208a

Shunts

Product Facts

- **7600 Series Programmable Shunts use conventional .100 x .300 [2.54x7.62] DIP leg spacing**
- **Post Shunts are used to common pairs of .025 [0.64] square posts, .025 [0.64] diameter round posts and .022 x .026 [0.56 x 0.66] formed posts**



Tyco Electronics offers a variety of high quality shunts for low cost manual programming. Tyco Electronics 7600 Series Programmable Shunts are designed on the standard .100 x .300 [2.54 x 7.62] DIP spacing.

Tyco Electronics DIP Shunts are a highly reliable, low cost means of manually programming various types of electrical/electronic equipment. The shunt consists of a series of conductive straps packaged in a DIP configuration. The straps can be retained intact for a closed circuit or broken with a hand tool to produce an open circuit.

Tyco Electronics Post Shunts mate with any common pairs of square, rectangular and round posts. Post shunts come in two-position low profile, 2 mm miniature, tandem spring, dual beam, and multiposition versions.

Among the options available are choices of gold or tin plating, beryllium copper or phosphor bronze contact material and shunts with 94V-0 rated housing spaces on .079 [2.00], .100 [2.54] and .200 [5.08] centers with the low profile series requiring only .250 [6.35] clearance from the pc board.

All Tyco Electronics shunts feature one-piece construction for high reliability. All have high normal forces for excellent electrical continuity. For added reliability, Tandem Spring and Dual Beam Shunts have two points of contact in each receptacle.

Catalog 1307819
Revised 8-08

www.tycoelectronics.com

Dimensions are in inches and millimeters unless otherwise specified. Values in brackets are metric equivalents.

Dimensions are shown for reference purposes only. Specifications subject to change.

USA: 1-800-522-6752
Canada: 1-905-470-4425
Mexico: 01-800-733-8926
C. America: 52-55-1106-0803

South America: 55-11-2103-6000
Hong Kong: 852-2735-1628
Japan: 81-44-844-8013
UK: 44-8706-080-208a

Dual In-Line Package (DIP) Shunts — 7600 Series

Standard Shunt
Standard Pressure

Material and Finish

Housing — Glass-filled polyester, UL 94V-0 rated

Contacts — Brass

Finish — Selectively plated .000100 min. tin on solder area over .000050 min. nickel on entire contact

Contact Lead Spacing — .100 x .300 [2.54x7.62]

Lead Length — .140 [3.56] below mounting surface

Housing Color — Black

Programming Tool — See below

Programming Hand Tool
Part No. 435862-1

This tool provides a reliable means of programming DIP shunts. It is rugged, light-weight and dependable. No special skills are required to use this tool.







No. of Pos.	Dimension A		Standard Shunt Standard Pressure
	inch	mm	
4	.400	10.16	1825190-4
6	.600	15.24	1825190-6
7	.700	17.78	1825190-7
8	.800	20.32	1825190-8
9	.900	22.86	1825190-9
10	1.000	25.40	1-1825190-0
12	1.200	30.48	1-1825190-2

Note: All part numbers are RoHS compliant.

Catalog 1307819
Revised 8-08

www.tycoelectronics.com

Dimensions are in inches and millimeters unless otherwise specified. Values in brackets are metric equivalents.

Dimensions are shown for reference purposes only. Specifications subject to change.

USA: 1-800-522-6752
Canada: 1-905-470-4425
Mexico: 01-800-733-8926
C. America: 52-55-1106-0803

South America: 55-11-2103-6000
Hong Kong: 852-2735-1628
Japan: 81-44-844-8013
UK: 44-8706-080-208a

Post Shunts

Product Facts

- One-piece contact construction
- High normal forces
- 94V-0 rated housings
- Gold inlay, gold plate or tin plate over nickel
- Stackable
- Those post shunts indicated are recognized under the component program of Underwriters Laboratories Inc., File No. E28476 and certified by the Canadian Standards Association File No. LR 7189

Tandem Spring Shunts

- Two points of contact provide extra reliability
- Shunts accept posts as short as .175 [4.45]; posts bottom at .330 [8.38]

2mm Mini Shunts

- Stackable on 2mm contact centerline
- Low profile
- Available in strips of 10

Material and Finish — Low Profile and 2mm Shunts

Housing — Glass-filled thermoplastic, black, UL 94V-0 rated

Contacts — Beryllium copper or phosphor bronze, plated .000050 [0.00127] nickel underplate with gold plate in contact area or tin overall

Material and Finish — Tandem Spring Shunts

Housing — Nylon, UL 94V-0 rated

Contacts — Phosphor Bronze

Finish — .000030 [0.00076] nickel underplate with gold inlay in the contact area or tin overall

2-Position, Low Profile Shunts

Economy Shunt
.100 [2.54] Centerline



Configuration	Housing Color	Part Numbers			
		Gold Plate[1] .000015 [0.00038]	Gold Flash[1] .000005 [0.00013]	Tin Plate .000100 [0.00254]	Gold Plate .000030 [0.00076]
Strip of 10	Blue	382811-2	—	—	—
Strip of 10	Black	382811-6	382811-8	382811-5	2-382811-0
Strip of 10	Red	382811-9	—	—	—
Loose Piece	Black	1-382811-6	1-382811-8	—	—

[1]In contact area

Standard Housing Shunt
.200 [5.08] Centerline



Configuration	Housing Color	Part Numbers		
		Gold Plate[1] .000015 [0.00038]	Gold Plate[1] .000030 [0.00076]	Tin Plate .000100 [0.00254]
Strip of 10	Black	531230-2	531230-3	531230-1

[1]In contact area

Note: All part numbers are RoHS compliant.

Catalog 1307819
Revised 8-08

www.tycoelectronics.com

Dimensions are in inches and millimeters unless otherwise specified. Values in brackets are metric equivalents.

Dimensions are shown for reference purposes only. Specifications subject to change.

USA: 1-800-522-6752
Canada: 1-905-470-4425
Mexico: 01-800-733-8926
C. America: 52-55-1106-0803

South America: 55-11-2103-6000
Hong Kong: 852-2735-1628
Japan: 81-44-844-8013
UK: 44-8706-080-208a

Post Shunts (Continued)

2-Position, Low Profile Shunts (Novo) (Continued)

Handle Shunt
.100 [2.54] Centerline



Housing Color	Loose Piece Part Numbers				Type
	Gold Plate[1] .000015 [0.00038]	Gold Plate[1] .000030 [0.00076]	Gold Plate[1] .000050 [0.00127]	Tin Plate .000100 [0.00254]	
Black	881545-1	881545-2	881545-3	4-881545-2	Open Top
Black	880584-1	880584-2	880584-3	880584-4	Closed Top

[1]In contact area

2 mm Mini-Shunt
.079 [2.00] Centerline



Configuration	Housing Color	Part Numbers	
		Gold Plate[1] .000015 [0.00038]	Gold Plate[1] .000030 [0.00076]
Strip of 10	Black	382575-2	382575-3

[1]In contact area

Dual Beam Shunt



Configuration	Housing Color	Part Numbers		Type
		Gold Plate[1] .000015 [0.00038]	Gold Plate[1] .000030 [0.00076]	
Strip of 10	Black	390088-2	390088-1	Open Top
Strip of 10	Blue	390088-4	390088-3	Open Top
Strip of 10	Yellow	—	390088-5	Open Top

[1]In contact area

Note: All part numbers are RoHS compliant.

Catalog 1307819
Revised 8-08

www.tycoelectronics.com

Dimensions are in inches and millimeters unless otherwise specified. Values in brackets are metric equivalents.

Dimensions are shown for reference purposes only. Specifications subject to change.

USA: 1-800-522-6752
Canada: 1-905-470-4425
Mexico: 01-800-733-8926
C. America: 52-55-1106-0803

South America: 55-11-2103-6000
Hong Kong: 852-2735-1628
Japan: 81-44-844-8013
UK: 44-8706-080-208a

Post Shunts (Continued)

Tandem Spring Shunt

.100 [2.54] Centerline



Housing Color	Part Numbers	
	Gold Inlay[1] .000030 [0.00076]	TinPlate .000100 [0.00254]
Black	530153-2	4-530153-1

[1]In contact area

Multiposition Shunts for.025 [0.64] Square Posts

.200 [5.08] Centerline

Housing — Glass-filled polyester
Contacts — Beryllium Copper
Finish — .000030 [.00076] gold in contact area over .000050 [.00127] nickel on entire contact
Current Rating — 2.5 amps



Size	Dimension A		Housing Color	Part Number
	inch	mm		
2x2	.246	6.25	Black	390102-1
2x2	.246	6.25	Red	390102-3
2x3	.396	10.01	Black	390102-2

Note: All part numbers are RoHS compliant.

Catalog 1307819
Revised 8-08

www.tycoelectronics.com

Dimensions are in inches and millimeters unless otherwise specified. Values in brackets are metric equivalents.

Dimensions are shown for reference purposes only. Specifications subject to change.

USA: 1-800-522-6752
Canada: 1-905-470-4425
Mexico: 01-800-733-8926
C. America: 52-55-1106-0803

South America: 55-11-2103-6000
Hong Kong: 852-2735-1628
Japan: 81-44-844-8013
UK: 44-8706-080-208a

Performance Specifications

Dual In-Line Package (DIP) Shunts — 7600 Series

Current Rating —
Standard pressure — 2 amperes for +20˚C rise above ambient (one conductor per shunt
Machine insertable — 1 ampere for +20˚C rise above ambient (one conductor per shunt)

Insulation Resistance — 1x 10^{10} ohms min. at 100 VDC

Dielectric Withstanding Voltage — 500 VDC min.

Capacitance — 2 picofarads max. between adjacent straps

Temperature Rating — -55˚C to +105˚C

Terminal Strength (Bend Test) — Two 45˚ bend cycles per MIL-STD-202, Method 211, Condition B

Solder Bridging —
Cut straps can be reconnected by solder bridging. Solder bridging recommendations are:

- Use low temperature solder (60/40 tin/lead)
- Use solder tip approximately 1/32 [0.79] in diameter
- Do not let solder tip come in contact with plastic material

Post Shunts

Current Rating —
3 amperes max. unless otherwise noted

Temperature Rating — -65˚C to +105˚C (gold) -40˚C to +85˚C (tin)

Technical Documents

Various technical documents are available for your use:

Product Specifications describe technical performance characteristics and verification tests. They are intended for the Design, Component and Quality Engineer.

108-7533	Dual In-Line Package (DIP) Shunts
108-1445	2mm Mini Shunt
108-1476	Economy Shunt, Multiposition Shunt
108-1674	Dual Beam Shunt
108-9057	Low Profile Shunt
108-9062	Tandem Spring Shunt
108-37006	Novo Shunt with Handle

Application Specifications describe requirements for using the product in its intended application and/or crimping information. They are intended for the Packaging and Design Engineer and the Machine Setup Person.

114-1045	Tandem Spring Shunt
114-1054	Dual In-Line Package (DIP) Shunts
114-1059	Economy Shunt, Dual Beam Shunt, Low Profile Shunt, Multiposition Shunt
114-1074	2mm Mini Shunt

Instruction Sheets provide instructions for assembling or applying the product. They are intended for the Manufacturing Assembler or Operator.

408-7768	Dual In-Line Package (DIP) Shunts
408-3208	Tandem Spring Shunt
408-3230	Economy Shunt, Dual Beam Shunt, Low Profile Shunt
408-3251	Multiposition Shunt
408-3276	2mm Mini Shunt

Catalog 1307819
Revised 8-08

www.tycoelectronics.com

Dimensions are in inches and millimeters unless otherwise specified. Values in brackets are metric equivalents.

Dimensions are shown for reference purposes only. Specifications subject to change.

USA: 1-800-522-6752
Canada: 1-905-470-4425
Mexico: 01-800-733-8926
C. America: 52-55-1106-0803

South America: 55-11-2103-6000
Hong Kong: 852-2735-1628
Japan: 81-44-844-8013
UK: 44-8706-080-208a

Engineering Notes

Catalog 1307819
Revised 8-08

www.tycoelectronics.com

Dimensions are in inches and millimeters unless otherwise specified. Values in brackets are metric equivalents.

Dimensions are shown for reference purposes only. Specifications subject to change.

USA: 1-800-522-6752
Canada: 1-905-470-4425
Mexico: 01-800-733-8926
C. America: 52-55-1106-0803

South America: 55-11-2103-6000
Hong Kong: 852-2735-1628
Japan: 81-44-844-8013
UK: 44-8706-080-208a

Part Number Index

Note: This index lists all cataloged parts by base no. only. Complete part nos. (with prefixes and/or suffixes) are shown on the page(s) indicated.

Part No.	Page
19156	139, 140
57013	58
57038	58
57118	58
57119	58
57131	58, 59
57138	58
57139	58
57144	58
57145	58
57288	58
57289	58
57290	58
85487	286
85493	286
85829	295
85839	296
85840	296
85875	296
85923	296
85969	213
86016	213
86147	294
86177	216
86181	285, 287, 288
86182	294
86207	296
86286	169, 172, 175-177, 180, 182, 189, 191, 195-197, 214-218, 220, 256, 257
86432	286
86434	286
86477	286
86479	98, 99
86480	286
86492	213
87003	286
87022	163
87025	291
87046	213
87077	214-218, 220, 256, 257
87105	286
87107	211
87116	293
87124	207
87131	209
87132	209
87133	209
87159	293
87160	295
87165	207
87175	208
87176	209
87179	208, 209
87190	207
87191	207
87194	297
87195	213
87215	96, 97
87220	85, 93
87224	93
87227	85, 96, 97
87230	85, 98, 99
87232	85, 94, 95, 210, 221
87233	94, 95
87247	295
87258	297
87262	295
87269	298
87270	299
87278	298
87283	296
87309	213
87316	286
87456	210, 216
87474	129
87483	210
87496	133
87499	210, 214
87523	213
87568	127
87572	126
87577	124, 125
87579	122, 123
87587	119, 120
87589	117, 118
87605	85, 131
87608	130
87623	163
87631	210, 218, 219
87654	297
87655	297
87666	213
87667	213
87710	218
87733	219
87743	204
87756	210, 213
87772	286
87774	286
87809	213
87878	163
87879	85, 177
87921	218
87922	218, 219
87977	210, 217
87983	287
87984	287
87985	287
87986	287
87987	289
87988	289
87989	287
87990	287
87993	287
87995	289
102055	126
102090	292
102095	211
102099	290
102100	290
102102	290
102103	290
102104	290
102106	290
102107	211
102114	203
102128	210, 213
102185	255, 258, 259
102198	139, 140
102202	115, 210
102203	85, 116
102241	210, 215
102312	258, 259
102316	213
102338	203
102348	211
102387	210, 220
102393	256
102394	256
102395	265
102396	255, 259
102398	255, 256
102399	265
102448	256
102449	265
102523	116
102536	255, 259
102537	255, 259
102540	255, 259
102541	255, 259
102548	213
102557	149
102567	198
102570	124, 125
102589	193, 200
102617	122, 123
102618	117, 118
102619	119, 120
102620	127
102641	265
102642	265
102666	199
102681	255, 259
102690	193, 199
102691	199
102692	198
102693	257
102694	257
102695	257
102699	85, 148
102742	177
102766	142
102777	199
102783	262, 263
102784	262, 263
102785	262, 263
102786	262, 263
102787	262, 263
102788	262, 263
102789	263
102791	264
102792	264
102802	200
102823	259

Catalog 1307819
Revised 8-08

www.tycoelectronics.com

Dimensions are in inches and millimeters unless otherwise specified. Values in brackets are metric equivalents.

Dimensions are shown for reference purposes only. Specifications subject to change.

USA: 1-800-522-6752
Canada: 1-905-470-4425
Mexico: 01-800-733-8926
C. America: 52-55-1106-0803

South America: 55-11-2103-6000
Hong Kong: 852-2735-1628
Japan: 81-44-844-8013
UK: 44-8706-080-208a

Part Number Index (Continued)

Part No.	Page
102826	144
102871	143
102898	146
102903	263
102917	213
102918	213
102920	213
102935	280
102972	107
102973	107
102976	107
102977	107
102985	263
102987	261, 263
102988	261, 263
102991	264
103056	281
103058	281
103080	115
103136	261, 263
103137	261, 263
103138	262, 263
103139	262, 263
103140	262, 263
103141	262, 263
103152	261, 263
103153	261, 263
103157	261, 263
103158	261, 263
103164	85, 126
103165	127
103166	85, 122, 123, 210, 255
103167	124, 125
103168	85, 117, 118, 210, 255
103169	119, 120
103171	213
103185	107
103186	107
103233	147
103239	107
103240	107
103264	193, 201
103268	259
103291	199
103321	107
103322	107
103327	107
103328	107
103336	85, 146
103340	261, 263
103341	261, 263
103349	281
103350	281
103361	116
103414	85, 115
103455	213
103542	85, 147
103577	85, 163
103634	247
103635	247
103639	245
103640	231
103641	231
103644	231
103645	231
103648	233
103649	233
103650	233
103651	233
103652	233
103653	237
103654	239
103655	239
103656	239
103657	239
103658	237
103659	237
103660	237
103661	237
103669	245
103672	247
103673	247
103680	240
103681	241
103682	242
103684	229
103685	229
103686	229
103687	229
103688	221, 229
103734	231
103735	245
103817	86, 100
103893	237
103894	237
103895	239
103896	239
103897	231
103900	233
103901	233
103902	229
103903	229
103904	247
103908	245
103911	39
103916	35
103944	237
103945	237
103946	237
103947	237
103948	237
103949	237
103950	239
103951	239
103952	239
103953	239
103954	239
103955	239
103956	231
103957	231
103958	231
103959	231
103960	231
103961	231
103968	233
103969	233
103970	233
103971	233
103972	233
103973	233
103974	229
103975	229
103976	229
103977	229
103978	229
103979	229
104068	30
104069	29
104071	28
104074	27
104076	31
104078	40
104118	34
104178	33
104186	32
104192	38
104196	37
104257	221, 231
104271	261, 263
104272	261, 263
104317	121
104319	128
104361	250
104362	245
104363	245
104438	234
104439	234
104450	221, 248
104477	29
104479	221, 222, 253
104480	221, 222, 253
104481	221, 222, 253
104482	221, 223
104483	224
104500	241
104503	239
104505	254
104506	254
104549	44
104550	45
104583	282
104584	282
104652	15
104655	16
104656	16
104666	30
104693	16
104744	40
104804	28
104809	249
104891	22
104892	21
104893	21
104894	19
104895	19
104905	208
104909	245
104910	245
104935	247
111196	56
146079	163
146128	109
146129	109
146130	110
146131	110
146132	86, 109
146133	109
146134	86, 110
146135	110
146138	178
146205	202
146250	104, 107
146252	104, 107
146253	104, 107
146254	104, 107
146256	104, 107
146257	85, 104, 107
146258	104
146260	104
146261	104
146262	104
146264	104
146265	104
146266	104
146268	85, 104
146269	104
146270	104
146272	104
146273	104
146274	102, 107
146276	102, 107
146277	102, 107
146278	102, 107
146280	102, 107
146281	85, 102, 107
146282	102
146284	102
146285	102
146286	102
146288	102
146289	102
146290	102
146292	102
146293	85, 102
146294	102
146296	102
146297	102
146304	85, 103
146305	103
146306	85, 103
146307	103
146308	85, 105
146309	105
146310	105
146311	105
146315	202

Catalog 1307819
Revised 8-08

www.tycoelectronics.com

Dimensions are in inches and millimeters unless otherwise specified. Values in brackets are metric equivalents.

Dimensions are shown for reference purposes only. Specifications subject to change.

USA: 1-800-522-6752
Canada: 1-905-470-4425
Mexico: 01-800-733-8926
C. America: 52-55-1106-0803

South America: 55-11-2103-6000
Hong Kong: 852-2735-1628
Japan: 81-44-844-8013
UK: 44-8706-080-208a

Part Number Index (Continued)

Part No.	Page
146386	175
146427	85
146455	112
146456	112
146457	112
146458	112
146459	112
146460	112
146461	112
146462	112
146463	112
146464	112
146465	112
146466	112
146467	112
146468	112
146469	112
146470	112
146471	112
146472	112
146473	112
146474	86, 112
146475	112
146476	112
146477	112
146478	112
146479	112
146480	112
146481	112
146482	112
146483	113
146484	113
146485	113
146486	113
146487	113
146488	113
146489	113
146490	85, 113
146491	113
146492	113
146493	113
146494	113
146495	113
146496	113
146497	113
146498	113
146499	113
146500	113
146501	113
146502	113
146503	113
146504	113
146505	113
146506	113
146507	113
146508	113
146509	113
146510	113
146762	176
146763	175
146850	107
146851	107

Part No.	Page
146852	107
146853	107
146858	107
146859	107
146860	107
146861	107
146868	107
146869	107
146870	107
146871	107
147030	235
147070	86, 167
147071	167
147072	167
147095	183, 184
147096	183, 184
147099	182
147100	182
147101	190
147102	190
147103	190
147104	192
147105	86, 192
147106	192
147121	16
147254	202
147278	251
147323	251
147324	251
147326	177
147333	86, 165
147334	165
147335	165
147377	44
147378	45
147381	16
147382	16
147383	16
147384	15
147396	235
147413	15
147424	176
147433	165
147434	165
147435	165
147436	167
147437	167
147438	167
147503	16
147720	86, 181
147723	188
147724	187
147726	181
147727	181
147728	188
147729	188
147730	187
147731	187
147736	188
147737	188
147738	86, 188
147739	192

Part No.	Page
147740	192
147741	192
147742	187
147743	187
147744	187
147745	190
147746	190
147747	190
173144	155, 156
173145	155, 157, 158, 159
173146	155, 160, 161
219054	58
219055	58
219137	58
219138	58
219253	58
382575	309
382811	308
390088	309
390102	310
487544	50
487545	50
487547	48
487576	54
487923	48
487937	52
487938	52
487940	48
487941	48
499991	205
530153	310
530554	267
530901	269
530902	268
531226	267, 268
531230	308
532955	195
532956	193, 195
533009	195
534204	195
534206	85, 176
534237	85, 175
534245	200
534257	198
534258	201
534267	85, 182
534972	193, 196
534974	193, 197
534975	195
534978	198
534998	85, 179, 180
535541	85, 178
535542	86, 183, 184
535584	178
535585	179, 180
535598	179, 180
746383	139, 140
867052	207
880584	309
881545	309
966926	72
1375549	252

Part No.	Page
1375582	252
1375583	252
1375791	7, 12
1375792	7
1375793	7, 12
1375794	7
1375795	6, 12
1375796	6
1375797	9
1375798	9
1375799	8
1375800	8
1375801	12
1375959	10
1375961	10
1375963	10
1375965	11
1375967	11
1445251	12
1445439	12
1445440	12
1445441	12
1470108	79
1470109	78
1470209	80
1470213	66
1734493	75
1734506	81
1734507	67
1734508	66
1734516	84
1734531	83
1734569	77
1734606	82
1734770	73
1825190	307
1825851	139, 140, 210
2041068	76
2041069	84
5084476	71
5084780	74
5086147	294
5086182	294
5102084	170
5102154	139, 210, 255
5102156	139
5102160	140
5102162	140
5103308	135
5103309	135
5103310	136
5103311	136
5104338	137
5104340	138
5111595	57
5146139	169
5146140	170
5147721	86, 172
5147722	86, 173
5147732	172
5147733	172
5147734	173

Catalog 1307819
Revised 8-08

www.tycoelectronics.com

Dimensions are in inches and millimeters unless otherwise specified. Values in brackets are metric equivalents.

Dimensions are shown for reference purposes only. Specifications subject to change.

USA: 1-800-522-6752
Canada: 1-905-470-4425
Mexico: 01-800-733-8926
C. America: 52-55-1106-0803

South America: 55-11-2103-6000
Hong Kong: 852-2735-1628
Japan: 81-44-844-8013
UK: 44-8706-080-208a

Part Number Index (Continued)

Part No.	Page
5147735	173
5176264	70
5176837	68
5178751	70
5530553	269
5530901	269
5531216	269
5531224	269
5531225	269
5535512	85, 170
5535676	85, 169
5535677	169

Tooling Part Number Index

Note: This index lists all cataloged parts by base no. only. Complete part nos. (with prefixes and/or suffixes) are shown on the page(s) indicated.

Part No.	Page
58062	273
58074	273
58075	273
58336	273
58338	273
58342	254
58395	273
58540	273
58641	211, 213
90273	60
90274	290
90295	207
90308	298
90328	290
90381	211
90431	207
91047	60
91084	207
91085	62
91104	298
91112	62
91169	152
91170	152
91171	152
91200	60
91295	23
91410	263
91419	163
91516	213
91517	211, 213
91518	222, 253
91531	254
91533	207
91541	213
91551	222, 253
104072	253
217600	153, 164, 166, 303
224910	48, 60
265871	152
265964	152
308554	152
312522	274
318619	48, 60
354500	300
354786	275
356484	60
356500	300
380392	152
466007	298
466376	286
466562	213
466571	213
466655	213
466721	207
466723	269
466763	290
466764	290
466812	211
466819	269
466905	213
466918	213
466921	213
466937	290
466943	269
466950	298
466952	269
466980	222, 253
466981	222, 253
466982	222, 253
466983	254
527116	263
543518	23
547178	301
565967	286
567239	254
567296	222, 253
567297	222, 253
567298	222, 253
567307	211
567310	207
662820	303
679167	62
679996	207
758030	162
761420	275
768338	62
812665	263
843473	290
843477	253, 254, 265
843996	214, 215, 216, 217, 218, 219, 220
854040	301
854449	274
856002	274
856675	273
904507	163
904590	163
904591	163
904592	163
904640	166
904641	164
907459	162
931800	273
1213400	300

Catalog 1307819
Revised 8-08

www.tycoelectronics.com

Dimensions are in inches and millimeters unless otherwise specified. Values in brackets are metric equivalents.

Dimensions are shown for reference purposes only. Specifications subject to change.

USA: 1-800-522-6752
Canada: 1-905-470-4425
Mexico: 01-800-733-8926
C. America: 52-55-1106-0803

South America: 55-11-2103-6000
Hong Kong: 852-2735-1628
Japan: 81-44-844-8013
UK: 44-8706-080-208a

Engineering Notes

Catalog 1307819
Revised 8-08

www.tycoelectronics.com

Dimensions are in inches and millimeters unless otherwise specified. Values in brackets are metric equivalents.

Dimensions are shown for reference purposes only. Specifications subject to change.

USA: 1-800-522-6752
Canada: 1-905-470-4425
Mexico: 01-800-733-8926
C. America: 52-55-1106-0803

South America: 55-11-2103-6000
Hong Kong: 852-2735-1628
Japan: 81-44-844-8013
UK: 44-8706-080-208a

Engineering Notes

Catalog 1307819
Revised 8-08

www.tycoelectronics.com

Dimensions are in inches and millimeters unless otherwise specified. Values in brackets are metric equivalents.

Dimensions are shown for reference purposes only. Specifications subject to change.

USA: 1-800-522-6752
Canada: 1-905-470-4425
Mexico: 01-800-733-8926
C. America: 52-55-1106-0803

South America: 55-11-2103-6000
Hong Kong: 852-2735-1628
Japan: 81-44-844-8013
UK: 44-8706-080-208a

Tyco Electronics

Global Contacts

Americas

Argentina – Buenos Aires
Phone: +54-11-4733-2200
Fax: +54-11-4733-2211

Brasil – São Paulo
Phone: +55-11-2103-6000
Fax: +55-11-2103-6030

Chile – Santiago
Phone: +56-2-345-0361
Fax: +56-2-223-1477

Canada – Toronto
Phone: +905-475-6222
Fax: +905-474-5520
Product Information Center:
Phone: +905-470-4425
Fax: +905-474-5525

Colombia – Bogota
Phone: +57-1-319-8959
Fax: +57-1-319-8960

Mexico – Mexico City
Phone: +52-55-1106-0800
+01-800-733-8926
Fax: +52-55-1106-0901

For Latin/South American Countries not shown
Phone: +54-11-4733-2015
Fax: +54-11-4733-2083

United States
Harrisburg, PA
Phone: +1-717-564-0100
Fax: +1-717-986-7575
Product Information Center:
Phone: +1-800-522-6752
Fax: +1-717-986-7575

Troy, MI
Phone: +1-248-273-3359
Fax: +1-248-273-3322

Asia/Pacific

Australia – Sydney
Phone: +61-2-9554-2600
Fax: +61-2-9502-2556
Product Information Center:
Phone: +61-2-9840-8200
Fax: +61-2-9634-6188

India – Bangalore
Phone: +91-80-285-40800
Fax: +91-80-285-40820

Indonesia – Jakarta
Phone: +65-6482-0311
Fax: +65-6482-1012

Japan – Kawasaki, Kanagawa
Phone: +81-44-844-8111
Fax: +81-44-812-3207
Product Information Center:
Phone: +81-44-844-8013
Fax: +81-44-812-3200

Korea – Seoul
Phone: +82-2-3415-4500
Fax: +82-2-3486-3810

Malaysia – Selangor
Phone: +60-3-7805-3055
Fax: +60-3-7805-3066

New Zealand – Auckland
Phone: +64-9-634-4580
Fax: +64-9-634-4586

Philippines – Makati City
Phone: +632-848-0171
Fax: +632-867-8661

People's Republic of China
Hong Kong
Phone: +852-2735-1628
Fax: +852-2735-0243

Shanghai
Phone: +86-21-2407-1588
Fax: +86-21-2407-1599

Singapore – Singapore
Phone: +65-6482-0311
Fax: +65-6482-1012

Taiwan – Taipei
Phone: +886-2-8768-2788
Fax: +886-2-8768-2268

Thailand – Bangkok
Phone: +66-2-955-0500
Fax: +66-2-955-0505

Vietnam – Ho Chi Minh City
Phone: +84-8-930-5546
Fax: +84-8-930-3443

Europe/Middle East/Africa

Austria – Vienna
Phone: +43-1-905-60-0
Fax: +43-1-905-60-1333
Product Information Center:
Phone: +43-1-905-60-1249
Fax: +43-1-905-60-1251

Belarus – Minsk
Phone: +375 17 237 47 94
Fax: +375 17 237 47 94

Belgium – Kessel-Lo
Phone: +32-16-352-300
Fax: +32-16-352-355

Bulgaria – Sofia
Phone: +359-2-971-2152
Fax: +359-2-971-2153

Czech Republic and Slovakia
Czech Republic – Kurim
Phone: +420-541-162-111
Fax: +420-541-162-223
Product Information Center:
Phone: +420-541-162-113
Fax: +420-541-162-132

Denmark – Glostrup
Phone: +45-43-48-04-00
Fax: +45-43-44-14-14

Egypt – Cairo
Phone: +202-419-2334
Fax: +202-417-7647

Estonia – Tartu
Phone: +372-5138-274
Fax: +372-7400-779

Finland – Helsinki
Phone: +358-95-12-34-20
Fax: +358-95-12-34-250

France – Cergy-Pontoise Cedex
Phone: +33-1-3420-8888
Fax: +33-1-3420-8600
Product Information Center:
Phone: +33-1-3420-8686
Fax: +33-1-3420-8623

France Export Divisions – Cergy-Pontoise Cedex
Phone: +33-1-3420-8804
Fax: +33-1-3420-8699

Germany – Bensheim
Phone: +49-6251-133-0
Fax: +49-6251-133-1600
Product Information Center:
Phone: +49-6251-133-1999
Fax: +49-6251-133-1988

Greece – Athens
Phone: +30-210-9370-396/397
Fax: +30-210-9370-655

Hungary – Budapest
Phone: +36-1-289-1000
Fax: +36-1-289-1010
Product Information Center:
Phone: +36-1-289-1016
Fax: +36-1-289-1017

Ireland – Dublin
Phone: +353-1-866-5612
Fax: +353-1-866-5714

Israel – Petach-Tikva
Phone: +972-3-929-0999
Fax: +972-3-919-1088

Italy – Collegno (Torino)
Phone: +39-011-4012-111
Fax: +39-011-4031-116
Product Information Center:
Phone: +39-011-4012-428
Fax: +39-011-40-287-428

Lithuania and Latvia
Lithuania – Vilnius
Phone: +370-5-213-1402
Fax: +370-5-213-1403
Product Information Center:
Phone: +370-5-211-3016
Fax: +370-5-213-1403

Netherlands – 's-Hertogenbosch
Phone: +31-73-6246-246
Fax: +31-73-6212-365
Product Information Center:
Phone: +31-73-6246-999
Fax: +31-73-6246-998

Norway – Nesbru
Phone: +47-66-77-88-50
Fax: +47-66-77-88-55

Poland – Warsaw
Phone: +48-22-4576-700
Fax: +48-22-4576-720
Product Information Center:
Phone: +48-22-4576-704
Fax: +48-22-4576-720

Romania – Bucharest
Phone: +40-21-311-3479/3596
Fax: +40-21-312-0574

Russia – Moscow
Phone: +7-495-790-7902
Fax: +7-495-721-1893
Product Information Center:
Phone: +7-495-790-7902-404
Fax: +7-495-790-7902-401

Russia – St. Petersburg
Phone: +7-812-718-8192
Fax: +7-812-718-8193

Slovenia – Ljubljana
Phone: +386-1561-3270
Fax: +386-1561-3240

South Africa – Port Elizabeth
Phone: +27-41-503-4500
Fax: +27-41-581-0440

Spain – Barcelona
Phone: +34-93-291-0330
Fax: +34-93-201-7879

Sweden – Upplands Väsby
Phone: +46-8-50-72-50-00
Fax: +46-8-50-72-50-01

Switzerland – Steinach
Phone: +41-71-447-0447
Fax: +41-71-447-0444

Turkey – Istanbul
Phone: +90-212-281-8181/2/3
+90-212-282-5130/5430
Fax: +90-212-281-8184

Ukraine – Kiev
Phone: +380-44-206-2265
Fax: +380-44-206-2264
Product Information Center:
Phone: +380-44-206-2265
Fax: +380-44-206-2264

United Kingdom – Stanmore, Middlesex
Phone: +44-8706-080208
Fax: +44-208-954-6234
Product Information Center:
Freephone (UK only):
0800-267-666
Phone: +44-8706-080208
Fax: +44-208-420-8095

1307819–7.5M–LUG–FP–8-08
Printed in the U.S.A.

Tyco Electronics Corporation
Harrisburg, PA

tycoelectronics.com

1307819-7.5M-LUG-FP-8-08

Tyco Electronics

Our commitment. Your advantage.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TE Connectivity:
382575-2