



- 1 HOUSING: FLAME RETARDANT, GLASS FILLED, POLYESTER, COLOR: BLACK. CONTACT: PHOSPHOR BRONZE
- 2 CONTACT: DUPLEX PLATED 0.76µm[.000030] GOLD IN CONTACT AREA, 3.81-7.62µm[.000150-.000300] BRIGHT TIN-LEAD ON LEADS ALL OVER 1.27µm[.000050] MIN NICKEL
- 3 THESE DIMENSIONS PERTAIN TO CAVITY CENTERLINES ONLY - NOT TO CONTACT LOCATIONS
- 4 PART NUMBER AND DATE CODE MARKED IN APPROXIMATE LOCATION SHOWN, EITHER SIDE.
- 5 TOLERANCE IS NON-CUMULATIVE.
- 6 2 POSITION DATE CODE IS MARKED OPPOSITE SIDE OF TE CONNECTIVITY LOGO.
- 7 POINT-OF-MEASUREMENT DIMENSION FOR PLATING THICKNESS (INSIDE CONTACT BEAM).
- 8 POINT-OF-CONTACT DIMENSION.
- 9 NO PART NUMBER MARKING REQUIRED FOR THIS PART.
- 10 TE CONNECTIVITY LOGO AND CSA LOGO ARE MOLDED INTO HOUSING, THIS LOCATION.
- 11 CONTACT: DUPLEX PLATED 0.76µm[.000030] GOLD IN CONTACT AREA, 3.81-7.62µm[.000150-.000300] MATTE TIN ON LEADS ALL OVER 1.27µm[.000050] MIN NICKEL
- 12 ROHS 2002/95/EC COMPLIANT

6	9	OBSOLETE	2.54 [.100]	5.08 [.200]	2	12	8-534237-9
			99.06 [3.900]	101.60 [4.000]	40	12	8-534237-8
			96.52 [3.800]	99.06 [3.900]	39	12	8-534237-7
			93.98 [3.700]	96.52 [3.800]	38	12	8-534237-6
			91.44 [3.600]	93.98 [3.700]	37	12	8-534237-5
			88.90 [3.500]	91.44 [3.600]	36	12	8-534237-4
			86.36 [3.400]	88.90 [3.500]	35	12	8-534237-3
			83.82 [3.300]	86.36 [3.400]	34	12	8-534237-2
			81.28 [3.200]	83.82 [3.300]	33	12	8-534237-1
			78.74 [3.100]	81.28 [3.200]	32	12	8-534237-0
			76.20 [3.000]	78.74 [3.100]	31	12	7-534237-9
			73.66 [2.900]	76.20 [3.000]	30	12	7-534237-8
			71.12 [2.800]	73.66 [2.900]	29	12	7-534237-7
			68.58 [2.700]	71.12 [2.800]	28	12	7-534237-6
			66.04 [2.600]	68.58 [2.700]	27	12	7-534237-5
			63.50 [2.500]	66.04 [2.600]	26	12	7-534237-4
			60.96 [2.400]	63.50 [2.500]	25	12	7-534237-3
			58.42 [2.300]	60.96 [2.400]	24	12	7-534237-2
			55.88 [2.200]	58.42 [2.300]	23	12	7-534237-1
			53.34 [2.100]	55.88 [2.200]	22	12	7-534237-0
			50.80 [2.000]	53.34 [2.100]	21	12	6-534237-9
			48.26 [1.900]	50.80 [2.000]	20	12	6-534237-8
			45.72 [1.800]	48.26 [1.900]	19	12	6-534237-7
			43.18 [1.700]	45.72 [1.800]	18	12	6-534237-6
			40.64 [1.600]	43.18 [1.700]	17	12	6-534237-5
			38.10 [1.500]	40.64 [1.600]	16	12	6-534237-4
			35.56 [1.400]	38.10 [1.500]	15	12	6-534237-3
			33.02 [1.300]	35.56 [1.400]	14	12	6-534237-2
			30.48 [1.200]	33.02 [1.300]	13	12	6-534237-1
			27.94 [1.100]	30.48 [1.200]	12	12	6-534237-0
			25.40 [1.000]	27.94 [1.100]	11	12	5-534237-9
			22.86 [.900]	25.40 [1.000]	10	12	5-534237-8
			20.32 [.800]	22.86 [.900]	9	12	5-534237-7
			17.78 [.700]	20.32 [.800]	8	12	5-534237-6
			15.24 [.600]	17.78 [.700]	7	12	5-534237-5
			12.70 [.500]	15.24 [.600]	6	12	5-534237-4
			10.16 [.400]	12.70 [.500]	5	12	5-534237-3
			7.62 [.300]	10.16 [.400]	4	12	5-534237-2
			5.08 [.200]	7.62 [.300]	3	12	5-534237-1
			B	A	NO OF POSN		PART NUMBER

9	OBSOLETE	2.54 [.100]	5.08 [.200]	2	12	3-534237-9
		99.06 [3.900]	101.60 [4.000]	40	12	3-534237-8
		96.52 [3.800]	99.06 [3.900]	39	12	3-534237-7
		93.98 [3.700]	96.52 [3.800]	38	12	3-534237-6
		91.44 [3.600]	93.98 [3.700]	37	12	3-534237-5
		88.90 [3.500]	91.44 [3.600]	36	12	3-534237-4
		86.36 [3.400]	88.90 [3.500]	35	12	3-534237-3
		83.82 [3.300]	86.36 [3.400]	34	12	3-534237-2
		81.28 [3.200]	83.82 [3.300]	33	12	3-534237-1
		78.74 [3.100]	81.28 [3.200]	32	12	3-534237-0
		76.20 [3.000]	78.74 [3.100]	31	12	2-534237-9
		73.66 [2.900]	76.20 [3.000]	30	12	2-534237-8
		71.12 [2.800]	73.66 [2.900]	29	12	2-534237-7
		68.58 [2.700]	71.12 [2.800]	28	12	2-534237-6
		66.04 [2.600]	68.58 [2.700]	27	12	2-534237-5
		63.50 [2.500]	66.04 [2.600]	26	12	2-534237-4
		60.96 [2.400]	63.50 [2.500]	25	12	2-534237-3
		58.42 [2.300]	60.96 [2.400]	24	12	2-534237-2
		55.88 [2.200]	58.42 [2.300]	23	12	2-534237-1
		53.34 [2.100]	55.88 [2.200]	22	12	2-534237-0
		50.80 [2.000]	53.34 [2.100]	21	12	1-534237-9
		48.26 [1.900]	50.80 [2.000]	20	12	1-534237-8
		45.72 [1.800]	48.26 [1.900]	19	12	1-534237-7
		43.18 [1.700]	45.72 [1.800]	18	12	1-534237-6
		40.64 [1.600]	43.18 [1.700]	17	12	1-534237-5
		38.10 [1.500]	40.64 [1.600]	16	12	1-534237-4
		35.56 [1.400]	38.10 [1.500]	15	12	1-534237-3
		33.02 [1.300]	35.56 [1.400]	14	12	1-534237-2
		30.48 [1.200]	33.02 [1.300]	13	12	1-534237-1
		27.94 [1.100]	30.48 [1.200]	12	12	1-534237-0
		25.40 [1.000]	27.94 [1.100]	11	12	534237-9
		22.86 [.900]	25.40 [1.000]	10	12	534237-8
		20.32 [.800]	22.86 [.900]	9	12	534237-7
		17.78 [.700]	20.32 [.800]	8	12	534237-6
		15.24 [.600]	17.78 [.700]	7	12	534237-5
		12.70 [.500]	15.24 [.600]	6	12	534237-4
		10.16 [.400]	12.70 [.500]	5	12	534237-3
		7.62 [.300]	10.16 [.400]	4	12	534237-2
		5.08 [.200]	7.62 [.300]	3	12	534237-1
			B	A	NO OF POSN	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: mm [INCHES]	TOLERANCES UNLESS OTHERWISE SPECIFIED:	DIN M. BINNER OSNOV02	CSK J. JOLSON OSNOV02	APVD J. JOLSON OSNOV02	NAME
0. PLC ± -	1. PLC ± -	2. PLC ± 0.25[.010]	3. PLC ± 0.13[.005]	4. PLC ± -	ANGLES ± -
MATERIAL 1	FINISH SEE TABLE	WEIGHT -	SIZE A1	CAGE CODE 00779	DRAWING NO. 534237
CUSTOMER DRAWING		SCALE 4:1	SHEET 1 of 1	REV R5	

STE TE Connectivity

RECT. ASSY, MOD IV, SINGLE ROW, .100CL, VERTICAL BOARD MOUNT, CLOSED, TOP ENTRY, SHORT PNT. OF CONTACT

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[6-534237-8](#)