



1. FOR USE WITH 188A/u & 316/U COAX CABLE.

2. FERRULE CRIMPING TOOL: AMP TOOL #220066-1 CRIMP C OR 220066-2 CRIMP C OR 220009-1 CRIMP C.

3. CONTACT CRIMPING TOOL:M22520/2-01 OR AMP TOOL NUMBER 1-601966-6, SETTING NUMBER 5. DANIELS POSITIONER PART NO. K345 OR AMP TOOL NO. 1-601966-6.

4. SEE I.S.2348.

5. DANIELS MANUFACTURING CORP
2266 FRANKLIN ROAD
BLOOMFIELD HILLS, MI 48013

△ OUTER JACKET OF CABLE MUST BE TRIMMED TO ALLOW PROPER INTER-PIN CONTACT LOCATION AFTER FERRULE CRIMP OPERATION.

7. PARTS SHIPPED UNASSEMBLED AND CABLE IS SUPPLIED BY CUSTOMER.

225791-9

PART NO.

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN C.C.THOMAS 2-1-95	TE Connectivity			
		CHK J.DUNBAR 2-2-95				
DIMENSIONS: INCHES	TOLERANCES UNLESS OTHERWISE SPECIFIED:	APVD -	NAME			
	0 PLC ± -	PRODUCT SPEC	CONNECTOR,COAXIAL,RF SOCKET SIZE 5, ARINC (HEX CRIMP)			
	1 PLC ± -	108-12045				
	2 PLC ± -	APPLICATION SPEC				
MATERIAL	FINISH	WEIGHT	SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
SEE CALLOUTS	SEE CALLOUTS	-	A2	00779	C=225791-9	-
CUSTOMER DRAWING			SCALE	SHEET	REV	
			5:1	1 of 1	D	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[225791-9](#)