

4 3 2 1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION 1997  
 © COPYRIGHT 1997 ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS					
		P	LTR	DESCRIPTION	DATE	DWN	APVD
A1	-	B13		Released As per ECR-09-005436	9-Mar-2009	CJ	TS
		B14		ECR-11-002636	05APR2011	SR	AR

PN 1-1,2-1,3-1,4-1,5-1,1-2,2-2,3-2  
 4-2,5-2,6-1,4-3,1-8,2-8,3-8,4-8,5-8,  
 4-9,2-9,3-9,4-9 & 5-9

SCALE 5:1

PN 1-1,2-1,3-1,4-1,5-1,1-2,2-2,3-2  
 4-2,5-2,6-1,4-3,1-8,2-8,3-8,4-8,5-8,  
 4-9,2-9,3-9,4-9 & 5-9

NOTES

- 1 MATERIAL SEE TABLE
- 2 SURFACE SEE TABLE
- 3 ASSEMBLY WEIGHT SEE TABLE
- 4 PACKAGING: 50 PIECES IN POLY-BAG 0-1243085-8
- 5 PACKAGING: 500 PIECES IN POLY-BAG 0-1243085-8
- 6 PACKAGING: 10 PIECES IN POLY-BAG 0-1243085-8
- 7 CROSS-SECTION MARKING

PN 1-1,2-1,3-1,4-1,5-1,1-2,2-2,3-2  
 4-2,5-2,6-1,4-3,1-8,2-8,3-8,4-8,5-8,  
 4-9,2-9,3-9,4-9 & 5-9

SCALE 4:1

OB	OB	OB													3	1	2	7	2						
1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	Catch Spring	Stainless Steel								
																Pin Contact 1.5 mm <sup>2</sup>	0.00062	Ms/Brass	Ag/Ni	1.8	3.0				4
																Pin Contact 4.0 mm <sup>2</sup>	0.00059	Ms/Brass	Ag/Ni	2.4	3.2				6
				1												Pin Contact 2.5 mm <sup>2</sup>	0.00067	Ms/Brass	Au	2.2	3.2				5
					1											Pin Contact 1.5 mm <sup>2</sup>	0.00067	Ms/Brass	Au	1.8	3.0				4
						1										Pin Contact 0.75-10 mm <sup>2</sup>	0.00063	Ms/Brass	Au	1.45	2.6				3
							1									Pin Contact 0.5 mm <sup>2</sup>	0.00062	Ms/Brass	Au	1.1	2.6				2
								1								Pin Contact 0.14-0.37 mm <sup>2</sup>	0.00061	Ms/Brass	Au	0.9	2.6				1
									1							Pin Contact 2.5 mm <sup>2</sup>	0.00065	Ms/Brass	Ag/Cu	2.2	3.2				5
										1						Pin Contact 1.5 mm <sup>2</sup>	0.00067	Ms/Brass	Ag/Cu	1.8	3.0				4
											1					Pin Contact 0.75-10 mm <sup>2</sup>	0.00063	Ms/Brass	Ag/Cu	1.45	2.6				3
												1				Pin Contact 0.5 mm <sup>2</sup>	0.00062	Ms/Brass	Ag/Cu	1.1	2.6				2
OB	OB	OB														Pin Contact 0.14-0.37 mm <sup>2</sup>	0.00061	Ms/Brass		0.9	2.6				1
OB	OB	OB	1													Pin Contact 0.14-0.37 mm <sup>2</sup>	0.00065	Fe	Au	0.9	2.6				1
														1		Pin Contact 0.14-0.37 mm <sup>2</sup>	0.00067	Ms/Brass	Ag/Cu	0.9	2.6				1

4-3	6-1	1-4	1-3	5-2	4-2	3-2	2-2	1-2	5-1	4-1	3-1	2-1	1-1		DESCRIPTION	WEIGHT IN (Kg)	MATERIAL	SURFACE	ØA	ØB	CROSS SECTION MARKING	POS
					5-9	4-9	3-9	2-9	1-9	5-8	4-8	3-8	2-8	1-8								
HN.D-C-Sti.Ag/Ni.1.5 mm <sup>2</sup>	HN.D-C-Sti.Ag/Ni.4.0 mm <sup>2</sup>	HN.D-C-Sti.CuNi.0.74 -0.37 mm <sup>2</sup>	HN.D-C-Sti.Fe.Au.0.14 -0.37 mm <sup>2</sup>	HN.D-C-Sti.Au.2.5 mm <sup>2</sup>	HN.D-C-Sti.Au.1.5 mm <sup>2</sup>	HN.D-C-Sti.Au.0.75-1.00 mm <sup>2</sup>	HN.D-C-Sti.Au.0.5 mm <sup>2</sup>	HN.D-C-Sti.Au.0.14 -0.37 mm <sup>2</sup>	HN.D-C-Sti.Ag.2.5 mm <sup>2</sup>	HN.D-C-Sti.Ag.1.5 mm <sup>2</sup>	HN.D-C-Sti.Ag.0.75-1.00 mm <sup>2</sup>	HN.D-C-Sti.Ag.0.5 mm <sup>2</sup>	HN.D-C-Sti.Ag.0.14 -0.37 mm <sup>2</sup>									

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: mm

TOLERANCES UNLESS OTHERWISE SPECIFIED:  
 ISO 2768 MSL  
 0 PLC  
 1 PLC  
 2 PLC  
 3 PLC  
 4 PLC  
 ANGLES ±°

MATERIAL: 1  
 FINISH: 2

DWN: Braun 23.07.1997  
 CHK: Schnurpfeil 23.07.1997  
 APVD: -

PRODUCT SPEC: 108-74018  
 APPLICATION SPEC: 114-74015  
 WEIGHT: -

NAME: PIN CONTACT SERIES HN.D  
 SIZE: A2  
 CAGE CODE: 00779  
 DRAWING NO: G-1105050  
 RESTRICTED TO: -

CUSTOMER DRAWING  
 SCALE: 10:1  
 SHEET: 1 OF 1  
 REV: B14

1471-9 (3/11)  
 Pro/ENGINEER DRAWING

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[1-1105050-1](#)