



DETAIL L TYP BOTH ENDS
DETAIL M FOR -6 ONLY

- CONNECTOR MATES WITH ANY 15 POSN PLUG IN AMPLIMITE SERIES & COMPLIES WITH AMP SPEC 108-40005 WHERE APPLICABLE.
- MOLDED PARTS: FLAME RETARDANT 94V-0 RATED THERMOPLASTIC, BLACK.
SHELL: CARBON STEEL.
CONTACTS: PHOSPHOR BRONZE.
EYELETS: BRASS.
SCREWLOCKS: ZINC.
INSERTS: ZINC.
- SHELL: TIN PLATED.
CONTACTS: .000030 GOLD FOR A DISTANCE OF .100 MIN FROM MATING END, TIN PLATED .000100-.000200 ON OPPOSITE END, ALL OVER .000050 NICKEL.
EYELETS: TIN PLATED.
SCREWLOCKS: CLEAR CHROMATE.
INSERTS: CLEAR CHROMATE.

FEMALE SCREWLOCKS	5745782-6
THREADED INSERTS	5745782-4
NONE	5745782-2
MOUNTING HARDWARE	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: INCHES	TOLERANCES UNLESS OTHERWISE SPECIFIED:	0 PLC ± -	1 PLC ± -	2 PLC ± -	3 PLC ± .005	4 PLC ± -	ANGLES ± °
MATERIAL		FINISH		WEIGHT			

DIN	A. FERNANDEZ-DOCKS 04-06-05	TE Connectivity	
CHK	S. BOLASH 04-06-05	RCPT ASSY, SIZE 2, 15 POSN, RTANG, AMPLIMITE HD-20, WITH METAL SHELL, WITH OR WITHOUT SCREWLOCKS OR INSERTS	
APPD	M. WALMSLEY 04-06-05	PRODUCT SPEC	108-40025
APPLICATION SPEC	114-40010	SIZE	A1
CAGE CODE	00779	DRAWING NO	5745782
CUSTOMER DRAWING	SCALE 4:1	SHEET 1 OF 1	REV R

COPYRIGHT 2005 TE CONNECTIVITY CORP ALL RIGHTS RESERVED

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[5745782-6](#)