


AMP 4805 REV 31MAR2000

5	4	3	2
			GP 00 P LTR

1HOUSING: FLAME RETARDANT, 94V–0 OR POLYESTER, COLOR: BLACK Contacts: Phos bronze. INSERTS & SCREWLOCKS: ZINC.

- REFER TO APPLICATION SPEC FOR RE MOUNTING DIMENSIONS FOR AUTOMATIC 2CONTACTS: SEE TABLE $\overline{3}$
- INSERTS & SCREWLOCKS: CLEAR CH 4PLATED WITH GOLD FLASH FOR LENG MATING END, .000100 MIN TIN ON SC OVER .000050 MIN NICKEL ON ENTIR
- 5 PLATED WITH .000030 MIN GOLD FOR MATING END, .000100 MIN TIN SOLDE .000050 MIN NICKEL ON ENTIRE CON



1	
REVISIONS LTR DESCRIPTION DATE DWN APV	2
O RELEASED PER EC 0S13-0087-05 16SEP05 GP JC	;
	D
94V—O RATED, GLASS FILLED, NYLON K	
С.	
FOR RECOMMENDED P.C. BOARD ITOMATIC INSERTION.	
R CHROMATE COATING.	
LENGTH OF .055 MIN FROM	
ON SOLDER END, ALL Entire contact.	
D FOR LENGTH OF .055 MIN FROM Solder end, all over	С
E CONTACT.	
	В
WITH SCREWLOCKS 5 5747459-6WITH SCREWLOCKS 4 5747459-5	
WITH INSERTS 5747459-4	+
WITH .120 DIA HOLE 5 5747459-2	2
WITH .120 DIA HOLE45747459-7REMARKSFINISHPART NUMBER	A
S 16SEP05 16SE	1
H Electronics Individuality, FX (7) (05-3000 16SEP05 NAME SLEY RECEPTACLE ASSY, SIZE 1, 9 POSN,	-
-40025 SPEC RIGHT ANGLE, .590 SERIES, .026 DIA POSTS, AMPLIMITE HD-20 DIA POSTS, AMPLIMITE HD-20	-0
A 1 00779 C= 5747459 -	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TE Connectivity: 5747459-4