



**Product:** [1857A](#)

Triax, RG59, 22 AWG Str BC, Double 95% BC Braids, Belflex® Jkt, Flexible

### Product Description

Triax, RG59, 22 AWG (19x34) Bare Copper Conductor, PE Insulation, 95% Bare Copper Braid Shield, PE Insulation, 95% Bare Copper Braid Shield, Belflex® Jacket, Flexible

### Technical Specifications

#### Product Overview

Suitable Applications:	Analog Video; Interconnect camera to CCU (camera control unit)
------------------------	--

#### Construction Details

RG Type:	59
----------	----

#### Conductor

AWG	Stranding	Nom. Diameter	Material
22	19x34	0.031 in	BC - Bare Copper

#### Insulation

Material	Nom. Diameter
PE - Polyethylene (Foam)	0.143 in

#### Inner Shield Material

Layer	Inner Shield Type	Material	Coverage
1	Braid	Bare Copper (BC)	95%

#### Inner Jacket Material

Material	Nom. Diameter
PE - Polyethylene	0.216 in

#### Outer Shield Material

Layer	Outer Shield Type	Material	Coverage
1	Braid	Bare Copper (BC)	95%

#### Outer Jacket Material

Material	Nom. Diameter
PVC - Polyvinyl Chloride	0.360 in

#### Electrical Characteristics

##### Return Loss (RL)

Frequency [MHz]	Min. Return Loss [dB]
5 - 850 MHz	21 dB
850 - 3000 MHz	15 dB

##### Attenuation

Frequency	Nom. Attenuation [dB/100ft]
1 MHz	0.30 dB/100ft
3.6 MHz	0.50 dB/100ft

10 MHz	0.80 dB/100ft
71.5 MHz	2.20 dB/100ft
135 MHz	3.10 dB/100ft
270 MHz	4.50 dB/100ft
360 MHz	5.40 dB/100ft
540 MHz	6.80 dB/100ft
720 MHz	8.10 dB/100ft
750 MHz	8.40 dB/100ft
1000 MHz	10.10 dB/100ft
1500 MHz	13.30 dB/100ft
2250 MHz	17.60 dB/100ft
3000 MHz	21.40 dB/100ft

#### Electricals

Nom. Conductor DCR	Nom. Inner Shield DCR	Nom. Outer Shield DCR	Nom. Capacitance Cond-to-Shield	Nom. Impedence	Nom. Velocity
14.0 Ohm/1000ft	2.5 Ohm/1000ft	1.6 Ohm/1000ft	17.0 pF/ft	75 Ohm	77%

#### Voltage

Non-UL Voltage Rating
300 V

## Mechanical Characteristics

#### Temperature

Operating
-45°C to +60°C

#### Bend Radius

Installation Min.
3.6 in

Bulk Cable Weight:	78 lbs/1000ft
Max. Pull Tension:	102 lbs

## Standards and Compliance

Environmental Suitability:	Indoor/Outdoor, Indoor
Sustainability:	CA Prop 65
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU, EU Directive 2011/65/EU (ROHS II), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)

## History

Update and Revision:	Revision Number: 0.290 Revision Date: 09-30-2020
----------------------	--

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.