

4 3 2 1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION
 © COPYRIGHT - By - ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS					
FT	0	P	LTR	DESCRIPTION	DATE	DWN	APVD
		K2		REVISED PER ECO-11-004820	11MAR11	RK	HMR

PERIPHERAL SEAL BONDED IN PLACE SEE TABLE

.150 DIA 4 HOLES

1.750 ± .025

1.438 ± .010 TYP

1.438 ± .010 TYP

1.750 ± .025

Dimensions: .434, .372, .310, .248, .186, .124, .062, .000, .062, .124, .186, .248, .310, .372, .434

Dimensions: .443, .319, .212, .105, .000, .019, .143, .250, .357, .464

CONTACT CAVITIES IDENTIFIED BY CHARACTERS ON FRONT AND REAR FACES OF CONNECTOR.

.420 ± .015

.156 ± .010

1.438 ± .010 DIA

1.515 DIA MAX

.125 MAX PANEL THK

.924 MAX

1.500 MAX

AMP

1.733 DIA MAX

MATING FACE

FREE HANGING (-2 ONLY)

1.438 ± .010 TYP

1.438 ± .010 TYP

1.610 DIA

.150 .007 DIA .000 4 HOLES

PANEL CUTOUT
SCALE 1:1

NOTES:

- CONTACT CAVITIES IDENTIFIED BY CHARACTERS ON FRONT AND REAR FACES OF CONNECTOR.
- WILL ACCEPT (57) SIZE 20 SOCKET CONTACTS.
- PART NUMBER THIS AREA.
- #4 FASTENER RECOMMENDED FOR MOUNTING.
- OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

	OBSELETE	YES	206438-3
		NO	206438-2
		NO	206438-1
	PERIPHERAL SEAL		PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	A.STAUB BG	4/3/91			
DIMENSIONS: INCHES		CHK	W.G.LENKER	7-27-92			
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD	-	-	NAME		
0 PLC ± -		PRODUCT SPEC		108-10024			
1 PLC ± -		APPLICATION SPEC		-			
2 PLC ± -		WEIGHT		-			
3 PLC ± .005		SIZE		A2		CAGE CODE	
4 PLC ± -		DRAWING NO		00779		DRAWING NO	
ANGLES ± -		RESTRICTED TO		-			
FINISH		SCALE		2:1		SHEET	
THERMOPLASTIC, -		CUSTOMER DRAWING		1 of 1		REV	
				K2			

1471-9 (3/11)

206438

A

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[206438-1](#)