




- Close unneeded panel holes and electrical knockouts.
- Quick and easy installation.
- Convex, matte finish head tapers to thin edge (Except DP-187).
- Multiple sizes for use in .187” (4,7 mm) to 6.000” (152,4 mm) diameter holes.
- Lock firmly into panel up to .250” (6,4 mm) thick.
- Locking fingers in fractional increments up to the maximum panel thickness.
- Approximate Head Thickness: .062” (1,6 mm). Thickness may vary.
- For Snap-In Metric Dome Plugs see page 6-30.

Heyco® Dome Plugs

Mounting Hole Diameter Range: .187” (4,7 mm) to 2.500” (63,5 mm)

| MOUNTING HOLE DIAMETER | | PART NO. | | | DESCRIPTION | PART DIMENSIONS | | | |
|---|----------------|----------------------------|----------------------------|------------------|-----------------------|--------------------|------|---------------------|------|
| in. | mm. | Black | White | Colors xx** | | A Head Diameter | | B Overall Height | |
| | | | | | in. | mm. | in. | mm. | |
| Single Locking Step for Panel Thickness up to .062” (1,6 mm) | | | | | | | | | |
| .187 | 4,7 | 2590 | 2591 | 2592xx | DP 187* | .25 | 6,4 | .23 | 5,9 |
| .250 | 6,4 | 2607 2603 | 2608 2604 | 2609xx 2605xx | DP 250-040† DP 250 | .31 | 7,9 | .31 | 7,9 |
| .312 | 7,9 | 2613 | 2614 | 2615xx | DP 312 | .38 | 9,5 | | |
| Multiple Locking Steps for Panel Thickness up to .125” (3,2 mm) | | | | | | | | | |
| .375 | 9,5 | 2617 | 2618 | 2619xx | DP 375 | .47 | 11,9 | .41 | 10,3 |
| .437 | 11,1 | 2633 | 2634 | 2635xx | DP 437 | .53 | 13,5 | | |
| .500 | 12,7 | 2643 | 2644 | 2645xx | DP 500 | .56 | 14,2 | | |
| .562 | 14,3 | 2653 | 2654 | 2655xx | DP 562 | .66 | 16,7 | | |
| .625 | 15,9 | 2663 | 2664 | 2665xx | DP 625 | .72 | 18,2 | | |
| .687 | 17,4 | 2673 | 2674 | 2675xx | DP 687 | .78 | 19,8 | | |
| .750 | 19,1 | 2683 | 2684 | 2685xx | DP 750 | .92 | 23,4 | .45 | 11,5 |
| .812 | 20,6 | 2693 | 2694 | 2695xx | DP 812 | .99 | 25,1 | | |
| .875 | 22,2 | 2703 | 2704 | 2705xx | DP 875 | 1.02 | 25,8 | .47 | 11,9 |
| 1.000 | 25,4 | 2713 | 2714 | 2715xx | DP 1000 | 1.20 | 30,6 | | |
| 1.093 - 1.125 | 27,8 - 28,6 | 2723 | 2724 | 2725xx | DP 1093 | 1.22 | 30,9 | | |
| 1.187 | 30,1 | 2733 | 2734 | 2735xx | DP 1187 | 1.33 | 33,8 | .45 | 11,5 |
| 1.250 | 31,7 | 2740 | 2741 | 2742xx | DP 1250 | 1.38 | 34,9 | | |
| 1.375 | 34,9 | 2753 | 2754 | 2755xx | DP 1375 | 1.50 | 38,1 | | |
| 1.500 | 38,1 | 2763 | 2764 | 2765xx | DP 1500 | 1.67 | 42,4 | | |
| 1.625 | 41,3 | 2276 | 2277 | 2278xx | DP 1625 | 1.80 | 45,7 | | |
| 1.750 | 44,5 | 2773 | 2774 | 2775xx | DP 1750 | 1.92 | 48,7 | | |
| 1.875 | 47,6 | 2291 | 2292 | 2293xx | DP 1875 | 2.05 | 52,1 | .47 | 11,9 |
| 2.000 | 50,8 | 2783 | 2784 | 2785xx | DP 2000 | 2.17 | 55,1 | | |
| Multiple Locking Steps for Panel Thickness up to .250” (6,4 mm) | | | | | | | | | |
| 2.093 - 2.125 | 53,2 - 54,0 | 2403 | 2404 | *** | DP 2.093 | 2.34 | 59,9 | .75 | 19,1 |
| 2.250 | 57,2 | 2411 | 2412 | 2413xx | DP 2.25 | 2.48 | 63,0 | .75 | 19,1 |
| 2.500 | 63,5 | 2790 | 2791 | 2792xx | DP 2.5 | 2.71 | 68,8 | | |



Standard colors black and white. Consult Heyco for other colors (see below)

*Convex, glossy finish head.

** xx indicates that, following the color match process, Heyco adds a two letter suffix to the Root Part No. shown. This suffix will identify your particular CUSTOM Color selection. Consult Heyco for molded nylon color chips for accurate matching. For details as well as information regarding our Stock Colors, see page 6-53.

***Consult Heyco for root Part No.

† Max panel thickness is .040” (1,0 mm)

Quick
Specs

Material
Certifications



Nylon 6/6

Recognized under the Component Program of Underwriters' Laboratories File E51579



Certified by the Canadian Standards Association File 8919

Flammability Rating
Temperature Range

94V-2

-40°F (-40°C) to 221°F (105°C)

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Heyco:

[2591](#) [2590](#) [2694](#) [2674](#) [2634](#) [2643](#) [2644](#) [2603](#) [2604](#) [2683](#) [2684](#) [2663](#) [2664](#) [2613](#) [2618](#) [2614](#) [2693](#) [2653](#)
[2654](#) [2673](#) [2633](#) [2403](#) [2455](#) [2411](#) [2473](#) [2763](#) [2764](#) [2723](#) [2740](#) [2741](#) [2783](#) [2784](#) [2704](#) [2703](#) [2733](#) [2773](#)
[2790](#) [2714](#) [2713](#) [2753](#) [2482](#) [2483](#) [2404](#) [2465](#) [2456](#) [2412](#) [2474](#) [2734](#) [2774](#) [2791](#) [2754](#) [2464](#) [2724](#) [2451](#)
[2617](#) [2453](#) [2607](#) [2454](#) [2452](#) [2608](#) [2735](#) [2619](#) [2605](#) [2645](#) [2685](#) [2742](#) [2792](#) [2655](#) [2615](#) [2705](#) [2457](#) [2695](#)
[2725](#) [2755](#) [2635](#) [2785](#) [2775](#) [2765](#) [2665](#) [2715](#) [2675](#) [2723-P](#) [2724-P](#) [2291](#) [2277](#) [2276](#) [2292](#) [2404-P](#) [2644-P](#)
[2713-P](#) [2663-P](#) [2791-P](#) [2703-P](#) [2765JN](#) [2792JO](#) [2411-P](#) [2412-P](#) [2784-P](#) [2790-P](#) [2664-P](#)