



DRAWN BY:

CHECKED BY:

## **Electrical Characteristics**

		Electrical Charac	ler	ISUCS			
$\mathbf{a}$		Nominal Impedance: Frequency Range: VSWR: Insertion Loss: Operating Voltage (rms): Dielectric Withstand Voltage (rm: Contact Resistance: Insulation Resistance:		ns): Voltage (rms):	50 ohms DC to 4 GHz 1.3:1 maximum 0.2 dB at 4 GHz 500 V maximum at sea level 1500 V maximum at sea level 3.0 milliohms maximum 5000 megohms minimum		
)		Mechanical Char	act	eristics			
•		Mating Cycles:			500 cycles minimum		
_		Interface Dimensions:		Conform to MIL-C-39012			
2111		Environmental Ch	har	acteristics			
*		Temperature Range:			-65 °C to +165 °C		
	1	PART Body	Br	ESCRIPTION			
	2	Dielectric Contact		TFE ass, gold plated	1		
	-	Drawing Update			JT	3	12 Mar 10
	CAD Issue			SN	2	04 Feb 02	
	<u> </u>	First Issue			IS	1	28 Jan 92
					APPVD	ISS	DATE
TITLE: BNC Vertical P				PART NUMBE	R:		

6.25±0,1

MOUNTING HOLE

**Cinch Connectivity Solutions** 7-13 Russel Way, Widford Industrial Estate, Chelmsford,Essex, CONNECTIVITY SOLUTIONS a bel group

COPYRIGHT (C)

APPROVED BY: CM1 3AA, UK. ± 0.2mm unless Tel: +44 (0) 1245 359515 Fax: +44 (0) 1245 358938 otherwise stated DATE: 2002 VITELEC ELECTRONICS LIMITED

SCALE: Not To Scale

DIMENSIONS: mm

TOLERANCES:

THIS DRAWING MAY NOT BE REPRODUCED IN WHOLE OR IN PART WITHOUT OUR WRITTEN PERMISSION

PAGE: 1 of 1

S Nash

S Nash

M Nielsen

04 Feb 02

## **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Cinch Connectivity Solutions: