



NOTES

- 1 - ENCLOSURE FINISHED WITH GREEN EPOXY BASED ENAMEL COLOR NO. 34151 PER FEDERAL STANDARD 595
- 2 - COINCIDENCE OF OPERATING AND RELEASING POINTS: .010 OF PLUNGER TRAVEL
- 3 - CIRCUIT DIAGRAM, CATALOG LISTING AND DATE CODE ARE SHOWN ON NAMEPLATE
- 4 - SWITCH SEALED PER MIL-S-8805 SYMBOL 3
- 5 - EXTERNAL PLUNGER THROUGH HARDENED 43 ROCKWELL C MIN
- 6 - HARDWARE MAY BE PACKAGED UNASSEMBLED PER MIL-S-8805

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF MINNEAPOLIS-HONEYWELL REGULATOR CO. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

CHARACTERISTICS		ELECTRICAL DATA			SCALE FULL	
OPERATING FORCE ———— 10-16 LB		CONTACT ARRANGEMENT			DO NOT SCALE PRINT	
FULL OVERTRAVEL FORCE ———— 30 LB MAX		SPNO (I) SPNC (I)			UNLESS OTHERWISE NOTED DIMENSIONS ARE IN INCHES TOLERANCES ARE: ONE PLACE (.0) ±.030 TWO PLACE (.00) ±.015 THREE PLACE (.000) ±.005 ANGLES ± WEIGHT 6.5 OZ MAX	
RELEASE FORCE ———— 8 LB MIN		LOAD	28 VDC			
PRETRAVEL ———— .040 MAX			SEA LEVEL			
DIFFERENTIAL TRAVEL ———— .020 MAX			50,000 FT.			
OVERTRAVEL ———— .100 MIN						
		RES	4	4		
		IND	2	2		
		MOTOR	4			

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Honeywell:](#)

[1CH31-1B](#)