



REVISIONS		REV.	
REV.	DESCRIPTION	RELEASED	APPROVED
L	0507-021 REDRAWN; ADDED ITEM 11	02/06/04	(2)

A-770N




φ.266^{+.010}
2 MFG. HOLES
SPOTFACE φ.44 - SEE NOTE 2

MAXIMUM OPERATING VOLTAGE 29 VOLTS
PICKUP VOLTAGE (MAX) 18 VOLTS
DROP OUT VOLTAGE 11.5 VOLTS AT -65°F
RATED CONTACT LOAD 7^{+.0} VOLTS
COIL CURRENT AT 25°C .4 AMP
MINIMUM OPERATING PERIOD 3 HOURS
MINIMUM OPERATING CYCLES 300 AMP
MAXIMUM WEIGHT 50,000
RATED DUTY 1 LB. 15 OZ.
AUX. CONTACT 10 AMP, 28 VDC



10-32 UNF-2A
3 STUDS
1 φ.266^{+.010}
2 MFG. HOLES
SPOTFACE φ.44 - SEE NOTE 2

3/8-24 UNF-2A
2 STUDS
1 φ.266^{+.010}
2 MFG. HOLES
SPOTFACE φ.44 - SEE NOTE 2



NOTES:
1. TOLERANCES ON ALL TERMINAL LENGTHS TO BE ±.06.
2. FOR ELECTRICAL PURPOSES, EXPOSE BARE METAL BY
SANDING BOTTOM OF BOTH MOUNTING SURFACES AND
SPOTFACE TOP OF MOUNTING HOLES φ.44

FIND QTY	PART OR	NO RECD	IDENTIFYING NO	DESCRIPTION OR	SPECIFICATION	
					NO	FCN
<u>UNLESS OTHERWISE SPECIFIED</u> DIMENSIONS ARE IN INCHES TOLERANCES IN						
2	PL. DEC. 3 PL. DEC. ANGLES					
.03	+.000	1				
MATERIAL	DR BY	CSC	02/09/06			
CHK BY	C	2/09/06				
ENGR						
MFG	CODE IDENT					
C	74063					
SCALE 1/1	SHEET					

tyco Electronics

HartmanTM Division, 175 N. DIAMOND STREET, WARFIELD, OHIO 44002

CONTACTOR - CONTINUOUS DUTY
300 AMP, 28 VOLTS 093

REF. TYCO P/N 3-1616058-3

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[A770N](#)