

Distributed I/O device - FLM DI 8 M8 - 2773348

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



The space-saving local bus device is particularly suitable for use in close proximity to the process. Functions: 8 digital inputs with 3 ms filter time, channel-specific diagnostics, short-circuit and overload protection, 600 mA nominal current, M8 connection method.

Product Description

The device is designed for use in the Fieldline Modular M8 local bus, which is opened by a Fieldline or Inline bus coupler. It is used to acquire digital signals.

Product Features

- Can also be connected to an Inline station
- Optimized for 30 mm mounting profile
- Diagnostic and status indicators
- Short-circuit and overload protection
- Consistent connection via M8 connectors



Key Commercial Data

Packing unit	1 pc
Weight per Piece (excluding packing)	156.6 g
Custom tariff number	85389091
Country of origin	Germany

Technical data

Note

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---

Dimensions

Width	29.8 mm
Height	143 mm
Depth	26.5 mm
Note on dimensions	Length details incl. fixing clips

Distributed I/O device - FLM DI 8 M8 - 2773348

Technical data

Dimensions

Drill hole spacing	133 mm
--------------------	--------

Ambient conditions

Ambient temperature (operation)	-25 °C ... 60 °C
Ambient temperature (storage/transport)	-25 °C ... 85 °C
Permissible humidity (operation)	5 % ... 95 %
Permissible humidity (storage/transport)	10 % ... 95 %
Air pressure (operation)	80 kPa ... 106 kPa (up to 2000 m above sea level)
Air pressure (storage/transport)	70 kPa ... 106 kPa (up to 3000 m above sea level)
Degree of protection	IP65/IP67

General

Mounting type	Wall mounting
Net weight	137 g

Interfaces

Designation	Fieldline local bus
Connection method	M8 connector
Designation connection point	Copper cable
Transmission speed	500 kBit/s
Number of positions	4

Power supply for module electronics

Connection method	M8 connector
Designation	U _L
Number of positions	4
Supply voltage	24 V DC
Supply voltage range	18 V DC ... 30 V DC (including ripple)
Supply current	3 A

Fieldline potentials

Voltage supply U _L	24 V DC
-------------------------------	---------

Digital inputs

Input name	Digital inputs
Connection method	M8 connector
	2, 3-wire
Number of inputs	8
Protective circuit	Reverse polarity protection
Filter time	3 ms
Input characteristic curve	IEC 61131-2 type 1

Distributed I/O device - FLM DI 8 M8 - 2773348

Technical data

Digital inputs

Input voltage	24 V DC
Input voltage range "0" signal	-30 V DC ... 5 V DC
Input voltage range "1" signal	13 V DC ... 30 V DC

Standards and Regulations

Test section	To I/O 500 V AC
Connection in acc. with standard	CUL
Protection class	III, IEC 61140, EN 61140, VDE 0140-1

Classifications

eCl@ss

eCl@ss 4.0	27250302
eCl@ss 4.1	27250302
eCl@ss 5.0	27250302
eCl@ss 5.1	27242604
eCl@ss 6.0	27242604
eCl@ss 7.0	27242604
eCl@ss 8.0	27242604
eCl@ss 9.0	27242604

ETIM

ETIM 2.0	EC001430
ETIM 3.0	EC001599
ETIM 4.0	EC001599
ETIM 5.0	EC001599

UNSPSC

UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404
UNSPSC 11	43172015
UNSPSC 12.01	43201404
UNSPSC 13.2	43201404

Approvals

Approvals

Distributed I/O device - FLM DI 8 M8 - 2773348

Approvals

Approvals


UL Recognized / cUL Recognized / cULus Recognized


Ex Approvals


UL Recognized / cUL Recognized / cULus Recognized

Approvals submitted

Approval details

UL Recognized 

cUL Recognized 

cULus Recognized 

Accessories

Accessories

Adapter

Adapter - FLM ADAP M12/M8 - 2736961

Adapter for connecting Fieldline Modular M8 devices to a Fieldline Modular M12 local bus



Circular connector (cable-side)

Distributed I/O device - FLM DI 8 M8 - 2773348

Accessories

Connector - SACC-M 8MS-4CON-M-0,34-SH - 1542897



Connector, 4-position, shielded, Plug straight M8, A-coded, Screw connection, Knurl material: Nickel-plated brass, External cable diameter 3.5 mm ... 5.5 mm

Connector - SACC-M 8FS-4CON-M-0,34-SH - 1542910



Connector, 4-position, shielded, Socket straight M8, A-coded, Screw connection, Knurl material: Nickel-plated brass, External cable diameter 3.5 mm ... 5.5 mm

Data cable by the meter

Bus system cable - SAC-4P-950/... - 1543401



Bus system cable, INTERBUS, 4-position, PUR halogen-free, black RAL 9005, shielded, free cable end, on free cable end, Cable length: Free entry (0.5 ... 400.0 m)

Data cable preassembled

Bus system cable - SAC-4P-M 8MS/ 2,0-950 - 1543249



Bus system cable, INTERBUS, 4-position, PUR halogen-free, black RAL 9005, shielded, Plug straight M8, on free cable end, Cable length: 2 m

Bus system cable - SAC-4P-M 8MS/ 5,0-950 - 1543252



Bus system cable, INTERBUS, 4-position, PUR halogen-free, black RAL 9005, shielded, Plug straight M8, on free cable end, Cable length: 5 m

Distributed I/O device - FLM DI 8 M8 - 2773348

Accessories

Bus system cable - SAC-4P-M 8MS/10,0-950 - 1543265



Bus system cable, INTERBUS, 4-position, PUR halogen-free, black RAL 9005, shielded, Plug straight M8, on free cable end, Cable length: 10 m

Bus system cable - SAC-4P-M 8MS/15,0-950 - 1543278



Bus system cable, INTERBUS, 4-position, PUR halogen-free, black RAL 9005, shielded, Plug straight M8, on free cable end, Cable length: 15 m

Bus system cable - SAC-4P-M 8MS/20,0-950 - 1543281



Bus system cable, INTERBUS, 4-position, PUR halogen-free, black RAL 9005, shielded, Plug straight M8, on free cable end, Cable length: 20 m

Bus system cable - SAC-4P- 2,0-950/M 8FS - 1543294



Bus system cable, INTERBUS, 4-position, PUR halogen-free, black RAL 9005, shielded, free cable end, on Socket straight M8, Cable length: 2 m

Bus system cable - SAC-4P- 5,0-950/M 8FS - 1543304



Bus system cable, INTERBUS, 4-position, PUR halogen-free, black RAL 9005, shielded, free cable end, on Socket straight M8, Cable length: 5 m

Distributed I/O device - FLM DI 8 M8 - 2773348

Accessories

Bus system cable - SAC-4P-10,0-950/M 8FS - 1543317



Bus system cable, INTERBUS, 4-position, PUR halogen-free, black RAL 9005, shielded, free cable end, on Socket straight M8, Cable length: 10 m

Bus system cable - SAC-4P-15,0-950/M 8FS - 1543320



Bus system cable, INTERBUS, 4-position, PUR halogen-free, black RAL 9005, shielded, free cable end, on Socket straight M8, Cable length: 15 m

Bus system cable - SAC-4P-20,0-950/M 8FS - 1543333



Bus system cable, INTERBUS, 4-position, PUR halogen-free, black RAL 9005, shielded, free cable end, on Socket straight M8, Cable length: 20 m

Bus system cable - SAC-4P-M 8MS/ 0,13-950/M 8FS - 1543346



Bus system cable, INTERBUS, 4-position, PUR halogen-free, black RAL 9005, shielded, Plug straight M8, on Socket straight M8, Cable length: 0.13 m

Bus system cable - SAC-4P-M 8MS/ 0,3-950/M 8FS - 1543511



Bus system cable, INTERBUS, 4-position, PUR halogen-free, black RAL 9005, shielded, Plug straight M8, on Socket straight M8, Cable length: 0.3 m

Distributed I/O device - FLM DI 8 M8 - 2773348

Accessories

Bus system cable - SAC-4P-M 8MS/ 0,5-950/M 8FS - 1543524



Bus system cable, INTERBUS, 4-position, PUR halogen-free, black RAL 9005, shielded, Plug straight M8, on Socket straight M8, Cable length: 0.5 m

Bus system cable - SAC-4P-M 8MS/ 1,0-950/M 8FS - 1543537



Bus system cable, INTERBUS, 4-position, PUR halogen-free, black RAL 9005, shielded, Plug straight M8, on Socket straight M8, Cable length: 1 m

Bus system cable - SAC-4P-M 8MS/ 2,0-950/M 8FS - 1543359



Bus system cable, INTERBUS, 4-position, PUR halogen-free, black RAL 9005, shielded, Plug straight M8, on Socket straight M8, Cable length: 2 m

Bus system cable - SAC-4P-M 8MS/ 5,0-950/M 8FS - 1543362



Bus system cable, INTERBUS, 4-position, PUR halogen-free, black RAL 9005, shielded, Plug straight M8, on Socket straight M8, Cable length: 5 m

Bus system cable - SAC-4P-M 8MS/10,0-950/M 8FS - 1543375



Bus system cable, INTERBUS, 4-position, PUR halogen-free, black RAL 9005, shielded, Plug straight M8, on Socket straight M8, Cable length: 10 m

Distributed I/O device - FLM DI 8 M8 - 2773348

Accessories

Bus system cable - SAC-4P-M 8MS/15,0-950/M 8FS - 1543388



Bus system cable, INTERBUS, 4-position, PUR halogen-free, black RAL 9005, shielded, Plug straight M8, on Socket straight M8, Cable length: 15 m

Bus system cable - SAC-4P-M 8MS/20,0-950/M 8FS - 1543391



Bus system cable, INTERBUS, 4-position, PUR halogen-free, black RAL 9005, shielded, Plug straight M8, on Socket straight M8, Cable length: 20 m

I/O component

Inline function terminal - IB IL 24 FLM-PAC - 2736903



Inline branch terminal for coupling a Fieldline Modular local bus M12 or M8 at the end of an Inline station, conversion of Inline local bus physical structure to the Fieldline local bus physical structure

Protective cap

Screw plug - PROT-M8 - 1682540



An M8 screw plug for the unoccupied M8 sockets of the sensor/actuator cable, boxes and flush-type connectors

Terminal marking

Distributed I/O device - FLM DI 8 M8 - 2773348

Accessories

Zack Marker strip, flat - ZBF 8:UNBEDRUCKT - 0808781




Zack Marker strip, flat, Strip, white, unlabeled, can be labeled with: Plotter, Mounting type: Snap into flat marker groove, for terminal block width: 8 mm, Lettering field: 5.15 x 8.15 mm

Drawings


Dimensional drawing

Top view (dimensions in mm)

Connection diagram



Dimensional drawing



Side view (dimensions in mm)

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Phoenix Contact:](#)

[2773348](#)