

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [1707290004](#)
Status: **Active**
Overview: [iPass+ HD Interconnect System](#)
Description: iPass+ zHD Vertical Internal Connector Assembly, 1x4, Through Hole, 0.76µm Gold (Au) Plating

Documents:

3D Model	Application Specification AS-76867-002-001 (PDF)
Drawing (PDF)	Packaging Specification PK-76867-002-000 (PDF)
Product Specification PS-170729-001-001 (PDF)	Test Summary 1707290001-000 (PDF)
Application Specification 1707290002-000 (PDF)	Test Summary TS-170729-9906-001 (PDF)
Application Specification AS-170729-0001-001 (PDF)	RoHS Certificate of Compliance (PDF)

Agency Certification

CSA	LR19980
UL	E107635

General

Product Family	I/O Connectors
Series	170729
Application	Wire-to-Board
Component Type	Internal Receptacle
Overview	iPass+ HD Interconnect System
Product Name	iPass+, zHD
Type	N/A
UPC	887191187891

Physical

Circuits (Loaded)	144
Circuits (maximum)	144
Color - Resin	Black
Durability (mating cycles max)	50
Flammability	94V-0
Gender	Receptacle
Lock to Mating Part	Yes
Material - Metal	Copper Alloy
Material - Plating Mating	Gold over Nickel
Material - Plating Termination	Tin over Nickel
Material - Resin	High Temperature Thermoplastic
Net Weight	11.928/g
Number of Rows	4
Orientation	Vertical
PC Tail Length	1.37mm
PCB Locator	Yes
PCB Retention	Yes
PCB Thickness - Recommended	1.57mm
Packaging Type	Tray
Panel Mount	No
Pitch - Mating Interface	0.75mm
Plating min - Mating	0.760µm
Plating min - Termination	0.760µm
Polarized to Mating Part	Yes
Polarized to PCB	Yes
Ports	4
Temperature Range - Operating	-40° to +80°C
Termination Interface: Style	Through Hole - Compliant Pin



Series image - Reference only

EU ELV

Not Relevant

EU RoHS

Compliant

REACH SVHC

Not Contained Per - ED/71/2019 (16 July 2019)

Halogen-Free

Status

Low-Halogen

For more information, please visit [Contact US](#)

China ROHS

ELV

RoHS Phthalates

China RoHS

Green Image

Not Relevant

Not Contained

Search Parts in this Series

[170729 Series](#)

Mates With

[100189](#) , [100171](#) , [100190](#) , [100219](#) , [100172](#) , [100220](#) , [100221](#) , [100222](#) , [100223](#) , [100224](#) , [100225](#) , [100226](#)

Application Tooling | FAQ

Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.

Global

Description	Product #
-------------	-----------

I-PASS zHD Wafer Assembly Removal Tool	622024900
--	---------------------------

Press-In Tool for iPass Vertical zHD	622030770
--------------------------------------	---------------------------

Electrical

Current - Maximum per Contact 1.0A
Voltage - Maximum 48V AC (RMS) / 67V DC

Solder Process Data

Lead-free Process Capability N/A

Material Info**Reference - Drawing Numbers**

Application Specification 1707290002-000, AS-170729-0001-001,
AS-76867-002-001
Electrical Model Document EE-170729-0001
Packaging Specification PK-76867-002-000
Product Specification PS-170729-001-001
S-Parameter Model SP-170729-0001
Sales Drawing SD-170729-0001-000
Signal Integrity Report SI-170729-0001
Symbol/Footprint Data SYM-170729-0004
Test Summary 1707290001-000, TS-170729-9906-001

This document was generated on 09/26/2019

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Molex:](#)

[170729-0004](#)