

A

2

SUPERSEDED	TIN—LEAD	3.744	95.10	24	2-641113-4
	TIN—LEAD	3.588	91.14	23	2-641113-3
	TIN—LEAD	3.432	87.17	22	2-641113-2
	TIN—LEAD	3.276	83.21	21	2-641113-1
	TIN—LEAD	3.120	79.25	20	2-641113-0
	TIN—LEAD	2.964	75.29	19	1-641113-9
	TIN—LEAD	2.808	71.32	18	1-641113-8
	TIN—LEAD	2.652	67.36	17	1-641113-7
	TIN—LEAD	2.496	63.40	16	1-641113-6
	TIN—LEAD	2.340	59.44	15	1-641113-5
	TIN—LEAD	2.184	55.47	14	1-641113-4
	TIN—LEAD	2.028	51.51	13	1-641113-3
	TIN—LEAD	1.872	47.55	12	1-641113-2
	TIN—LEAD	1.716	43.59	11	1-641113-1
	TIN—LEAD	1.560	39.62	10	1-641113-0
	TIN—LEAD	1.404	35.66	9	641113-9
	TIN—LEAD	1.248	31.70	8	641113-8
	TIN—LEAD	1.092	27.74	7	641113-7
	TIN—LEAD	.936	23.77	6	641113-6
	TIN—LEAD	.780	19.81	5	641113-5
TIN—LEAD	.624	15.85	4	641113-4	
TIN—LEAD	.468	11.89	3	641113-3	
TIN—LEAD	.312	7.92	2	641113-2	
15	FINISH	IN	MM	NUMBER OF POSITIONS	PART NUMBER
		L			

METRIC

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[3-641113-4](#)