


REV.	DESCRIPTION	DATE
A	NEW DRAWING	4/20/2006



SPECIFICATIONS:
CONTACT RESISTANCE: 30m OHMS MAX
INSULATION RESISTANCE: 100M OHMS MIN: 500V DC
VOLTAGE WITHSTAND: 500V AC R.M.S. FOR 1 MINUTE
LIFE: 5,000 CYCLES
OPERATING TEMP: -20° ~ +85°C



TOLERANCE:
±0.3mm UNLESS OTHERWISE
SPECIFIED



9615 SW Allen Blvd., Ste. 103
Beaverton, OR 97005
Phone: 503-643-4899
800-275-4899
Fax: 503-372-1266
Website: www.cui.com

TITLE:	RCA Jack, Dual, Rt Angle, PCB Mount, Vert.	REV:	A
PART NO.	RCJ-33XXX	UNITS:	MM [INCHES]
DRAWN BY:	ZRJ	APPROVED BY:	
SCALE:			1:1

COLOR INDEX			
PART NO.	INPUT X1	INPUT X2	INPUT X3
RCJ-33234	Red Color	White Color	Yellow Color
RCJ-33X1 X2 X3	Color X1	Color X2	Color X3
COLOR CHART			
1	Black	BARRELS	PLATING
2	Red	TERMINAL 1	Nickel
3	White	TERMINAL 2	Silver
4	Yellow	TERMINAL 3	Silver
5	Blue	HOUSING 1	Silver
6	Green	HOUSING 2	Black Color
7	Orange	INPUT X1	Black Color
		INPUT X2	see color index
		INPUT X3	see color index