XZCC12FDM50B

female, M12, 5-pin, straight connector - cable gland Pg 7

Product availability: Non-Stock - Not normally stocked in distribution facility



Main	
Commercial Status	Commercialised
Accessory / separate part category	Cabling accessories
Accessory / separate part type	Connector
Electrical connection	Straight female connector M12, 5 pins
Collar material	Metal
Status LED	Without
Cable connection	Screw terminal / wire size <= 0 in² (0.75 mm²) / clamping capacity 0.120.24 in (36 mm)

Com	nle	me	nta	arv/
COIII	PiC	,,,,,	1110	∙ı y

Cable gland type	Pg 7	
Cable connector fixing	Screw-on	
[Ue] rated operational voltage	36 V DC 30 V AC	
[In] rated current	3 A	
Enclosure material	Plastic	
Insulating resistance	> 1000 GΩ	
Contact resistance	<= 8000 μOhm	
Product weight	0.04 lb(US) (0.02 kg)	

Environment

IP degree of protection	IP67
Ambient air temperature for operation	-40185 °F (-4085 °C)

Ordering and shipping details

Category	22483 - MACHINE CABLES
Discount Schedule	DS3
GTIN	003389110806274
Nbr. of units in pkg.	1
Package weight(Lbs)	0.06
Product availability	Non-Stock - Not normally stocked in distribution facility
Returnability	Υ
Country of origin	DE

Offer Sustainability

Sustainable offer status	Not Green Premium product	
RoHS	Compliant - since 0726 - Schneider Electric declaration of conformity	

Contractual warranty

Period	18 months	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Schneider Electric: XZCC12FDM50B