


Ceramic Singlelayer DC Disc Capacitors, Class 2, Low Loss (0.5 %), 1 kV_{DC}, 2 kV_{DC}, 3 kV_{DC}


FEATURES

- Low losses
- High stability
- Low DF minimizes self heating at HF
- Ideal for switching to 100 kHz
- Material categorization:
for definitions of compliance please see
www.vishay.com/doc?99912


RoHS
COMPLIANT

APPLICATIONS

In electronic circuits where low losses and high capacitance per volume are essential, for example:

- HF ballast
- SMPS
- Snubber and HV circuits

DESIGN

The capacitors consist of a ceramic disc which is silver plated on both sides. Connection leads are made of tinned copper having diameters of 0.6 mm or 0.8 mm.

The capacitors may be supplied with straight or kinked leads having a lead spacing of 7.5 mm or 10.0 mm.

Coating is made of blue colored flame retardant epoxy resin in accordance with UL 94 V-0.

QUICK REFERENCE DATA			
DESCRIPTION	VALUE		
Ceramic Class	2		
Ceramic Dielectric	Y5S		
Voltage (V _{DC})	1000	2000	3000
Min. Capacitance (pF)	100	100	100
Max. Capacitance (pF)	4700	4700	3300
Mounting	Radial		

MARKING

Marking indicates series, capacitance, tolerance code, and rated voltage.

OPERATING TEMPERATURE RANGE

-40 °C to +125 °C

TEMPERATURE CHARACTERISTICS

Y5S (2C3)

SECTIONAL SPECIFICATIONS

Climatic category (according to EN 60068-1):
40/125/21

APPROVALS

IEC 60384-9, EIA 198

CAPACITANCE RANGE

100 pF to 4700 pF

RATED DC VOLTAGE

- 1 kV_{DC}
- 2 kV_{DC}
- 3 kV_{DC}

DIELECTRIC STRENGTH

- 2000 V_{AC}, 50 Hz, 2 s Component test
- 3000 V_{AC}, 50 Hz, 2 s
- 4000 V_{AC}, 50 Hz, 2 s

INSULATION RESISTANCE AT 500 V_{DC}


≥ 10 000 MΩ (60 s)

TOLERANCE ON CAPACITANCE

± 20 % (± 10 % available on request)

DISSIPATION FACTOR

Max. 0.5 % (1 kHz)



ORDERING INFORMATION							
CAPACITANCE (pF)	TOLERANCE (%)	BODY DIAMETER D_{max} (mm)	BODY THICKNESS S_{max} (mm)	LEAD SPACING ⁽¹⁾ F (mm) $\pm 1 \text{ mm}$	LEAD DIAMETER ⁽¹⁾ d (mm) $\pm 0.05 \text{ mm}$	WIDTH ⁽¹⁾ V (mm) $\pm 0.5 \text{ mm}$	ORDERING CODE MISSING DIGITS SEE ORDERING CODE BELOW
1 kV_{DC}							
100	± 20 ⁽²⁾	7.0	5.0	7.5	0.6	1.1	HAK101#BA###KR
150							HAK151#BA###KR
220							HAK221#BA###KR
270							HAK271#BA###KR
330							HAK331#BA###KR
390							HAK391#BA###KR
470							HAK471#BA###KR
560		HAK561#BA###KR					
680		HAK681#BA###KR					
820		HAK821#BA###KR					
1000		HAK102#BA###KR					
1200		HAK122#BA###KR					
1500		HAK152#BA###KR					
1800		HAK182#BA###KR					
2200		HAK222#BA###KR					
2700		HAK272#BA###KR					
3300		HAK332#BA###KR					
3900		HAK392#BA###KR					
4700	HAK472#BA###KR						
2 kV_{DC}							
100	± 20 ⁽²⁾	7.0	5.0	7.5	0.6	1.6	HBK101#BB###KR
150							HBK151#BB###KR
220							HBK221#BB###KR
270							HBK271#BB###KR
330							HBK331#BB###KR
390							HBK391#BB###KR
470							HBK471#BB###KR
560		HBK561#BB###KR					
680		HBK681#BB###KR					
820		HBK821#BB###KR					
1000		HBK102#BB###KR					
1200		HBK122#BB###KR					
1500		HBK152#BB###KR					
1800		HBK182#BB###KR					
2200		HBK222#BB###KR					
2700		HBK272#BB###KR					
3300		HBK332#BB###KR					
3900		HBK392#BB###KR					
4700	HBK472#BB###KR						



ORDERING INFORMATION							
CAPACITANCE (pF)	TOLERANCE (%)	BODY DIAMETER D _{max.} (mm)	BODY THICKNESS S _{max.} (mm)	LEAD SPACING ⁽¹⁾ F (mm) ± 1 mm	LEAD DIAMETER ⁽¹⁾ d (mm) ± 0.05 mm	WIDTH ⁽¹⁾ V (mm) ± 0.5 mm	ORDERING CODE MISSING DIGITS SEE ORDERING CODE BELOW
3 kV_{DC}							
100	± 20 ⁽²⁾	7.0	5.0	10.0	0.6	1.6	HCK101#BC###KR
150							HCK151#BC###KR
220							HCK221#BC###KR
270							HCK271#BC###KR
330							HCK331#BC###KR
390							HCK391#BC###KR
470		HCK471#BC###KR					
560		HCK561#BC###KR					
680		HCK681#BC###KR					
820		HCK821#BC###KR					
1000		HCK102#BC###KR					
1200		HCK122#BC###KR					
1500		HCK152#BC###KR					
1800		HCK182#BC###KR					
2200		HCK222#BC###KR					
2700		HCK272#BC###KR					
3300		HCK332#BC###KR					

Notes


⁽¹⁾ Standard lead configuration, other lead spacing and diameter available on request

⁽²⁾ ± 10 % available on request


ORDERING CODE							
#	7 th digit	Capacitance tolerance		± 10 % = K, ± 20 % = M			
###	10 th to 12 th digit	Lead configuration		see "General Information"			
Example	HCK	02	M	BC	DF0	K	R
	Series	Capacitance value	Tolerance code	Voltage code	Lead configuration	Internal code	RoHS compliant

MARKING	
<p>D_{max.} ≤ 10 mm</p>	<p>D_{max.} ≥ 11 mm</p>


CAPACITANCE CHANGE VS. VOLTAGE (Typical)



SELF HEATING (Typical)



CAPACITANCE CHANGE AND DISSIPATION FACTOR VS. TEMPERATURE (Typical)



RELATED DOCUMENTS

General Information

www.vishay.com/doc?222001



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.