HIS COPY IS PRO		A RESTRICTED BASIS AND IS NOT TO BE	USED IN ANY WAY DETRI	MENTAL TO THE I	IE INTERESTS OF PANDUIT CORP.
Material		High Conductivity Seamless Copper Tube			
Plating		Electro-Tin			
Wire Size		8 AWG]		
Wire Type		Stranded Copper; Class B: Compact, Compressed or Concentric, Class C: Concentric	.41±.04	8 STR CU	Wire inspection window
Wire Strip Length		3/4 in.		 → → → .63±.02 → .20±.02 DIA (2) PLS 	
Stud Size		#10	.23±.04 —		
UL Listed Wire Connector		Yes, for applications up to 35kv. Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 volts.			(2) FLS
UL Temperature Rating		90° C			
C.S.A Certified Wire Connector		Yes	 		
Panduit Color Code on Barrel		RED			
Panduit Die Index No. on Barrel		. P21	.08±.01	90°±5° 1.03 REF .70±.04	
Alternate Industry Die Index No. () on Barrel		N/A			
	CERTIFIE	ED LISTED Wire Connector		1.53	.18±.01 .27±.01 53 REF Beveled wire entry Barrel markings
					CORP. TINLEY PARK, ILLINOIS
					LCC8-10AWF-L Copper Lua - Two-Hole, Long Barrel with Window, 90° Angle Tongue
	B DRL	RELEASED DESCRIPTION		10342 ECN	42 SCALE DRAWING NO / CAD FILE
		5250Kii I			N/A

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Panduit: LCC8-10AWF-L