

Basic terminal block - URELG 7 - 2820178

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Basic termination blocks with screw connection for NS 32 and NS 35/7.5 DIN rail, with end cover, for ST-REL..., ST-OV... and ST-OE... plugs, 7-pos.

The figure shows versions with a different no. of positions



Key Commercial Data

Packing unit	10 pc	
GTIN	4 017918 076801	
GTIN	4017918076801	

Technical data

Dimensions

Width	45.6 mm
Height	42.5 mm
Depth	112 mm

General

Number of positions	7	
Nominal voltage U _N	400 V (voltage is determined by the coupling connector.)	
Nominal current I _N	16 A (current is determined by the coupling connector.)	
Color	gray	
Insulating material	PA	

Connection data

Conductor cross section solid min.	0.2 mm²
Conductor cross section solid max.	4 mm²
Conductor cross section flexible min.	0.2 mm²
Conductor cross section flexible max.	4 mm²
Conductor cross section AWG min.	24



Basic terminal block - URELG 7 - 2820178

Technical data

Connection data

Conductor cross section AWG max.	12
Connection method	Screw connection
Stripping length	9 mm
Screw thread	M3

Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50	
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"	

Approvals		
Approvals		
Approvals		
DNV GL / EAC		
Ex Approvals		
Approval details		
DNV GL	http://exchange.dnv.com/tari/	/ TAE00001CT
EAC		RU C- DE.A*30.B.01742

Phoenix Contact 2018 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8

32825 Blomberg

Germany

Tel. +49 5235 300 Fax +49 5235 3 41200

http://www.phoenixcontact.com

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Phoenix Contact: 2820178