

4

3

2

1

THIS DRAWING IS UNPUBLISHED.  
VERTRAULICHE UNVERÖFFENTLICHTE ZEICHNUNGRELEASED FOR PUBLICATION  
FREI FUER VERÖFFENTLICHUNG  
ALL RIGHTS RESERVED.  
ALLE RECHTE VORBEHALTENMATED WITH:  
PASSEND ZU:  
BG 3REVISIONS  
ÄNDERUNGENDESCRIPTION  
BESCHREIBUNG

DATE

DWN

APVD

© COPYRIGHT - By -

P

LTR

A10

ECR-17-009069

09FEB2018

SG

MKO

1;5;6 Screw version Thermo  
M3x10  
8  
44  
52

1 Crimp version  
M3x10  
8  
21.2  
34  
27  
33  
44  
52

1;7 spring clamp version  
M3x10  
8  
44  
52

assembly directions

Sti  
Bu  
x19.5

x distance for a safe -  
contact max: 21mm

Printing 1-6 Thermo

4- 5- 6-  
1+ 2+ 3+

Contact arrangement

view from termination side

Printing 1-6 Screw

4 5 6  
1 2 3

NOTES:

1 SUITABLE CRIMP CONTACTS: SERIES HE/HA  
OUTER DIMENSIONS OF INSULATION: MAX. Ø3,2 MM

2 SUITABLE HOOD SIZE 3: SERIES HB; HD; HIP; EMV  
SUITABLE INSERTION AND EXTRACTION TOOL:  
SCREWDRIVER 0,5x3 DIN 5264

3 Strip length: Screw connection 10mm  
Spring clamp connection 10mm Crimp connection 7.5mm

4 STANDARDS:  
DIN EN 61984; DIN EN 60664-1

△ PACKAGING:  
5 SETS IN A CARTON, PRE-MOUNTED

△ SPECIAL PACKAGING: Krauss-Maffei  
PACKAGING UNIT: 150 PIECES

OBSOLETE	OBSOLETE	SUPERSEDED BY T2040063201-000	OBSOLETE	OBSOLETE	DESCRIPTION	MATERIAL	COLOR	ITEM NO. POS.	NOTES SURFACE
4	4	4	4	4	fixing screw	steel	nickel plated	blue	8 M3x10
		6			contact spring clamp	brass	silver plated		7
		6			contact socket screw termination	brass	gold plated		6
		6			contact socket screw termination	brass	silver plated		5
		1			cover spring clamp version		light grey		4
		1			cover crimp version		light grey		3
1	1		1	1	cover screw version		light grey		2
1	1	1	1	1	socket insert		light grey		1
0-3	0-2	7-1	2-3	1-7	1-1				
△	△	△	△	△	△				

  

THIS DRAWING IS A CONTROLLED DOCUMENT. DIESE ZEICHNUNG IST EIN KONTROLLIERTES DOKUMENT.		DWN 12.02.1999 Gräf	 TE Connectivity Female insert HE.6.BU.C/S	
DIMENSIONS: MASSENGHEITEN: mm		CHK 18.02.1999 Schweiger		
TOLERANCES UNLESS OTHERWISE SPECIFIED: ALLGEMEINTOLERANZEN		NAME		DRAWING NO ZEICHNUNGS-NR. C=1103635
0 PLC ± 0.15 1 PLC ± 0.15 2 PLC ± 0.15 3 PLC ± 0.15 4 PLC ± 0.15 ANGLES / WINKEL ± 0.15		PRODUCT SPEC PRODUKTSPEZ.		
MATERIAL		APPLICATION SPEC VERARBEITUNGSSPEZ.		RESTRICTED TO NUR FUER
FINISH/OBERFLAECHE/FARBE		WEIGHT GEWICHT		SCALE MASSSTAB 1:1
ORDERING TEXT / BESTELLTEXT		CUSTOMER DRAWING/KUNDENZEICHNUNG		SHEET BLATT 1 von 1
		SIZE A3 CAGE CODE 00779		REV A10

M3  
37  
27  
20  
36  
44  
52  
Panel cut-out for contact insert  
when used without housing

1470-19 (1/15)