

Product data sheet

Characteristics

XCCRAS1010

shaft coupling - for encoder - homokinetic with bellows Ø 10 to 10 mm

Product availability: Non-Stock - Not normally stocked in distribution facility



Main

Commercial Status	Commercialised
Accessory / separate part designation	Shaft coupling
Accessory / separate part destination	Rotary encoder with solid shaft
Accessory / separate part category	Coupling accessories
Accessory / separate part type	Homokinetic with bellow
Bore diameter encoder side	0.39 in (10 mm)
Bore diameter machine side	0.39 in (10 mm)

Complementary

Collar material	Aluminium
Bellow material	Stainless steel
Maximum angular misalignment	4°
Maximum axial misalignment	+/- 0.5 mm
Maximum lateral misalignment	+/- 0.3 mm
Torque value	<= 7.08 lbf.in (0.8 N.m)
Product weight	0.03 lb(US) (0.015 kg)

Ordering and shipping details

Category	21581 - ENCODERS, XCC
Discount Schedule	DS2
GTIN	00785901694854
Nbr. of units in pkg.	1
Package weight(Lbs)	0.03
Product availability	Non-Stock - Not normally stocked in distribution facility
Returnability	N
Country of origin	FR

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS	Compliant - since 0701 - Schneider Electric declaration of conformity

Contractual warranty

Period	18 months
--------	-----------

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Schneider Electric:](#)

[XCCRAS1010](#)