


EM5025 Series**EuroMag Terminal Blocks**



Header (Mates with EM5015 Series);

5.00 Centers

SPECIFICATIONS**Rating:** 15A, 300V**Center Spacing:** 0.197" (5.00mm)**Housing Material:** Black UL 94V0 Thermoplastic**Contact Material:** Tin-Plated Brass**Operating Temperature:** 120°C (221°F) max., -40°C (-40°F) min.**Recommended PCB Hole Diameters:** 0.059" (1.50mm)**Construction:** Mold-to-Length**Agency Information:**  File E62622; CE Certified**Mating orientations**

Poles	L (mm)	Poles	L (mm)
2	10.0	14	70.0
3	15.0	15	75.0
4	20.0	16	80.0
5	25.0	17	85.0
6	30.0	18	90.0
7	35.0	19	95.0
8	40.0	20	100.0
9	45.0	21	105.0
10	50.0	22	110.0
11	55.0	23	115.0
12	60.0	24	120.0
13	65.0		

To convert to inches, divide by 25.4

Dimensions - in (mm)**Part Numbering System****Series****# of Poles****Mating Plug:** EM5015 pg. 103**EM5025**

02 to 24

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Eaton:](#)

[EM502502](#) [EM502503](#) [EM502504](#) [EM502505](#) [EM502506](#) [EM502508](#) [EM502510](#) [EM502512](#) [EM502514](#)
[EM502524](#) [EM502509](#) [EM502520](#) [EM502523](#) [EM502516](#) [EM502511](#) [EM502513](#) [EM502521](#) [EM502515](#)
[EM502519](#) [EM502507](#) [EM502522](#) [EM502517](#) [EM502518](#)