

Technical drawing of a 3-hole PLCS (Programmable Logic Controller) showing dimensions and labels. The drawing includes a side view and a top view. The side view shows a rectangular unit with three circular modules. The top view shows the circular modules with crosshairs. Dimensions are indicated with arrows and text: ".53 (TYP.)" for the width of the circular modules, ".35" for the width of the rectangular unit, and "L" for the length of the unit. A label "3-hole PLCS" points to the unit.

Technical drawing of a 3-hole PLCS (PLC Slave Card). The drawing shows a side view of the card with three circular holes. Dimensions are indicated: .35 for the hole diameter, .53 (TYP.) for the hole spacing, and A for the total length. A label "N" PLCS" points to the card.

NOTES:
1. UL486A-UI486B LISTED, DUAL RATED CU9AL FOR ALUMINUM OR COPPER CONDUCTORS. MEETS OR EXCEEDS ANSI C119.4
2. SEE TABLE FOR WIRE RANGE.

3. STRIP LENGTH: .56 +/- .06 / 0
4. FOR TIGHTENING TORQUE SEE TABLE
5. VOLTAGE RATING: 600 V. MAX. BUILDING WIRE,
1000 V. MAX. IN SIGNS & FIXTURES.
6. TEMPERATURE RATING: 90 °C (CUPAL).
7. CONNECTOR BLOCK BODY ARE MADE FROM ALUMINUM.
CONDUCTOR PORTS IN CONNECTOR BLOCK
ARE PREFILLED WITH AN OXIDE-INHIBITING COMPOUND.
8. CONNECTOR TO INCLUDE TIN PLATED ALUMINUM CLAMPING
SCREWS FOR EACH CONDUCTOR PORT.
9. INSULATION MATERIAL IS CLEAR PVC.
10. CLAMPING SCREW ACCESS PORTS AND ALL WIRE ENTRY PORTS
PROVIDED WITH REMOVABLE PLASTIC CLOSURE PLUGS.
11. ALL DIMENSIONS SHOWN ARE NOMINAL.
- 12 ONLY ONE CONDUCTOR PER PORT ALLOWED.
- 13 PACKAGE QTY: -12 = 12 PCS.
-6 = 6 PCS.
-4 = 4 PCS.
-3 = 3 PCS.
-2 = 2 PCS.

[illegible]

PANDUIT CORP. • TINLEY PARK, ILLINOIS

**MULTI-TAP INSULATED CONNECTORS
PCSB2/0 SERIES SINGLE SIDED**

UNLESS OTHERWISE SPECIFIED

UNLESS OTHERWISE SPECIFIED,
ALL DIMENSIONS ARE GIVEN IN
INCHES, THIRD ANGLE PROJECTION

SCALE	1 5.1
-------	-------

SEE NOTE 1 ABOVE

DRAWING NO / CAD FILE	DWG
C41523_03	B

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Panduit:

[PCSB2/0-3S-6Y](#) [PCSB2/0-4S-6Y](#) [PCSB2/0-6S-4Y](#) [PCSB2/0-5S-4Y](#)