

Product: [8424](#) 

Microphone Cable, 4 Conductor 20 AWG, TC



Product Description

Microphone 4 Conductor 20 AWG stranded (26x34) high-conductivity tinned copper conductors, EPDM rubber insulation, rayon braid, TC braid shield (85% coverage), cotton wrap, EPDM rubber jacket.

Technical Specifications

Product Overview

Suitable Applications:	Low-Impedance Audio/Microphone Cable
------------------------	--------------------------------------

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	Nominal Diameter	No. of Conductors
20	26x34	High Conductivity Tinned Copper	0.037 in	4

Conductor Count:	4
------------------	---

Insulation

Material	Nominal Diameter	Nominal Wall Thickness
EPDM - Ethylene Propylene Diene Monomer	0.083 in	0.023 in

Color Chart

Number	Color
1	Black
2	White
3	Red
4	Green

Outer Shield Material

Type	Material	Coverage [%]
Braid	Rayon	
Braid	TC - Tinned Copper	85 %

Outer Jacket Material

Material	Nominal Diameter	Separator Material
EPDM - Ethylene Propylene Diene Monomer	0.294 in	Cotton Serve

Electrical Characteristics

Conductor DCR

Nominal Conductor DCR	Nominal Outer Shield DCR
10.2 Ohm/1000ft	3.2 Ohm/1000ft

Capacitance

Nom. Capacitance Between Conductors in Quad	Nom. Capacitance Conductor to Conductor
59 pF/ft	47 pF/ft

Inductance

Nominal Inductance

0.18 µH/ft

Impedance**Nominal Characteristic Impedance**

52 Ohm

Delay**Nominal Velocity of Propagation (VP) [%]**

52 %

Current**Max. Recommended Current [A]**

3.2 Amps per conductor @ 25°C

Voltage**UL Voltage Rating**

600 V RMS

Electrical Characteristics Notes:	2/c 17AWG equivalent DCR when connected to a 3-pin XLR
-----------------------------------	--

Other Electrical Characteristic 2:	59 pF/ft - Nom. Cap. Between Cond. In a Quad Config.
------------------------------------	--

Temperature Range

Non-UL Temp Rating:	60°C
---------------------	------

Operating Temp Range:	-50°C To +90°C
-----------------------	----------------

Mechanical Characteristics

Bulk Cable Weight:	61 lbs/1000ft
--------------------	---------------

Max Recommended Pulling Tension:	87 lbs
----------------------------------	--------

Min Bend Radius/Minor Axis:	3 in
-----------------------------	------

Applicable Environmental and Other Programs

Environmental Space:	Indoor (Not Riser or Plenum)
----------------------	------------------------------

EU Directive 2000/53/EC (ELV):	Yes
--------------------------------	-----

EU Directive 2003/96/EC (BFR):	Yes
--------------------------------	-----

EU Directive 2011/65/EU (ROHS II):	Yes
------------------------------------	-----

EU Directive 2012/19/EU (WEEE):	Yes
---------------------------------	-----

EU Directive 2015/863/EU:	Yes
---------------------------	-----

EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
--------------------------	-------------------------------

EU CE Mark:	Yes
-------------	-----

EU RoHS Compliance Date (yyyy-mm-dd):	2004-01-01
---------------------------------------	------------

MII Order #39 (China RoHS):	Yes
-----------------------------	-----

Suitability

Suitability - Indoor:	Yes
-----------------------	-----

Flammability, LSOH, Toxicity Testing

UL voltage rating:	600 V RMS
--------------------	-----------

Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

Part Number**Variants**

Item #	Color	Putup Type	Length	UPC
--------	-------	------------	--------	-----

8424 010100	Black	Reel	100 ft	612825206606
8424 010250	Black	Reel	250 ft	612825206620
8424 010500	Black	Reel	500 ft	612825206583
8424 010U500	Black	UnReel	500 ft	612825206804
8424 0101000	Black	Reel	1,000 ft	612825206613

Footnote: C - CRATE REEL PUT-UP.

Product Notes

Notes:	Overall Cabling Separator Material: Rayon Braid. Outer Shield Separator Material: Cotton Wrap. Quad connection scheme: The black and red wires (or wires directly opposite one another) are connected together to form one conductor, and similarly the white and green wires (or remaining wires) are connected together to form the second conductor. Outer Shield Separator Material: Cotton Wrap
--------	--

History

Update and Revision:	Revision Number: 0.300 Revision Date: 04-28-2020
----------------------	--

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Belden Wire & Cable:](#)

[8424 010500](#) [8424 010250](#) [8424 010U500](#)