Product data sheet Characteristics

XS1M18PAS40

inductive sensor XS1 M18 - L60mm - stainless - Sn5mm - 12..24VDC - cable 2m



Product availability: Non-Stock - Not normally stocked in distribution facility

TTT COLUMN	
Commercial Status	Commercialised
Range of product	OsiSense XS
Series name	Application
Sensor type	Inductive proximity sensor
Product specific application	Selective detection of ferrous materials
Sensor name	XS1
Sensor design	Cylindrical M18
Size	60 mm
Body type	Fixed
Detector flush mounting acceptance	Flush mountable
Material	Stainless steel
Type of output signal	Discrete
Wiring technique	3-wire
[Sn] nominal sensing distance	0.2 in (5 mm)
Discrete output function	1 NO
Output circuit type	DC
Discrete output type	PNP
Electrical connection	Cable
Cable length	6.56 ft (2 m)
[Us] rated supply voltage	1224 V DC with reverse polarity protection
Switching capacity in mA	<= 200 mA with overload and short-circuit protection
IP degree of protection	IP68 conforming to IEC 60529

Complementary

Complementary	
ISO thread	M18 x 1
Detection face	Frontal
Front material	PPS
Enclosure material	Stainless steel : 304 CU
Operating zone	00.16 in (04 mm)
Cable composition	3 x 0.34 mm²
Wire insulation material	PvR
Status LED	1 LED yellow for output state
Supply voltage limits	1038 V DC
Switching frequency	<= 1000 Hz
Voltage drop	<= 2.6 V at closed state
Current consumption	015 mA at no-load
Delay first up	<= 10 ms
Delay response	<= 0.3 ms
Delay recovery	<= 0.7 ms
Marking	CE
Threaded length	2.05 in (52 mm)

Length	2.36 in (60 mm)	
Product weight	0.26 lb(US) (0.12 kg)	
Environment		
Product certifications	CSA UL	
Ambient air temperature for operation	-13158 °F (-2570 °C)	
Ordering and shipping details		
Category	22486 - SENSORS, PROXIMITY	
Discount Schedule	DS2	
GTIN	003389110835595	
Nbr. of units in pkg.	1	
Package weight(Lbs)	0.32	
Product availability	Non-Stock - Not normally stocked in distribution facility	
Returnability	N	
Country of origin	FR	
Offer Sustainability		
Sustainable offer status	Green Premium product	
RoHS	Compliant - since 1104 - Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
Product environmental profile	Available Download Product Environmental	
	Available Download End Of Life Manual	

18 months

Period

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Schneider Electric: XS1M18PAS40