



# SmartRack 116 16-Port Console Cat5 KVM with 17-in. LCD

MODEL NUMBER: 0SU52091







Description
Local Access

Control More Servers

Slim, 1U Solution that Saves Space

#### **Features**

- 16 Port KVM
- 17" TFT LCD Display
- BIOS level access
- Multi-platform PS/2 and USB support
- Extends distance between servers and switch up to 30 meters/100 feet
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

### **Specifications**

| OVERVIEW |              |
|----------|--------------|
| UPC Code | 654518211344 |

#### **Highlights**

- 16 Port KVM
- 17" TFT LCD Display
- BIOS level access
- Multi-platform PS/2 and USB support
- Extends distance between servers and switch up to 30 meters/100 feet
- Compliant with the Federal
   Trade Agreements Act (TAA) for
   GSA Schedule purchases

## System Requirements Operating System

Compatible with Windows,
 Linux, Unix and all other major
 operating systems

#### Resolution

 Supports video resolutions up to 1280 x 1024

#### Package Includes

- SmartRack 116 Cat5 KVM Switch
- RS232 Download Cable
- Rackmount Kit
- Owner's Manual





| Console                             | Yes                        |
|-------------------------------------|----------------------------|
| Consolic                            |                            |
| PHYSICAL                            |                            |
| Color                               | Black                      |
| Shipping Weight (kg)                | 19.00                      |
| Shipping Weight (lbs.)              | 41.89                      |
| Unit Dimensions (hwd / cm)          | 4.4 x 44.75 x 64           |
| Unit Dimensions (hwd / in.)         | 1.7 x 17.6 x 25.2          |
| Unit Weight (kg)                    | 18.19                      |
| Unit Weight (lbs.)                  | 40.1                       |
| ENVIRONMENTAL                       |                            |
| Storage Temperature Range           | -40 to 70 C / -40 to 158 F |
| Relative Humidity                   | 10 to 90% RH               |
| Operating Temperature               | 0 to 40 C / 32 to 104 F    |
| COMMUNICATIONS                      |                            |
| Port Control                        | Hotkeys, OSD               |
| IP Remote Access                    | No                         |
| CONNECTIONS                         |                            |
| Ports                               | 16                         |
| PC/Server Connections               | VGA; USB; PS/2             |
| FEATURES & SPECIFICATIONS           |                            |
| Number of Users                     | 1                          |
| NIAP-Certified Secure               | No                         |
| Cat5 KVM Switch                     | Yes                        |
| WARRANTY                            |                            |
| Product Warranty Period (Worldwide) | 3-year limited warranty    |

© 2020 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <a href="https://www.tripplite.com/products/product-certification-agencies">https://www.tripplite.com/products/product-certification-agencies</a>