



RECOMMENDED HOLE LAYOUT

А

4805 (3/11)

1	ASSEMBLY MAY BE BROKEN TO THE
2	TRUE POSITION TOLERANCE OF THE I FLAT AGAINST THE PRINTED CIRCUIT
$\sqrt{3}$	THE NOTED DIMENSIONS APPLY AT TH
4	POINT OF MEASUREMENT FOR PLATIN
5	OBSOLETE PARTS: OBSOLETE CIS STR

4





THIS	DRAWING	IS A C
	DIMENSIONS	<u>s</u> .
	DIMENSION	J.
	INCHES	
	- - - - - - - - - - - - - -	
MATERIAI	L HOUSING: FLAME RETAR THERMOPLAS COLOR-BLA	TIC;
PC	OSTS: COPPER	ALLOY

		2					1			
	LOC	DIST		REVISIONS						
	AD	00	Ρ	LTR		DESCRIPTION		DATE	DWN	APVD
·		•		Н	REVISED PER E	20-14-000068	3	25APR2014	NK	MM
		·								

DESIRED NUMBER OF POSITIONS

E POST TIPS APPLIES WHEN THE HEADERS ARE HELD T BOARD

THE INTERSECTION OF THE POST AND HOUSING

ING THICKNESS

TREAMLINING PER D.RENAUD/D.SINISI

_		3.984	3.900	39	40	4-103185-0
	\wedge	3.884	3.800	- 38 -	- 39	3-103185-9
	$\overline{5}$	3.784	3.700		- 38 -	3-103185-8
(OBSOLETE	3.684	3.600	- 36 -	37	3-103185-7
_		3.584	3.500	35	36	3-103185-6
		3.484	3.400	- 34	35	3-103185-5
		3.384	3.300	-33	- 34	3-103185-4
		3.284	3.200	- 32	33	3-103185-3
	\bigwedge	3.184	3.100	31	32	3-103185-2
	$\overline{5}$	3.084	3.000		31	3-103185-1
	OBSOLETE	2.984	2.900	-29		3-103185-0
		2.884	2.800	-28-	-29	2-103185-9
		2.784	2.700	27		2-103185-8
		2.684	2.600	-26	27	2 - 103185 - 7
	OBSOLETE	2.584	2.500	25	26	2-103185-6
	OBSOLETE	2.00	2.200	20	-25	2-103185-5
<u>/ 3 </u>		2.384	2.300	23	24	2-103185-4
Γ	^	2.384	2.200	22	23	2-103185-4 2-103185-3
	5	2.20+ 2.184	2.200	22	22	
	OBSOLETE	2.084	2.000	20	21	2 - 103185 - 2
	JESULEIE	1.984	1.900	19	20	2 - 103185 - 1
Г		1.904	1.800	<u> </u>	19	2-103185-0
	5					1-103185-9
		1.784		17	18	1-103185-8
	OBSOLETE	1.684	1.600	16	17	1-103185-7
	<u> </u>	1.584	1.500	15	16	1-103185-6
RCEDED BY	6-146280-5		1.400	14	15	1-103185-5
\wedge \square		1.384	1.300	13	14	1-103185-4
$25\sqrt{2}$	OBSOLETE	1.284	1.200	12	13	1-103185-3
		1.184	1.100	1 1	12	1-103185-2
		1.084	1.000	10	1 1	1-103185-1
RCEDED BY	6-146280-0		.900	9	10	1-103185-0
		.884	.800	8	9	103185-9
		.784	.700	7	8	103185-8
		.684	.600	6	7	103185-7
		.584	.500	5	6	103185-6
		.484	.400	4	5	103185-5
		.384	.300	3	4	103185-4
		.284	.200	2	3	103185-3
		.184	.100	1	2	103185-2
		.084			1	103185-1
		C	B	A	NO OF POSN	PART NUMBER
A CONTROLLED DOCUMENT.	DWN	130CT87				
, JOHNOLLED DOCUMENT.	н MOLL Снк	200CT87		e te	TE C	onnectivity
TOLERANCES UNLESS OTHERWISE SPECIFIED:	T. CLARK	200CT87 NAME				
0 PLC ± -	T. CLARK PRODUCT SPEC				MOD II, B	
$\begin{array}{c} 1 \ PLC \qquad \pm \ - \\ 2 \ PLC \qquad \pm \ - \end{array}$	_		SI		, .100CL, \ Square	
3 PLC ± .005 4 PLC ± -	APPLICATION SPEC	SIZ	E CAGE CODE			RESTRICTED TO
ANGLES ± – FINISH POSTS:	WEIGHT	A		C- 1031	85	
.000015 GOLD ON CONTACT ARE .000100000200 MATTE TIN-LEA ON SOLDER TAIL, ALL OVER	D		1 00773		ALE SH	EET OF REV
.000050 NICKEL	CUSTOMER DRA	WING			4:1	<u>1 1 H</u>

D

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TE Connectivity: 103185-1