



15 Watt Fixed Wall Plug Series Adapter Meets Level VI Requirements



Features

- Limited Power Source (LPS)
- Class B EMI
- Level VI Compliant
- Class II Double Insulated
- High Efficiency
- Low Cost

Applications

- Wireless Communications
- Peripherals
- Portable Equipment
- PDA

Safety Approvals

- cUL/UL

Mechanical Characteristics

- Length: 71.7mm (2.82in)
- Width: 50mm (1.97in)
- Height: 33.2mm (1.31in)
- Weight: 145g (5.12oz)

Output Specifications

Model	DC Output Voltage	Load		Ripple ⁽¹⁾ P-P (max.)	Regulation Line & Load
		Min.	Max.		
PSC15A-050-R	5V	0A	3.0A	100mV	$\pm 5\%$
PSC15A-060-R	5.9V	0A	2.5A	100mV	$\pm 5\%$
PSC15A-075-R	7.5V	0A	2.0A	100mV	$\pm 5\%$
PSC15A-090-R	9V	0A	1.67A	120mV	$\pm 5\%$
PSA15A-120P6-R	12V	0A	1.25A	100mV	$\pm 5\%$
PSA15A-150P6-R	15V	0A	1.0A	100mV	$\pm 5\%$
PSA15A-240P6-R	24V	0A	0.65A	200mV	$\pm 5\%$
PSA15A-480P6-R	48V	0A	0.31A	400mV	$\pm 5\%$

(1) Measured after 30 minutes with by-pass capacitors 0.1uF/10uF at output connector terminal and oscilloscope set at 20Mhz.

Phihong is not responsible for any error, and reserves the right to make changes without notice. Please visit our website at www.phihong.com for the most up-to-date specifications and contact information.

Input:

AC Input Voltage Rating
100 to 240V AC

AC Input Voltage Range
90 to 264V AC

AC Input Frequency
47 to 63Hz

Input Current
0.5A (RMS) maximum at 120V AC
0.25A (RMS) maximum at 240V AC

Leakage Current
0.25mA maximum at all line conditions

Inrush Current
<40A for 120V AC at maximum load
<60A for 240V AC at maximum load
(Cold start at ambient 25°C)

Input Power Saving
0.1W maximum at no load

Output:

Efficiency
US DOE Level VI

Environmental:**Temperature**

Operation	0 to +40°C
Non-operation	-40 to +85°C
Humidity	20 to 90%

Emissions

Complies with FCC Class B
Complies with EN55032 Class B

Immunit

IEC610004-2
IEC610004-3
IEC610004-4
IEC610004-5
IEC610004-6
IEC61000-4-8
IEC61000-4-11
EN61000-3-2

Hold-up Time

8mS minimum at 120V AC and maximum load

Over-Voltage Protection

Zener clamping if voltage exceeds 120% of limit

Over-Current Protection

Output equipped with short circuit protection – auto-restart

Short-Circuit Protection

Output can be shorted without damage


Dielectric Withstand (Hi-pot) Test

Primary to Secondary: 3000V AC for 1 min., 10mA

DC Output Connector

2.1 x 5.5mm Center Positive Barrel

Dimension Diagram Unit: mm



**Supplier's Declaration of Conformity
47 CFR § 2.1077 Compliance Information**

Phihong USA Corporation
47800 Fremont Boulevard
Fremont, CA 94538
Telephone: (510) 445-0100
www.phihong.com

The models in this product series have been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

Changes or modifications to equipment not expressly approved by PHIHONG could void the user's authority to operate the equipment.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Phihong](#):

[PSC15A-075](#) [PSC15A-050](#) [PSC15A-060](#) [PSC15A-090](#) [PSA15A-120P](#) [PSA15A-150P](#) [PSA15A-240P](#) [PSA15A-480P](#)