



# CRYSTEK

## MICROWAVE

A DIVISION OF CRYSTEK CORPORATION

### RG-316 DOUBLE SHIELDED RF COAX CABLE ASSEMBLIES

- RG316DS 50 Ohm Coaxial Cables**
- SMA Male Straight / SMA Male Straight
- SMA Male Straight / SMA Female Bulkhead
- SMA Male Straight / SMA Male Right Angle
- SMA Male Right Angle / SMA Male Right Angle
- SMA Male Straight / BNC Male Straight



#### Features:

- Strain Relief:** Adhesive shrink tubing over crimp area
- Center Conductor:** SCCS (Silver-Plated Copper Clad Steel Stranded)
- Shielding:** Double Braid, SPC(2) (Silver-plated copper)
- Insulation:** PTFE (Polytetrafluoroethylene) dielectric
- Jacket:** FEP (Fluorinated Ethylene Propylene)
- Operating Temperature:** -40°C to +85°C
- Minimum Bend Radius:** 0.6"

*Custom Lengths Available  
(Minimum Order Quantity Required)*

Electrical Data:  
PN: CCSMA-MM-RG316DS-24

Freq. (MHz)	Insertion Loss	VSWR
50	-0.035	1:1.014
500	-0.173	1:1.092
1000	-0.303	1:1.159
2000	-0.468	1:1.358
3000	-0.502	1:1.257
4000	-0.787	1:1.473
5000	-0.822	1:1.288
6000	-1.09	1:1.596
7000	-1.27	1:1.473
8000	-1.42	1:1.579

#### SMA / SMA [Straight/Straight]

Part Number	Description	Length
CCSMA-MM-RG316DS-6	RG316 Double Shielded Cable, SMA Male/Male, Straight/Straight	6"
CCSMA-MM-RG316DS-12	RG316 Double Shielded Cable, SMA Male/Male, Straight/Straight	12"
CCSMA-MM-RG316DS-24	RG316 Double Shielded Cable, SMA Male/Male, Straight/Straight	24"
CCSMA-MM-RG316DS-36	RG316 Double Shielded Cable, SMA Male/Male, Straight/Straight	36"
CCSMA-MM-RG316DS-48	RG316 Double Shielded Cable, SMA Male/Male, Straight/Straight	48"

#### SMA / SMA [Straight/Right Angle]

Part Number	Description	Length
CCSMA1-MM-RG316DS-6	RG316 Double Shielded Cable, SMA Male/Male, Straight/RA	6"
CCSMA1-MM-RG316DS-12	RG316 Double Shielded Cable, SMA Male/Male, Straight/RA	12"
CCSMA1-MM-RG316DS-24	RG316 Double Shielded Cable, SMA Male/Male, Straight/RA	24"
CCSMA1-MM-RG316DS-36	RG316 Double Shielded Cable, SMA Male/Male, Straight/RA	36"



**CRYSTEK**  
CORPORATION

12730 COMMONWEALTH DRIVE • FORT MYERS, FL 33913  
 PHONE: 239-561-3311 • 800-237-3061 Rev.: H  
 FAX: 239-561-1025 • WWW.CRYSTEK.COM Date: 3-01-16



**SMA / SMA [Right Angle/Right Angle]**

Part Number	Description	Length
CCSMA2-MM-RG316DS-6	RG316 Double Shielded Cable, SMA Male/Male, RA/RA	6"
CCSMA2-MM-RG316DS-12	RG316 Double Shielded Cable, SMA Male/Male, RA/RA	12"
CCSMA2-MM-RG316DS-24	RG316 Double Shielded Cable, SMA Male/Male, RA/RA	24"
CCSMA2-MM-RG316DS-36	RG316 Double Shielded Cable, SMA Male/Male, RA/RA	36"

**SMA / SMA [Male Stright/Female Straight]**

Part Number	Description	Length
CCSMA-MFB-RG316DS-12	RG316 Double Shielded Cable, SMA Male/Female, STR/Bulkhead	12"
CCSMA-MFB-RG316DS-24	RG316 Double Shielded Cable, SMA Male/Female, STR/Bulkhead	24"
CCSMA-MFB-RG316DS-36	RG316 Double Shielded Cable, SMA Male/Female, STR/Bulkhead	36"



**SMA / BNC [Straight/Straight]**

Part Number	Description	Length
CCBNS-MM-RG316DS-6	RG316 Double Shielded Cable, SMA Male/BNC Male, Straight	6"
CCBNS-MM-RG316DS-12	RG316 Double Shielded Cable, SMA Male/BNC Male, Straight	12"
CCBNS-MM-RG316DS-24	RG316 Double Shielded Cable, SMA Male/BNC Male, Straight	24"
CCBNS-MM-RG316DS-36	RG316 Double Shielded Cable, SMA Male/BNC Male, Straight	36"



# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

## Crystek:

[CCSMA-MM-RG316DS-12](#) [CCSMA-MM-RG316DS-24](#) [CCSMA-MM-RG316DS-36](#) [CCSMA-MM-RG316DS-48](#)  
[CCBNS-MM-RG316DS-12](#) [CCBNS-MM-RG316DS-24](#) [CCBNS-MM-RG316DS-36](#) [CCBNS-MM-RG316DS-6](#) [CCSMA1-](#)  
[MM-RG316DS-12](#) [CCSMA1-MM-RG316DS-24](#) [CCSMA1-MM-RG316DS-36](#) [CCSMA1-MM-RG316DS-6](#) [CCSMA2-](#)  
[MM-RG316DS-12](#) [CCSMA2-MM-RG316DS-24](#) [CCSMA2-MM-RG316DS-36](#) [CCSMA2-MM-RG316DS-6](#) [CCSMA-MM-](#)  
[RG316DS-6](#) [CCSMA-MM-RG316DS-12P](#) [CCSMA-MM-RG316DS-24P](#) [CCSMA-MM-RG316DS-36P](#) [CCSMA-MM-](#)  
[RG316DS-48P](#) [CCSMA-MM-RG316DS-6P](#) [CCSMA-MFB-RG316DS-12](#) [CCSMA-MM-RG316DS-06P](#)