


APTGLQ40HR120CT3G

Phase Leg & Dual Common Emitter Power Module



High speed Trench & Field Stop IGBT4 (Q1, Q2):
 $V_{CES} = 1200V$; $I_C = 40A$ @ $T_c = 80^\circ C$

Trench & Field Stop IGBT3 (Q3, Q4):
 $V_{CES} = 600V$; $I_C = 50A$ @ $T_c = 80^\circ C$

Application


- Solar converter
- Uninterruptible Power Supplies

Features

- **Q1, Q2 High speed Trench + field Stop IGBT4**
 - Low voltage drop
 - Low tail current
- **Q3, Q4 Trench + field Stop IGBT3**
 - Low voltage drop
 - Low tail current
 - Switching frequency up to 20 kHz
- **SiC Schottky Diode (D3, D4)**
 - Zero reverse recovery
 - Zero forward recovery
 - Temperature Independent switching behavior
 - Positive temperature coefficient on VF
- Kelvin emitter for easy drive
- Very low stray inductance
- High level of integration
- Internal thermistor for temperature monitoring

Benefits

- Stable temperature behavior
- Very rugged
- Solderable terminals for easy PCB mounting
- Direct mounting to heatsink (isolated package)
- Low junction to case thermal resistance
- Easy paralleling due to positive T_c of V_{CESat}
- Low profile
- RoHS Compliant



All multiple inputs and outputs must be shorted together
 10/11 ; 23/24 ; 2/3 ; ...

All ratings @ $T_j = 25^\circ C$ unless otherwise specified

 **CAUTION:** These Devices are sensitive to Electrostatic Discharge. Proper Handling Procedures Should Be Followed.
 See application note APT0502 on www.microsemi.com

1. High speed Trench & Field Stop IGBT4 Phase Leg Q1&Q2 (per IGBT)
Absolute maximum ratings (per IGBT)

Symbol	Parameter	Max ratings	Unit
V_{CES}	Collector - Emitter Breakdown Voltage	1200	V
I_C	Continuous Collector Current	$T_C = 25^\circ C$	75
		$T_C = 80^\circ C$	40
I_{CM}	Pulsed Collector Current	$T_C = 25^\circ C$	160
V_{GE}	Gate - Emitter Voltage		± 20
P_D	Maximum Power Dissipation		250
RBSOA	Reverse Bias Safe Operating Area	$T_j = 150^\circ C$	80A @ 1100V

Electrical Characteristics (per IGBT)

Symbol	Characteristic	Test Conditions	Min	Typ	Max	Unit
I_{CES}	Zero Gate Voltage Collector Current	$V_{GE} = 0V, V_{CE} = 1200V$			100	μA
$V_{CE(sat)}$	Collector Emitter Saturation Voltage	$V_{GE} = 15V$	$T_j = 25^\circ C$	1.7	2.05	2.4
		$I_C = 40A$	$T_j = 150^\circ C$		2.6	
$V_{GE(th)}$	Gate Threshold Voltage	$V_{GE} = V_{CE}, I_C = 1\text{ mA}$	5.0	5.8	6.5	V
I_{GES}	Gate - Emitter Leakage Current	$V_{GE} = 20V, V_{CE} = 0V$			120	nA

Dynamic Characteristics (per IGBT)

Symbol	Characteristic	Test Conditions	Min	Typ	Max	Unit	
C_{ies}	Input Capacitance	$V_{GE} = 0V$ $V_{CE} = 25V$ $f = 1MHz$		2300		pF	
C_{oes}	Output Capacitance			150			
C_{res}	Reverse Transfer Capacitance			135			
Q_G	Gate charge	$V_{GE} = 15V, I_C = 40A$ $V_{CE} = 960V$		185		nC	
$T_{d(on)}$	Turn-on Delay Time	Inductive Switching ($25^\circ C$) $V_{GE} = \pm 15V$ $V_{Bus} = 600V$ $I_C = 40A$ $R_G = 12\Omega$		30		ns	
T_r	Rise Time			57			
$T_{d(off)}$	Turn-off Delay Time			290			
T_f	Fall Time			16			
$T_{d(on)}$	Turn-on Delay Time	Inductive Switching ($150^\circ C$) $V_{GE} = \pm 15V$ $V_{Bus} = 600V$ $I_C = 40A$ $R_G = 12\Omega$		30		ns	
T_r	Rise Time			49			
$T_{d(off)}$	Turn-off Delay Time			366			
T_f	Fall Time			48			
E_{on}	Turn on Energy	$V_{GE} = \pm 15V$ $V_{Bus} = 600V$ $I_C = 40A$ $R_G = 12\Omega$	$T_j = 25^\circ C$	3.2		mJ	
E_{off}	Turn off Energy		$T_j = 150^\circ C$	3.75			
I_{sc}	Short Circuit data		$T_j = 25^\circ C$	1.2			
			$T_j = 150^\circ C$	2.25			
R_{thJC}	Junction to Case Thermal Resistance	$V_{GE} \leq 15V ; V_{Bus} = 600V$ $t_p \leq 10\mu s ; T_j = 150^\circ C$		150		A	

Diode ratings and characteristics (D1 & D2) (per diode)

Symbol	Characteristic	Test Conditions		Min	Typ	Max	Unit	
V_{RRM}	Maximum Peak Repetitive Reverse Voltage			1200			V	
I_{RM}	Maximum Reverse Leakage Current	$V_R = 1200V$				100	μA	
I_F	DC Forward Current	$T_c = 80^\circ C$		25			A	
V_F	Diode Forward Voltage	$I_F = 25A$			2.6	3.1	V	
		$I_F = 50A$			3.2			
		$I_F = 25A$	$T_j = 125^\circ C$		1.8			
t_{rr}	Reverse Recovery Time	$I_F = 25A$ $V_R = 667V$ $di/dt = 200A/\mu s$	$T_j = 25^\circ C$		320		ns	
			$T_j = 125^\circ C$		360			
Q_{rr}	Reverse Recovery Charge		$T_j = 25^\circ C$		480		nC	
			$T_j = 125^\circ C$		1800			
R_{thJC}	Junction to Case Thermal Resistance					1.4	$^\circ C/W$	

2. Trench & Field Stop IGBT3 Dual common emitter Q3&Q4 (per IGBT)
Absolute maximum ratings (per IGBT)

Symbol	Parameter		Max ratings	Unit
V_{CES}	Collector - Emitter Breakdown Voltage		600	V
I_C	Continuous Collector Current	$T_c = 25^\circ C$	80	A
		$T_c = 80^\circ C$	50	
I_{CM}	Pulsed Collector Current	$T_c = 25^\circ C$	100	
V_{GE}	Gate – Emitter Voltage		± 20	V
P_D	Maximum Power Dissipation	$T_c = 25^\circ C$	176	W
RBSOA	Reverse Bias Safe Operating Area	$T_j = 150^\circ C$	100A @ 550V	

Electrical Characteristics (per IGBT)

Symbol	Characteristic	Test Conditions		Min	Typ	Max	Unit
I_{CES}	Zero Gate Voltage Collector Current	$V_{GE} = 0V, V_{CE} = 600V$				250	μA
$V_{CE(sat)}$	Collector Emitter Saturation Voltage	$V_{GE} = 15V$	$T_j = 25^\circ C$		1.5	1.9	V
		$I_C = 50A$	$T_j = 150^\circ C$		1.7		
$V_{GE(th)}$	Gate Threshold Voltage	$V_{GE} = V_{CE}, I_C = 600\mu A$		5.0	5.8	6.5	V
I_{GES}	Gate – Emitter Leakage Current	$V_{GE} = 20V, V_{CE} = 0V$				600	nA

Dynamic Characteristics (per IGBT)

Symbol	Characteristic	Test Conditions	Min	Typ	Max	Unit
C_{ies}	Input Capacitance	$V_{GE} = 0V$ $V_{CE} = 25V$ $f = 1MHz$		3150		pF
C_{oes}	Output Capacitance			200		
C_{res}	Reverse Transfer Capacitance			95		
Q_G	Gate charge	$V_{GE} = \pm 15V$, $I_C = 50A$ $V_{CE} = 300V$		500		nC
$T_{d(on)}$	Turn-on Delay Time	Inductive Switching (25°C) $V_{GE} = \pm 15V$ $V_{Bus} = 300V$ $I_C = 50A$ $R_G = 8.2\Omega$		110		ns
T_r	Rise Time			45		
$T_{d(off)}$	Turn-off Delay Time			200		
T_f	Fall Time			40		
$T_{d(on)}$	Turn-on Delay Time	Inductive Switching (150°C) $V_{GE} = \pm 15V$ $V_{Bus} = 300V$ $I_C = 50A$ $R_G = 8.2\Omega$		120		ns
T_r	Rise Time			50		
$T_{d(off)}$	Turn-off Delay Time			250		
T_f	Fall Time			60		
E_{on}	Turn-on Switching Energy	$V_{GE} = \pm 15V$ $V_{Bus} = 300V$	$T_j = 25^\circ C$	0.2		mJ
E_{off}	Turn-off Switching Energy		$T_j = 150^\circ C$	0.26		
I_{sc}	Short Circuit data	$V_{GE} \leq 15V$; $V_{Bus} = 360V$ $t_p \leq 10\mu s$; $T_j = 150^\circ C$		250		A
R_{thJC}	Junction to Case Thermal Resistance				0.85	°C/W

3. SiC diode ratings and characteristics (D3 & D4) (per diode)

Symbol	Characteristic	Test Conditions	Min	Typ	Max	Unit
V_{RRM}	Maximum Peak Repetitive Reverse Voltage		600			V
I_{RM}	Maximum Reverse Leakage Current	$V_R = 600V$	$T_j = 25^\circ C$	10	60	μA
			$T_j = 175^\circ C$	20	300	
I_F	DC Forward Current		$T_c = 100^\circ C$	10		A
V_F	Diode Forward Voltage	$I_F = 10A$	$T_j = 25^\circ C$	1.6	1.8	V
			$T_j = 175^\circ C$	2	2.4	
Q_C	Total Capacitive Charge	$I_F = 10A$, $V_R = 600V$ $di/dt = 500A/\mu s$		28		nC
C	Total Capacitance	$f = 1MHz$, $V_R = 200V$ $f = 1MHz$, $V_R = 400V$		65		pF
				50		
R_{thJC}	Junction to Case Thermal Resistance				2.5	°C/W

4. Thermal & package characteristics

Temperature sensor NTC

Symbol	Characteristic	Min	Typ	Max	Unit
R_{25}	Resistance @ 25°C		22		$\text{k}\Omega$
$\Delta R_{25}/R_{25}$	Resistance tolerance			5	%
$\Delta B/B$	Beta tolerance			3	
$B_{25/100}$	$T_{25} = 298.16 \text{ K}$		3980		K


$$R_T = \frac{R_{25}}{\exp\left[B_{25/100}\left(\frac{1}{T_{25}} - \frac{1}{T}\right)\right]}$$

T: Thermistor temperature
R_T: Thermistor value at T

Thermal and package characteristics

Symbol	Characteristic	Min	Typ	Max	Unit
V_{ISOL}	RMS Isolation Voltage, any terminal to case $t = 1$ min, 50/60Hz	4000			V
T_J	Operating junction temperature range	-40		175	
T_{STG}	Storage Temperature Range	-40		125	$^{\circ}\text{C}$
T_C	Operating Case Temperature	-40		100	
Torque	Mounting torque	To heatsink	M4	2	3
Wt	Package Weight			110	g


SP3F Package outline (dimensions in mm)






See application note 1906 - Mounting Instructions for SP3F Power Modules on www.microsemi.com





5. Typical performance curve




Q1, Q2 High speed Trench + field stop IGBT4 + CR1 & CR2 diode characteristics









Q3, Q4 Trench + field stop IGBT3





CR3 & CR4 SiC diode characteristics



DISCLAIMER

The information contained in the document (unless it is publicly available on the Web without access restrictions) is PROPRIETARY AND CONFIDENTIAL information of Microsemi and cannot be copied, published, uploaded, posted, transmitted, distributed or disclosed or used without the express duly signed written consent of Microsemi. If the recipient of this document has entered into a disclosure agreement with Microsemi, then the terms of such Agreement will also apply. This document and the information contained herein may not be modified, by any person other than authorized personnel of Microsemi. No license under any patent, copyright, trade secret or other intellectual property right is granted to or conferred upon you by disclosure or delivery of the information, either expressly, by implication, inducement, estoppels or otherwise. Any license under such intellectual property rights must be approved by Microsemi in writing signed by an officer of Microsemi.

Microsemi reserves the right to change the configuration, functionality and performance of its products at anytime without any notice. This product has been subject to limited testing and should not be used in conjunction with life-support or other mission-critical equipment or applications. Microsemi assumes no liability whatsoever, and Microsemi disclaims any express or implied warranty, relating to sale and/or use of Microsemi products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright or other intellectual property right. Any performance specifications believed to be reliable but are not verified and customer or user must conduct and complete all performance and other testing of this product as well as any user or customers final application. User or customer shall not rely on any data and performance specifications or parameters provided by Microsemi. It is the customer's and user's responsibility to independently determine suitability of any Microsemi product and to test and verify the same. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the User. Microsemi specifically disclaims any liability of any kind including for consequential, incidental and punitive damages as well as lost profit. The product is subject to other terms and conditions which can be located on the web at <http://www.microsemi.com/legal/tnc.asp>

Life Support Application

Seller's Products are not designed, intended, or authorized for use as components in systems intended for space, aviation, surgical implant into the body, in other applications intended to support or sustain life, or for any other application in which the failure of the Seller's Product could create a situation where personal injury, death or property damage or loss may occur (collectively "Life Support Applications").

Buyer agrees not to use Products in any Life Support Applications and to the extent it does it shall conduct extensive testing of the Product in such applications and further agrees to indemnify and hold Seller, and its officers, employees, subsidiaries, affiliates, agents, sales representatives and distributors harmless against all claims, costs, damages and expenses, and attorneys' fees and costs arising, directly or indirectly, out of any claims of personal injury, death, damage or otherwise associated with the use of the goods in Life Support Applications, even if such claim includes allegations that Seller was negligent regarding the design or manufacture of the goods.

Buyer must notify Seller in writing before using Seller's Products in Life Support Applications. Seller will study with Buyer alternative solutions to meet Buyer application specification based on Sellers sales conditions applicable for the new proposed specific part.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Microsemi:](#)

[APTGLQ40HR120CT3G](#)