

## Plastic label - US-EMLP (35X9) YE - 0828899

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Plastic label, Card, yellow, unlabeled, can be labeled with: THERMOMARK CARD, Mounting type: Adhesive, Lettering field: 35 x 9 mm



The illustration shows a version of the product



### Key Commercial Data

|                                      |          |
|--------------------------------------|----------|
| Packing unit                         | 1 pc     |
| Minimum order quantity               | 10 pc    |
| Weight per Piece (excluding packing) | 15.0 g   |
| Custom tariff number                 | 39199000 |
| Country of origin                    | Germany  |

### Technical data

#### Dimensions

|            |          |
|------------|----------|
| Length (b) | 34.65 mm |
| Width (a)  | 9 mm     |
| Height     | 0.5 mm   |

#### Ambient conditions

|                                 |                                 |
|---------------------------------|---------------------------------|
| Ambient temperature (operation) | -30 °C ... 80 °C                |
| Recommended storage conditions  | 20 °C / 50 % relative humidity. |

#### General

|                                        |                             |
|----------------------------------------|-----------------------------|
| Color                                  | yellow                      |
| Components                             | Silicone-free               |
| Flammability rating according to UL 94 | V0                          |
| Material                               | PVC                         |
| Wipe resistance                        | DIN EN 61010-1 (VDE 0411-1) |
| Number of individual labels            | 45                          |

## Plastic label - US-EMLP (35X9) YE - 0828899

### Technical data

#### General

|                                                                     |                                     |
|---------------------------------------------------------------------|-------------------------------------|
| Number of individual labels per row                                 | 3                                   |
| RoHS compliant                                                      | Yes                                 |
| Adhesive                                                            | Acrylic                             |
| Printability                                                        | Thermal transfer                    |
| Device                                                              | 5146464 THERMOMARK CARD             |
|                                                                     | 5146451 THERMOMARK CARD-US-MAG1     |
| Ink ribbon                                                          | 0801371 THERMOMARK-RIBBON 110-TC    |
| Test for substances that would hinder coating with paint or varnish | VW PV 3.10.7:2005-02                |
| Result                                                              | Test passed                         |
| Test specification weathering-resistance                            | Following ISO 4892-2:2013-03        |
| Test duration                                                       | 96 h                                |
| Wipe resistance test result                                         | Test passed                         |
| Salt spray test specification                                       | DIN EN 60068-2-11:2000-02           |
| Test duration                                                       | 96 h                                |
| Salt spray testing result                                           | Test passed                         |
| Alternating condensation climate with SO2 test specification        | DIN 50018:2013-05                   |
| Climate level                                                       | AHT 1.0 S                           |
| Cycles                                                              | 2                                   |
| Condensation test result                                            | Test passed                         |
| Wipe resistance of test specification inscriptions                  | DIN EN 61010-1 (VDE 0411-1):2011-07 |
| Result                                                              | Test passed                         |
| Foil strength                                                       | 500 µm                              |
| Adhesive strength                                                   | 250 µm                              |
| Marking mounting type                                               | Adhesive                            |

#### Standards and Regulations

|                                        |                             |
|----------------------------------------|-----------------------------|
| Wipe resistance                        | DIN EN 61010-1 (VDE 0411-1) |
| Flammability rating according to UL 94 | V0                          |

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 24190219 |
| eCl@ss 4.1 | 24190219 |
| eCl@ss 5.0 | 27141137 |
| eCl@ss 5.1 | 27141137 |
| eCl@ss 6.0 | 27141137 |
| eCl@ss 7.0 | 27141137 |

## Plastic label - US-EMLP (35X9) YE - 0828899

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 8.0 | 27149129 |
|------------|----------|

#### ETIM

|          |          |
|----------|----------|
| ETIM 2.0 | EC000761 |
| ETIM 3.0 | EC000761 |
| ETIM 4.0 | EC000761 |
| ETIM 5.0 | EC001288 |

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211811 |
| UNSPSC 7.0901 | 39121410 |
| UNSPSC 11     | 39121410 |
| UNSPSC 12.01  | 39121410 |
| UNSPSC 13.2   | 39121410 |

### Accessories

#### Accessories

#### Magazine

Magazine - THERMOMARK CARD-US-MAG1 - 5146451



Magazine for the THERMOMARK CARD printer, for accommodating US cards

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Phoenix Contact:

0828899