

XS9C2A2A1M12

inductive sensor XS9 40x40x70 - PBT - Sn25 mm - 24VDC - M12

Product availability: Stock - Normally stocked in distribution facility



Main

| | |
|------------------------------------|---|
| Commercial Status | Commercialised |
| Range of product | OsiSense XS |
| Series name | General purpose |
| Sensor type | Inductive proximity sensor |
| Product specific application | - |
| Sensor name | XS9 |
| Sensor design | Form 40 x 40 x 70 |
| Size | 70 mm |
| Body type | Fixed |
| Detector flush mounting acceptance | Non flush mountable |
| Material | Plastic |
| Enclosure material | PBT |
| Type of output signal | Analogue |
| Wiring technique | 3-wire |
| [Sn] nominal sensing distance | 0.98 in (25 mm) |
| Output circuit type | DC |
| Analogue output range | 0...10 V |
| Electrical connection | 4 pins M12 male connector |
| [Us] rated supply voltage | 24 V DC with reverse polarity protection |
| IP degree of protection | IP69K conforming to DIN 40050 IP65 conforming to IEC 60529 IP67 conforming to IEC 60529 |

Complementary

| | |
|-----------------------|-------------------------------|
| Detection face | 5 positions turret head |
| Front material | PBT |
| Operating zone | 0.08...1.06 in (2...27 mm) |
| Differential travel | 3...15% of Sr |
| Repeat accuracy | <= 3% of Sr |
| Linearity error | <= 3% of Sr |
| Status LED | 1 LED yellow for output state |
| Supply voltage limits | 15...36 V DC |
| Current consumption | 0...4 mA at no-load |
| Delay first up | <= 7.5 ms |
| Delay response | <= 6 ms |
| Delay recovery | <= 6 ms |
| Marking | CE |
| Height | 1.57 in (40 mm) |
| Length | 1.57 in (40 mm) |
| Width | 2.76 in (70 mm) |
| Product weight | 0.33 lb(US) (0.149 kg) |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

| | |
|---------------------------------------|---|
| Product certifications | CCC CSA UL |
| Ambient air temperature for operation | -13...158 °F (-25...70 °C) |
| Ambient air temperature for storage | -40...185 °F (-40...85 °C) |
| Vibration resistance | 25 gn amplitude = +/- 2 mm (f = 10...55 Hz) conforming to IEC 60068-2-6 |
| Shock resistance | 50 gn for 11 ms conforming to EN 60068-2-27 |

Ordering and shipping details

| | |
|-----------------------|---|
| Category | 22486 - SENSORS, PROXIMITY |
| Discount Schedule | DS2 |
| GTIN | 00785901335511 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 0.35 |
| Product availability | Stock - Normally stocked in distribution facility |
| Returnability | Y |

Contractual warranty

| | |
|--------|-----------|
| Period | 18 months |
|--------|-----------|

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Schneider Electric:](#)

[XS9C2A2A1M12](#)