

# XCNT2145G11

limit switch XCNT - th.plastic roller lever  
var.length - 1NC+1NO - snap - Pg11

Product availability: Non-Stock - Not normally stocked in distribution facility



## Main

|                               |                                                            |
|-------------------------------|------------------------------------------------------------|
| Commercial Status             | Commercialised                                             |
| Range of product              | OsiSense XC                                                |
| Series name                   | Standard format                                            |
| Product or component type     | Limit switch                                               |
| Device short name             | XCNT                                                       |
| Sensor design                 | Compact                                                    |
| Body type                     | Fixed                                                      |
| Head type                     | Rotary head                                                |
| Material                      | Plastic                                                    |
| Body material                 | Plastic                                                    |
| Head material                 | Plastic                                                    |
| Fixing mode                   | By the body                                                |
| Movement of operating head    | Rotary                                                     |
| Type of operator              | Spring return roller lever thermoplastic (variable length) |
| Type of approach              | Lateral approach 2 directions                              |
| Cable entry                   | 2 entries tapped for Pg 11 cable gland                     |
| Number of poles               | 2                                                          |
| Contacts type and composition | 1 NC + 1 NO                                                |
| Contacts operation            | Snap action                                                |

## Complementary

|                                        |                                                                                                                                                                             |
|----------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Switch actuation                       | By 30° cam                                                                                                                                                                  |
| Electrical connection                  | Screw-clamp open terminals, clamping capacity: 1 x 0.34...2 x 1.5 mm²                                                                                                       |
| Contacts insulation form               | Zb                                                                                                                                                                          |
| Positive opening                       | With                                                                                                                                                                        |
| Positive opening minimum torque        | 1.33 lbf.in (0.15 N.m)                                                                                                                                                      |
| Minimum torque for tripping            | 0.88 lbf.in (0.1 N.m)                                                                                                                                                       |
| Maximum actuation speed                | 4.92 ft/s (1.5 m/s)                                                                                                                                                         |
| Contact code designation               | R300, DC-13 (Ue = 250 V, Ie = 0.1 A) conforming to EN/IEC 60947-5-1 appendix A<br>A300, AC-15 (Ue = 240 V, Ie = 3 A), Ithe = 10 A conforming to EN/IEC 60947-5-1 appendix A |
| [Ui] rated insulation voltage          | 300 V conforming to CSA C22.2 No 14<br>500 V degree of pollution 3 conforming to IEC 60947-1<br>300 V conforming to UL 508                                                  |
| [Uimp] rated impulse withstand voltage | 6 kV conforming to IEC 60947-1<br>6 kV conforming to IEC 60664                                                                                                              |
| Short circuit protection               | 10 A cartridge fuse type gG                                                                                                                                                 |
| Mechanical durability                  | 10000000 cycles                                                                                                                                                             |
| Width                                  | 2.31 in (58.8 mm)                                                                                                                                                           |
| Height                                 | 4.31 in (109.6 mm)                                                                                                                                                          |
| Depth                                  | 1.66 in (42.2 mm)                                                                                                                                                           |

## Environment

|                                            |                                                                 |
|--------------------------------------------|-----------------------------------------------------------------|
| Shock resistance                           | 35 gn (duration = 11 ms) conforming to IEC 60068-2-27           |
| Vibration resistance                       | 25 gn (f = 10...500 Hz) conforming to IEC 60068-2-6             |
| IP degree of protection                    | IP65 conforming to IEC 60529                                    |
| IK degree of protection                    | IK04 conforming to EN 50102                                     |
| Class of protection against electric shock | Class II conforming to NF C 20-030<br>Class II                  |
| Ambient air temperature for operation      | -13...158 °F (-25...70 °C)                                      |
| Ambient air temperature for storage        | -40...158 °F (-40...70 °C)                                      |
| Protective treatment                       | TC                                                              |
| Product certifications                     | CCC<br>CSA<br>UL                                                |
| Standards                                  | EN/IEC 60204-1<br>EN/IEC 60947-5-1<br>UL 508<br>CSA C22.2 No 14 |

## Ordering and shipping details

|                       |                                                           |
|-----------------------|-----------------------------------------------------------|
| Category              | 22435 - LIMIT SWITCHES,TYPE XCM                           |
| Discount Schedule     | T                                                         |
| GTIN                  | 003389119047128                                           |
| Nbr. of units in pkg. | 10                                                        |
| Package weight(Lbs)   | 0.29                                                      |
| Product availability  | Non-Stock - Not normally stocked in distribution facility |
| Returnability         | N                                                         |
| Country of origin     | ID                                                        |

## Offer Sustainability

|                               |                                                                                       |
|-------------------------------|---------------------------------------------------------------------------------------|
| Sustainable offer status      | Not Green Premium product                                                             |
| RoHS                          | Compliant - since 1024 - <a href="#">Schneider Electric declaration of conformity</a> |
| REACH                         | Reference not containing SVHC above the threshold                                     |
| Product environmental profile | Available <a href="#">Download Product Environmental</a>                              |

## Contractual warranty

|        |           |
|--------|-----------|
| Period | 18 months |
|--------|-----------|

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Schneider Electric:](#)

[XCNT2145G11](#)