

Interface module - VIP-3/PT/PDM-2/16 - 2903797

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



VARIOFACE module, with two equipotential busbars (P1, P2) for potential distribution, for mounting on NS 35 rails. Module width: 41.9 mm



Key Commercial Data

Packing unit	1 pc
Weight per Piece (excluding packing)	126.5 g
Custom tariff number	85369010
Country of origin	United States

Technical data

Dimensions

Width	41.9 mm
Height	75.8 mm
Depth	63 mm

Ambient conditions

Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C

General

Nominal voltage U_N	250 V AC/DC
Max. current carrying capacity per branch	15 A
Total current	30 A (per potential)
Potential connections	Per potential (P1, P2) 2 power/8 distributor terminal blocks
Mounting position	any
Standards/regulations	IEC 60664
	DIN EN 50178

Interface module - VIP-3/PT/PDM-2/16 - 2903797

Technical data

General

	IEC 62103
Degree of pollution	2
Overvoltage category	III

Connection data, supply

Connection method	Push-in-/Spring-cage connection
Stripping length	15 mm
Conductor cross section solid	0.25 mm ² ... 6 mm ²
Conductor cross section flexible	0.25 mm ² ... 4 mm ²
Conductor cross section AWG	24 ... 10
Number of connections	2

Connection data, distribution

Connection method	Push-in connection
Stripping length	8 mm
Conductor cross section solid	0.14 mm ² ... 2.5 mm ²
Conductor cross section flexible	0.14 mm ² ... 2.5 mm ²
Conductor cross section AWG	26 ... 14
Number of connections	16

Standards and Regulations

Connection in acc. with standard	CSA
Standards/regulations	IEC 60664
	DIN EN 50178
	IEC 62103
Degree of pollution	2
Overvoltage category	III

Classifications

eCl@ss

eCl@ss 4.0	27250313
eCl@ss 4.1	27250313
eCl@ss 5.0	27250313
eCl@ss 5.1	27250313
eCl@ss 6.0	27242608
eCl@ss 7.0	27242608
eCl@ss 8.0	27141152
eCl@ss 9.0	27141152

Interface module - VIP-3/PT/PDM-2/16 - 2903797

Classifications

ETIM

ETIM 3.0	EC001604
ETIM 4.0	EC001604
ETIM 5.0	EC002780

UNSPSC

UNSPSC 6.01	30211824
UNSPSC 7.0901	39121421
UNSPSC 11	39121421
UNSPSC 12.01	39121421
UNSPSC 13.2	39121421

Approvals

Approvals

Approvals

CSA / UL Recognized / cUL Recognized / EAC / cULus Recognized

Ex Approvals

Approvals submitted

Approval details

CSA 	
mm²/AWG/kcmil	26-14
Nominal current I _N	15 A
Nominal voltage U _N	250 V

Interface module - VIP-3/PT/PDM-2/16 - 2903797

Approvals

UL Recognized 	
mm²/AWG/kcmil	26-14
Nominal current I _N	15 A
Nominal voltage U _N	250 V


cUL Recognized 	
mm²/AWG/kcmil	26-14
Nominal current I _N	15 A
Nominal voltage U _N	250 V

EAC


cULus Recognized 
--

Drawings

Circuit diagram



Dimensional drawing



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Phoenix Contact:

2903797