

145 Adams Avenue, Hauppauge, NY 11788 USA Tel: (631) 435-1110 • Fax: (631) 435-1824

Manufacturers of World Class Discrete Semiconductors

TIP110 TIP111 TIP112 NPN TIP115 TIP116 TIP117 PNP

SILICON POWER DARLINGTON COMPLEMENTARY TRANSISTORS

**JEDEC TO-220 AB CASE** 

## **DESCRIPTION**

The CENTRAL SEMICONDUCTOR TIP110, TIP115 series types are Complementary Silicon Power Darlington Transistors designed low speed switching and amplifier applications.

## MAXIMUM RATINGS (T<sub>C</sub> = 25°C)

		TIP110	TIP111	TIP112	
	<u>SYMBOL</u>	<u>TIP115</u>	<u>TIP116</u>	<u>TIP117</u>	<u>UNITS</u>
Collector-Base Voltage	V <sub>CBO</sub>	60	80	100	٧
Collector-Emitter Voltage	V <sub>CEO</sub>	80	80	100	V
Emitter-Base Voltage	$V_{EBO}$	5.0	5.0	5.0	V
Collector Current	lc		2.0		Α
Collector Current (Peak)	ICM		4.0		Α
Base Current	l <sub>B</sub>		50		mA
Power Dissipation	$P_{D}$		50		W
Operating and Storage					
Junction Temperature	$T_{J}, T_{stg}$		-65 to +150	)	οС
Thermal Resistance	θ <sub>JC</sub>		2.5		oC/W

## ELECTRICAL CHARACTERISTICS ( $T_C = 25^{\circ}$ C unless otherwise noted)

		TIP110			TIP1	12	
		<u>TIP115</u>	<u>TIP</u>	<u>TIP116</u>		<u>TIP117</u>	
SYMBOL	TEST CONDITIONS	MIN MA	AX MIN	MAX	MIN	MAX	<u>UNITS</u>
ICBO	V <sub>CB</sub> =60V	1.	.0	-		-	mA
СВО	$V_{CB} = 80V$		-	1.0		-	mA
I <sub>СВО</sub>	$V_{CB} = 100V$		•	-		1.0	mA
ICEO	V <sub>CE</sub> =30V	2.	.0	-		-	mA
ICEO	V <sub>CE</sub> =40V	•	-	2.0		-	mA
ICEO	V <sub>CE</sub> =50V		-	~		2.0	mΑ
I <sub>EBO</sub>	V <sub>BE</sub> = 5.0V	2.	.0	2.0		2.0	mA
BVCEO	$I_C = 30 \text{mA}$	60	80		100		V
V <sub>CE(SAT)</sub>	$I_C = 2.0A$ , $I_B = 8.0mA$	2.	.5	2.5		2.5	V
V <sub>BE(ON)</sub>	$V_{CE} = 4.0V, I_{C} = 2.0A$	2.	.8	2.8		2.8	V
ηŁΕ	$V_{CE} = 4.0V, I_{C} = 1.0A$	1000	1000		1000		
hFE	$V_{CE} = 4.0V, I_{C} = 2.0A$	500	500		500		
f <sub>T</sub>	$V_{CE} = 10V$ , $I_{C} = 750$ mA, $f = 1.0$ MHz	25	25		25		MHz

(Continued on reverse side)

# $\underline{ELECTRICAL\ CHARACTERISTICS} \quad (T_C = 25^{o}C\ unless\ otherwise\ noted)$

		<u>MIN</u>	MAX	<u>UNITS</u>
Cob	$V_{CB} = 10V$ , $I_E = 0$ , $f = 0.1MHz$			
	TIP110, TIP111, TIP112		100	pF
C <sub>ob</sub>	$V_{CB} = 10V$ , $I_E = 0$ , $f = 0.1MHz$			
	TIP115, TIP116, TIP117		200	pF



145 Adams Avenue Hauppauge, NY 11788 USA Tel: (631) 435-1110 • Fax: (631) 435-1824 www.centralsemi.com

#### **OUTSTANDING SUPPORT AND SUPERIOR SERVICES**



#### PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- · Inventory bonding
- · Consolidated shipping options

- · Custom bar coding for shipments
- · Custom product packing

#### **DESIGNER SUPPORT/SERVICES**

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free guick ship samples (2<sup>nd</sup> day air)
- Online technical data and parametric search
- SPICE models
- · Custom electrical curves
- · Environmental regulation compliance
- · Customer specific screening
- · Up-screening capabilities

- Special wafer diffusions
- PbSn plating options
- Package details
- Application notes
- · Application and design sample kits
- Custom product and package development

#### REQUESTING PRODUCT PLATING

- 1. If requesting Tin/Lead plated devices, add the suffix "TIN/LEAD" to the part number when ordering (example: 2N2222A TIN/LEAD).
- 2. If requesting Lead (Pb) Free plated devices, add the suffix "PBFREE" to the part number when ordering (example: 2N2222A PBFREE).

#### **CONTACT US**

#### Corporate Headquarters & Customer Support Team

Central Semiconductor Corp. 145 Adams Avenue Hauppauge, NY 11788 USA

Main Tel: (631) 435-1110 Main Fax: (631) 435-1824

Support Team Fax: (631) 435-3388

www.centralsemi.com

Worldwide Field Representatives: www.centralsemi.com/wwreps

**Worldwide Distributors:** 

www.centralsemi.com/wwdistributors

For the latest version of Central Semiconductor's **LIMITATIONS AND DAMAGES DISCLAIMER**, which is part of Central's Standard Terms and Conditions of sale, visit: <a href="https://www.centralsemi.com/terms">www.centralsemi.com/terms</a>

www.centralsemi.com (001)



# Product End of Life Notification

PDN ID:	PDN01042
Notification Date:	8/15/16
Last Buy Date:	2/15/17
Last Shipment Date	8/15/17

Summary: The TIP110 series of NPN and PNP Darlington power transistors, with the exception of TIP112 and TIP117, is discontinued and now classified as End of Life (EOL).

Although Central Semiconductor Corp. makes every effort to continue to produce devices that have been proclaimed EOL (End of Life) by various manufacturers, it is an accepted industry practice to discontinue certain devices when customer demand falls below a minimum level of sustainability. Accordingly, the following product(s) have been transitioned to End of Life status as part of Central's Product Management Process. Any replacement product will be noted below. The effective date for placing the last purchase order will be six(6) months from the date of this notice and twelve(12) months from the notice date for final shipments; this may be extended if inventory is available.

Central Part Number	Replacement	
TIP110	TIP112	
TIP111	TIP112	
TIP115	TIP117	
TIP116	TIP117	

Central would be happy to assist you by providing additional information or technical data to help locate an alternate source if we have no replacement available. Please email your requests to engineering@centralsemi.com.

DISCLAIMER: This End of Life (EOL) notification is in accordance with JEDEC standard JESD48 - Product Discontinuance. Central Semiconductor Corp. will make every effort to offer life-time buy (LTB) opportunities and/or offer replacement devices to existing customers for discontinued devices, however, one or both may not be possible for all devices. Please contact your local Central Semiconductor sales representative for LTB opportunities/additional information.

CCC785 REV 002

# **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Central Semiconductor: TIP117 TIP112 SL TIP112