



- ① HOUSING WILL ACCOMODATE FLEXIBLE FLAT CABLE .050 OR .062 WIDE CONDUCTORS (CABLE .015 MAX THK) AND/OR #22-32 AWG WIRE WITH INSULATION RANGE OF .045 TO .069 DIA.
- ② MOLDED "AMP" TRADEMARK, IN THIS AREA
- ③ PART NO. AND DATE CODE TO BE LASER MARKED
- ④ DETENTS: 6,8,10,12 & 18 POSN,(1) DETENT LOCATED AS FOLLOWS:  
6 & 8 POSN-  $\phi$  OF THRID CIRCUIT FROM RIGHT  
10 & 12 POSN-  $\phi$  OF FOURTH CIRCUIT FROM RIGHT  
18 POSN-  $\phi$  OF SIXTH CIRCUIT FROM RIGHT  
20 POSN & ABOVE- (2) DETENTS LOCATED AS SHOWN
- ⑤ CAVITY IDENT NO. TO BE LASER MARKED (SEE TABLE)
- ⑥ INDICATES POSITION 1, SURFACE TEXTURE CONTRAST'S WITH REST OF HOUSING
- ⑦ THIS HOUSING WILL MATE WITH FFC PIN HOUSING
- ⑧ OBSOLETE PART NUMBER
- ⑨ SUPERSEDED BY AS MOLDED PART NUMBER.
- ⑩ GLASS-FILLED NYLON, BLACK, UL V-0.
- ⑪ OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

⑧	4-88179-1	12-15-22	2-5-10	1.350	1.234	1.140	22	⑧	4-88179-2
⑧	3-88179-9			.650	.534	.440	8	⑧	4-88179-0
⑧	3-88179-7	16-20-25-30	2-5-10-14	1.750	1.634	1.540	30	⑧	3-88179-8
⑨	3-88179-5	18-25-30-34	2-5-10-16	1.950	1.834	1.740	34	⑧	3-88179-6
①	3-88179-3	7-12	2-5	.850	.734	.640	12	⑧	3-88179-4
⑧	3-88179-1	4-6	2	.550	.434	.340	6	⑧	3-88179-2
⑧	2-88179-9	6-10	2-4	.750	.634	.540	10	⑧	3-88179-0
⑧	2-88179-7			3.750	3.634	3.540	70	⑧	2-88179-8
⑧	2-88179-5			3.150	3.034	2.940	58	⑧	2-88179-6
⑧	2-88179-3	23-25-30-35-40-44	2-5-10-15-20-21	2.450	2.334	2.240	44	⑧	2-88179-4
⑧	2-88179-1	21-25-30-35-40	2-5-10-15-19	2.250	2.134	2.040	40	⑧	2-88179-2
⑧	1-88179-9	19-25-30-36	2-5-10-17	2.050	1.934	1.840	36	①	2-88179-0
⑧	1-88179-7			1.650	1.534	1.440	28	⑧	1-88179-8
⑧	1-88179-5	14-20-26	2-5-12	1.550	1.434	1.340	26	①	1-88179-6
①	1-88179-3	13-20-24	2-5-11	1.450	1.334	1.240	24	⑧	1-88179-4
①	1-88179-1	26-30-35-40-45-50	2-5-10-15-20-24	2.750	2.634	2.540	50	⑧	1-88179-2
①	88179-9	10-15-18	2-5-8	1.150	1.034	.940	18	⑧	1-88179-0
⑧	88179-7	34-40-45-50-55-60-66	2-5-10-15-20-25-32	3.550	3.434	3.340	66	①	88179-8
⑧	88179-3	20-25-30-35-38	2-5-10-15-18	2.150	2.034	1.940	38	⑧	88179-6
①	88179-2	11-15-20	2-5-9	1.250	1.134	1.040	20	⑧	88179-5
⑧	88179-1			3.250	3.134	3.040	60	⑧	88179-4

LASER MARKED PART NUMBER	FAR SIDE CAVITY POSN NO.	NEAR SIDE STAMPED	C	B	A	NO OF POS'N	AS MOLDED PART NUMBER
THIS DRAWING IS A CONTROLLED DOCUMENT. <span style="float: right;">DIN KATE HELM 11/07/88</span> DIMENSIONS: INCHES <span style="float: right;">CHK D.L.ROCKER 3-6-89</span> TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ± - 1 PLC ± - 2 PLC ± - 3 PLC ± .005 4 PLC ± - ANGLES ± - MATERIAL $\Delta$ 10 FINISH - WEIGHT - CUSTOMER DRAWING							
HOUSING,RCPT,DBL ROW WITH DETENTS,.100 CL.				APVD - PRODUCT SPEC - APPLICATION SPEC - SIZE A1 CAGE CODE 00779 DRAWING NO. 88179 RESTRICTED TO - SCALE 3:1 SHEET 1 OF 1 REV AR3			

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[2-88179-2](#)