

STRAIGHT PLUG CRIMP TYPE


CABLE 5/50 S

R141.082.000

Series : BNC







All dimensions are in mm.

 1

COMPONENTS	MATERIALS	PLATING (μm)
BODY	BRASS	NICKEL 2
CENTER CONTACT	BRASS	GOLD 0.5 OVER NICKEL 2
OUTER CONTACT	-	-
INSULATOR	PTFE	
GASKET	SILICONE RUBBER	
OTHERS PARTS	BRASS	NICKEL 2
-	-	₩
· -	_	_

Issue: 0619 D

In the effort to improve our products, we reserve the right to make changes judged to be necessary.



STRAIGHT PLUG CRIMP TYPE

CABLE 5/50 S

R141.082.000

Series: BNC

PACKAGING

Standard	Unit	Other
100	'W' option	Contact us

ELECTRICAL CHARACTERISTICS

- (

Impedance

50 Ω

Frequency

0-4 GHz

VSWR

 $1.3 + 0.0000 \times F(GHz)$ Maxi

Insertion loss

0.115 √F(GHz) dB Maxi

RF leakage

57 - F(GHz)) dB Maxi 500 Veff Maxi

Voltage rating Dielectric withstanding voltage

1500 Veff mini

Insulation resistance

5000 $M\Omega$ mini

MECHANICAL CHARACTERISTICS

Center contact retention

Axial force – Mating end

27 N mini

Axial force – Opposite end

27 N mini

Torque

NA N.cm mini

Recommended torque

Mating

NA N.cm

Panel nut

NA N.cm

Clamp nut

NA N.cm

A/F clamp nut

0,0000 mm

Mating life

500 Cycles mini

Weight

9,0000 g

ENVIRONMENTAL

Operating temperature

-65/+165 ° C

Hermetic seal

NA Atm.cm3/s

Panel leakage

NA

SPECIFICATION

CABLE ASSEMBLY

Stripping	a	b	С	d	е	f
mm	4,00	8,50	15,0	0,00	11,0	0,00

Assembly instruction:

Crimp 02

Recommended cable(s)

RG 58

RG 141

KX 15

ECO 142

Characteristics indicated on this data sheet are those that can be achieved with the highest performance cable. Intrinsic limitations of the cable may diminish the performance of the assembly

Cable retention

- pull off

90 N mini

- torque

NA N.cm

TOOLING

Part Number	Description	Hexagon
	-	,
R282.293.000	CRIMPING TOOL	-
R282.223.000	CRIMPING TOOL	1.73-5.41
R282.235.011	CRIMPING DIES	1.73-5.41

OTHER CHARACTERISTICS

Issue: 0619 D

In the effort to improve our products, we reserve the right to make changes judged to be



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Radiall:

R141082000