

LARISA-O-CLIP16

~40° x 20° oval beam. Clip fastening for 1.6 mm thick PCB.

TECHNICAL SPECIFICATIONS:

Dimensions	9.9 mm
Height	7.5 mm
Fastening	clips
ROHS compliant	yes ⓘ


MATERIAL SPECIFICATIONS:

Component	Type	Material	Colour	Finish
LARISA-O	Single lens	PMMA		
LARISA-HOLDER-CLIP16	Holder	PC		

ORDERING INFORMATION:

Component		Qty in box	MOQ	MPQ	Box weight (kg)
CP12943_LARISA-O-CLIP16	Single lens	10000	300	100	6.6
» Box size: 300 x 250 x 250 mm					









PHOTOMETRIC DATA (MEASURED):





LED XB-D
FWHM 39.0 + 21.0°
Efficiency 80 %
Peak intensity 2.200 cd/lm
LEDs/each optic 1
Light colour White
Required components:





LED XD16
FWHM 40.0 + 20.0°
Efficiency 75 %
Peak intensity 2.100 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED XP-G
FWHM 39.0 + 25.0°
Efficiency 83 %
Peak intensity 2.050 cd/lm
LEDs/each optic 1
Light colour White
Required components:




LED XQ-E HD
FWHM 40.0 + 17.0°
Efficiency 82 %
Peak intensity 2.800 cd/lm
LEDs/each optic 1
Light colour White
Required components:




PHOTOMETRIC DATA (MEASURED):




LED XQ-E HI
FWHM 43.0 + 14.0°
Efficiency 74 %
Peak intensity 3.200 cd/lm
LEDs/each optic 1
Light colour White
Required components:





LED H35B0 (LEMWA32)
FWHM 38.0 + 22.0°
Efficiency 82 %
Peak intensity 2.200 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED H35C0 (LEMWA33)
FWHM 39.0 + 27.0°
Efficiency 81 %
Peak intensity 1.840 cd/lm
LEDs/each optic 1
Light colour White
Required components:





LED LUXEON A
FWHM 39.0 + 26.0°
Efficiency 81 %
Peak intensity 1.900 cd/lm
LEDs/each optic 1
Light colour White
Required components:





PHOTOMETRIC DATA (MEASURED):





LED LUXEON C
FWHM 40.0 + 18.0°
Efficiency 79 %
Peak intensity 2.600 cd/lm
LEDs/each optic 1
Light colour White
Required components:





LED LUXEON Rebel
FWHM 40.0 + 18.0°
Efficiency 84 %
Peak intensity 2.700 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED LUXEON Rebel ES
FWHM 39.0 + 25.0°
Efficiency 82 %
Peak intensity 1.900 cd/lm
LEDs/each optic 1
Light colour White
Required components:




LED LUXEON Rebel Plus
FWHM 40.0 + 19.0°
Efficiency 83 %
Peak intensity 2.600 cd/lm
LEDs/each optic 1
Light colour White
Required components:





PHOTOMETRIC DATA (MEASURED):





LED LUXEON Z
FWHM 41.0 + 14.0°
Efficiency 81 %
Peak intensity 3.540 cd/lm
LEDs/each optic 1
Light colour White
Required components:





LED LUXEON Z ES
FWHM 40.0 + 18.0°
Efficiency 86 %
Peak intensity 2.800 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED NCSxx19A
FWHM 41.0 + 19.0°
Efficiency 81 %
Peak intensity 2.250 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED NVSxx19A
FWHM 40.0 + 24.0°
Efficiency 79 %
Peak intensity 1.850 cd/lm
LEDs/each optic 1
Light colour White
Required components:





PHOTOMETRIC DATA (MEASURED):

OSRAM

Opto Semiconductors



LED Duris S5 (2 chip)
FWHM 26.0 + 41.0°
Efficiency 79 %
Peak intensity 1.800 cd/lm
LEDs/each optic 1
Light colour White
Required components:



OSRAM

Opto Semiconductors



LED OSLOM Square EC
FWHM 40.0 + 22.0°
Efficiency 78 %
Peak intensity 1.950 cd/lm
LEDs/each optic 1
Light colour White
Required components:



OSRAM

Opto Semiconductors



LED OSLOM SSL 150
FWHM 39.0 + 19.0°
Efficiency 84 %
Peak intensity 2.900 cd/lm
LEDs/each optic 1
Light colour White
Required components:



OSRAM

Opto Semiconductors


LED OSLOM SSL 80
FWHM 40.0 + 17.0°
Efficiency 77 %
Peak intensity 2.530 cd/lm
LEDs/each optic 1
Light colour White
Required components:



PHOTOMETRIC DATA (SIMULATED):



LED XP-E
FWHM 39.0 + 17.0°
Efficiency 89 %
Peak intensity cd/m
LEDs/each optic 1
Light colour White
Required components:



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Ledil:

[CP12943_LARISA-O-CLIP16](#)