

Magnetically Compensated Choke, 1-phase, high design



See below:

Approvals and Compliances

Description

- Current compensated choke
- 1-phase choke
- THT-terminals
- Inductor vertically positioned in housing

Applications

- Attenuation of common mode interferences
- Designed for 230/400 VAC applications
- Chopper amplifiers
- DC drives and stepper motor controls
- Switching power supplies

Weblinks

pdf datasheet, html-datasheet, General Product Information, Distributor-Stock-Check, Detailed request for product, SPICE Library

| lechnical Data | |
|---------------------------|-------------------------|
| Rated voltage | up to 440 VAC |
| Rated Current | 0.6 - 6.3 A @ Ta 40 °C |
| Rated inductance | 0.6 - 50mH, Tol30% +50% |
| Power Operating Frequency | 50 - 400 Hz |
| Terminal Type | THT |
| Weight | 3 - 30g |
| Material: Housing | UL 94V-0 |
| Sealing Compound | UL 94V-0 |

| Test Voltage | 1.8 kV, 50 Hz, 1 min, winding to winding |
|---------------------------|--|
| Isolation Voltage | 2kV eff., winding to ambient |
| Climatic Category | 25/100/21 acc. to IEC 60068-1 |
| Allowable Operation Temp. | -25°C to 100°C |

Approvals and Compliances

Detailed information on product approvals, code requirements, usage instructions and detailed test conditions can be looked up in Details about Approvals

SCHURTER products are designed for use in industrial environments. They have approvals from independent testing bodies according to national and international standards. Products with specific characteristics and requirements such as required in the automotive sector according to IATF 16949, medical technology according to ISO 134485 or in the aerospace industry can be offered exclusively with customer-specific, individual agreements by SCHURTER.

Approvals

The approval mark is used by the testing authorities to certify compliance with the safety requirements placed on electronic products. Approval Reference Type: DFKH

Approval Logo Certificates **Certification Body** Description UL **UL** Approvals UL File Number: C**FL** us

Application standards

Application standards where the product can be used

Organization Description Design Standard Designed for applications acc. IEC/UL 60950 IEC 60950-1 includes the basic requirements for the safety of information IEC technology equipment.

Compliances


The product complies with following Guide Lines


| Identification | Details | Initiator | Description |
|----------------|------------------------------|-------------|---|
| C€ | CE declaration of conformity | SCHURTER AG | The CE marking declares that the product complies with the applicable requirements laid down in the harmonisation of Community legislation on its affixing in accordance with EU Regulation 765/2008. |
| ROHS | RoHS | SCHURTER AG | EU Directive RoHS 2011/65/EU |
| © | China RoHS | SCHURTER AG | The law SJ $/$ T 11363-2006 (China RoHS) has been in force since 1 March 2007. It is similar to the EU directive RoHS. |
| REACH | REACH | SCHURTER AG | On 1 June 2007, Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorization and Restriction of Chemicals 1 (abbreviated as "REACH") entered into force. |


Dimension [mm]


Case 50-2, 51-2, 52-2

Case 09-2











Case 19-2









Impedance curves


DFKH-14-xxxx



DFKH-22-xxxx



DFKH-31-xxxx



All Variants

| I _n [A] | L _n [mH] | R _{cu} [mΩ] | Tripped Power Dissipation [W] | f _{RES} [MHz] | Weight [g] | Housings | Packing unit [pcs.] | Order Number |
|--------------------|---------------------|-------------------------|-------------------------------|---------------------------|------------|----------|---------------------|--------------|
| 0.6 | 11 | 600 | 0.5 | 0.5 | 3 g | 50-2 | 100 | DFKH-14-0001 |
| 0.6 | 50 | 1200 | 0.9 | 0.15 | 22 g | 19-2 | 70 | DFKH-31-0001 |
| 1 | 20 | 500 | 1 | 0.25 | 10 g | 09-2 | 50 | DFKH-22-0002 |
| 1 | 33 | 700 | 1.4 | 0.25 | 30 g | 19-2 | 70 | DFKH-31-0002 |
| 1 | 4 | 250 | 0.5 | 1.2 | 3 g | 51-2 | 100 | DFKH-14-0002 |
| 1.4 | 27 | 470 | 1.8 | 0.3 | 30 g | 19-2 | 70 | DFKH-31-0003 |
| 2 | 1 | 65 | 0.5 | 2.5 | 3 g | 52-2 | 100 | DFKH-14-0003 |
| 2 | 6 | 150 | 1.3 | 0.6 | 10 g | 09-2 | 50 | DFKH-22-0003 |
| 2 | 6.8 | 150 | 1.2 | 0.5 | 30 g | 19-2 | 70 | DFKH-31-0005 |
| 2.5 | 5.6 | 110 | - | - | 30 g | 19-2 | 70 | DFKH-31-0006 |
| 4 | 1.5 | 36 | 1.2 | 1.5 | 10 g | 09-2 | 50 | DFKH-22-0004 |
| 4 | 3.3 | 58 | 1.8 | 0.8 | 30 g | 19-2 | 70 | DFKH-31-0007 |
| 6 | 2 | 24 | 1.8 | 1.2 | 30 g | 19-2 | 70 | DFKH-31-0008 |
| 6.3 | 0.6 | 15 | 1.4 | 2.5 | 10 g | 09-2 | 50 | DFKH-22-0005 |

Most Popular.

Availability for all products can be searched real-time:https://www.schurter.com/en/Stock-Check/Stock-Check-SCHURTER

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Schurter:

<u>DFKH-14-0003</u> <u>DFKH-14-0001</u> <u>DFKH-14-0002</u> <u>DFKH-22-0003</u> <u>DFKH-22-0002</u> <u>DFKH-31-0008</u> <u>DFKH-31-0008</u> <u>DFKH-31-0006</u> <u>DFKH-31-0006</u>